NOT MEASUREMENT SENSITIVE

MIL-DTL-15665/123
29 July 2022

DETAIL SPECIFICATION SHEET

COLLAR INSIGNIA, CHIEF MASTER SERGEANT OF THE AIR FORCE, U.S. SPACE FORCE

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-15665.



MATERIAL: Red Brass 85/15 (UNS Alloy No. C- 230)

FINISH: Nickel Plated, Mirror-like Polished and shall match The Institute of Heraldry Metal Finish Chip Number 16

DIMENSIONS:
HEIGHT (Overall): 1 inch (REF)
WIDTH (Overall): 7/8 inch (REF)
THICKNESS: 0.060 inch ± 0.010 inch

ATTACHING DEVICE:
-1: The attaching device shall consist of two prongs with wing type clutch.

-2: The two prongs shall be fused or soldered on the horizontal centerline and centered on the right and left outer rim.

AMSC N/A FSC 8455

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:08Z
Check the source to verify that this is the current version before use.

NOTES:

1. The term (REF) refers to measurements taken from the Government furnished hub or die.

2. The reverse of the insignia shall be dapped to a radius of 1-5/8 inches ± 1/8 inch.

3. Pierced areas shall be as indicated.

Custodian:
Army - IH
Air Force - 11

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2022-138)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:08Z
Check the source to verify that this is the current version before use.