NOT MEASUREMENT SENSITIVE

MIL-DTL-15665/126
9 September 2024

DETAIL SPECIFICATION SHEET

INSIGNIA, DRESS COLLAR, OFFICER, U.S. MARINE CORPS

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-15665.


-1



LEFT HAND ASSEMBLED



EAGLE & GLOBE LEFT



ANCHOR LEFT



ANCHOR/ROPE LEFT



LANDMASS LEFT

-2



RIGHT HAND ASSEMBLED



EAGLE & GLOBE RIGHT



ANCHOR RIGHT



FOULED/ROPE RIGHT



LANDMASS RIGHT

DASH NO.
-1: Collar, Dress, Silver/Gold, Left
-2: Collar, Dress, Silver/Gold, Right

MATERIAL: Red Brass 85/15 (UNS Alloy No. C- 230)

FINISH:
-1, -2: Eagle, Globe and Rope - Nickel Plated, Rhodium Plated, Brightly Polished.

-1, -2: Land Mass and Anchor - 24K Gold Plated, Mirror-like Polished and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 6.

AMSC N/A

FSC 8455

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:09Z
Check the source to verify that this is the current version before use.

DIMENSIONS:
HEIGHT (Overall):
Eagle/Globe: 1-1/8 inches (REF)
Fouled Anchor: 1-3/8 inches (REF)
WIDTH (At wing tips and anchor flukes):
Eagle/Globe: 1-3/16 inches (REF)
Fouled Anchor: 7/8 inches (REF)
THICKNESS: (At eagle head and anchor flukes)
Eagle/Globe: 0.026 ± 0.005
Fouled Anchor: 0.026 ± 0.005
Land Mass: 0.026 ± 0.005

ATTACHING DEVICE:

1. The attaching device shall be a screw post with nut.

2. The screw post shall be 3/8 inch ± 1/32 inch long, 1/8 inch in diameter and shall have a No. 5-40 UNC-2A thread. The thumb nut shall be 0.625 inch + 0.010 inch or 0.500 inch ± 0.010 inch in diameter and shall have a No. 5-40 UNC-2B thread.

3. The screw post shall be soldered or electronically fused to the insignia in the center of the anchor on the registering pad as indicated.

4. The registering prong shall be 3/16 inch ± 1/64 inch in length and 0.032 inch ± 0.002 inch in diameter. The prong shall be fused or soldered on the vertical center line on the back of the eagle's breast.

ROPE:

1. The rope for shall be 2 wires at .018 ± .005 diameter twisted at 26 ± 5 twists per 1” and finished at .034 ± .005

2. The rope will be soldered to the anchor as indicated.

LAND MASS:

1. Manufacturer will create a blanking tool for the land mass shape as indicated on TIOH Drawing B-2-0081.

2. Land mass shall be dapped to match the radius of the globe. The land mass shall be soldered to the globe as indicated.

NOTES:

1. The term (REF) refers to measurements taken from the Government furnished hub or die.

2. Forcers shall be used on the eagle, globe and anchor.

3. -1 and -2 shall be made in pairs (one left hand and one right hand).

4. Trimming on both sides of the eagle's head to be accomplished without altering or distorting the design detail.



Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:09Z
Check the source to verify that this is the current version before use.

Custodians:
Army - IH
Navy - MC

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2024-282)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.



Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:09Z
Check the source to verify that this is the current version before use.