MIL-T-15672D
17 July 1975
SUPERSEDING
MIL-T-15672C
18 September 1968

MILITARY SPECIFICATION

TABLES, LINE-UP AND REGISTER, PRINTING, LITHOGRAPHIC

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers line-up and register tables used in the photolithographic process.

1.2 Classification. The tables shall be of the following types, as specified (see 6.2 and 6.5):

Type 1 - 25-1/2 by 36-1/2 inches working area.
Type 2 - 36-1/2 by 48-1/2 inches working area.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

Federal

W-C-596	- Connector, Plug, Electrical; Connector, Receptacle, Electrical.
DD-G-451	- Glass, Plate, Sheet, Figured (Float, Flat, For Glazing, Corrugated, Mirrors and Other Uses).
GG-P-136	- Pen, Ruling, Draftsmen's: Spring Blade Type; Flat Handled, 6-Inch.

FSC 3610

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:09Z
Check the source to verify that this is the current version before use.

QQ-S-781	- Strapping, Steel, and Seals.
PPP-B-601	- Boxes, Wood, Cleated-Plywood.
PPP-B-636	- Boxes, Shipping, Fiberboard.
PPP-B-1055	- Barrier Material, Waterproofed, Flexible.
PPP-C-843	- Cushioning Material, Cellulosic.
PPP-P-40	- Packaging and Packing of Hand Tools.
PPP-T-60	- Tape: Packaging, Waterproof.

Military

MIL-P-116	- Preservation-Packaging, Methods of.
MIL-B-121	- Barrier Material, Greaseproofed, Waterproofed, Flexible.
MIL-P-514	- Plates, Identification, Instruction and Marking, Blank.

STANDARDS

Military

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-130	- Identification Marking of US Military Property.

(Copies of specifications and standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The folllowing documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, ATTN: Tariff Publishing Officer, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:09Z
Check the source to verify that this is the current version before use.

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Associations, Inc., ATTN: Tariff Order Section, 1616 P Street, NW, Washington, DC 20036.)

COUNTY OF LOS ANGELES - AIR POLLUTION CONTROL DISTRICT

Rule 66 - Organic Solvents.

(Application for copies should be addressed to the County of Los Angeles - Air Pollution Control District, 434 S. San Pedro Street, Los Angeles, CA 90013.)

3. REQUIREMENTS

3.1 Description. The table shall consist of a base frame with a shelf and lamp housing, a table top frame with a glass working surface, a horizontal and vertical straightedge carriage, and precision scales.

3.2 Material. Material shall be as specified herein. Materials not specified shall be selected by the supplier and shall be subject to all provisions of this specification.

3.3 Dimensions. Dimensions of the tables shall be as shown in Table I.

Table I. Dimensions (in inches).

	Size	
	Type 1	Type 2
Length (in)	57	69
Width (in)	44	55
Height (in)	36	36
* Glass area (sq in)	28 x 39	39 x 51

* Working area is 2-1/2 inches less than glass area.

Source: https://assist.dla.mil -- Downloaded: 202640-18T07:09Z
Check the source to verify that this is the current version before use.

3.4 Base frame. The base frame shall be of steel construction and shall support the table and all of its components.

3.5 Shelf. A shelf extending the entire length of the table shall be provided in the base frame. The shelf shall be of steel construction.

3.6 Lamp housing. An enclosed lamp housing of sheet steel shall be mounted so as to form an intergral part of the frame beneath the glass working surface. One or more access doors shall be provided to facilitate removing and installing lamps. A means for dissipating heat from the lamps shall be provided in the lamp housing. The interior of the lamp housing shall be finished in a nonpeeling flat white paint.

3.7 Illumination. The lamp housing shall be equipped with four or more daylight or cool white medium bipin, fluorescent lamps. The lamps shall be equipped with the necessary ballast and starters and shall be wired to a control switch mounted on the table for right-hand operation. The lamps shall be of the size shown in Table II.

Table II. Lamp Sizes

Table type	Lamp (bulb)	Lamp (watt)	Length (in)
1	T-8	30	36
2	T-12	40	48

3.8 Storage compartment. A minimum of one storage compartment or drawer shall be provided for the convenient storage of accessories and tools.

3.9 Tabletop frame. A frame of four machined steel bars shall be bolted to the top of the base frame around its perimeter. The tabletop frame shall form a plane and flat surface and shall provide a rigid support for the gear tracks, the glass working surface, the track for the sheet stop and grippers, and the side guide. The tabletop frame shall be adjustable for tilting up to 20 degrees.

Source: https://assist.dla.mil -- Downloaded: 202640-18T07:09Z
Check the source to verify that this is the currentversion before use.

3.10 Gear tracks. Gear tracks shall be macined from steel; shall be conditioned to relieve internal stresses; and shall remain dimensionally stable in use. The tracks shall be mounted flat against the tabletop frame on all four sides in such a way that if they are removed or accidentally become loose, they may be resecured in their proper position by using simple handtools. Gear tracks shall properly mesh with the gears specified in 3.18.

3.11 Stops and retainers. Stops and retainers shall be provided to keep the gears and gear tracks properly meshed, eliminate play between them, and prevent the straighedge carriages from running off the end of the track.

3.12 Sheet stops and grippers. Two combination sheet stops and grippers shall be provided to accurately position and firmly hold the front edge of the sheet, negative, or lithographic plate. The stops shall be placed on a guide track so that they may be moved to any point along the front edge of the working surface by sliding them on the track, and shall be equipped with a simple clamping device instantly operable by hand which shall secure the stop, the gripper, and the sheet. The stops shall not interfere in any way with the motion of the vertical straightedge assembly when they are in the secured position.

3.13 Side guide. A side guide shall be provided to accurately position the edge of the sheet, negative, or lithographic plate. The guide shall be placed on a guide track (which may be the sheet stop and gripper guide track) so that it may slide to any point along the front edge of the working surface. The guide shall be equipped with a pointer for measuring its position on the front fixed horizontal scale (see 3.27). The guide shall be pivoted so that it may be rotated into a position where it will not interfere with the motion of the straightedge assemblies.

3.14 Glass mounting frame. A rectangular metal frame shall be provided to mount the glass and diffuser in a firm, cushioned support. The construction of the frame and the method of mounting the glass and diffuser shall not induce strains or stresses which may cause breakage of the glass. Felt insulation shall be provided between the glass plate, diffuser and the frame. Adjustable glass mounting frame supports shall be mounted on the underside of the tabletop frame. The supports shall permit leveling the glass mounting frame and shall rigidly support it without placing strains on the glass. An adjustable support for the center of the glass and diffuser shall be provided.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:09Z
Check the source to verify that this is the current version before use.

3.15 Glass plate. The working surface shall be plate or float glass conforming to DD-G-451, Type I, Class 1, Quality 3 and shall be not less than 1/4 inch thick. All edges shall be free from sharp edges, chips, or cracks. When specified (see 6.2), extra glass plates and the number required shall be provided with each table.

3.15.1 Light diffusion. An opaline or milkey white plastic sheet not less than 1/8 inch thick shall be placed beneath the glass plate for light diffusion. The plastic sheet shall be the same size as the glass plate.

3.16 Straightedge carriages. Each table shall be equipped with one vertical and one horizontal straightedge carriage. Each carriage shall be provided with a straightedge, gear operated drive, vernier scales match plate, position lock, elevating mechanism, ruler guide track, and scales (see 3.27 and 3.28). Apron frames shall be mounted on the left and rear sides of the table for holding the horizontal and vertical straightedge assemblies and the gear tracks beyond the working surface. The apron frames shall provide strength and rigidity equivalent to the tabletop proper.

3.17 Straightedges. Each straightedge shall extend the full length or width of the glass working surface, and shall be movable across the entire working surface. The straightedges shall be straight within 0.0015 inch per foot of length. Movement of the straightedges shall be parallel to their respective fixed scales. When tested as specified in 4.4.2.7, the spacings of the grid intersections shall be accurate and precise to within plus or minus 0.0015 inch. Extreme diagonals shall be equal to each other within 0.016 inch for Size 1 tables and 0.022 for Size 2 tables.

3.18 Gear-operated drive. The straightedge carriages shall be gear driven with a gear for each track. Gears shall be machined from steel and conditioned to relieve internal stresses. Gears shall be connected to a shaft to maintain alinement. Each drive shall be operated by means of a knurled knob on the shaft.

3.19 Vernier dial. Each carriage shall be equipped with a vernier dial calibrated to read directly the movement of its respective straightedge in 64th-inch intervals. A transparent hairline indicator shall be mounted over the vernier dial to aid in precision settings. A vernier adjusting screw, with a positive locking device, shall be provided for precise adjustment of the vernier dial.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:09Z
Check the source to verify that this is the current version before use.

3.20 Position lock. A means shall be provided for locking either straightedge carriage in any lateral position on the working surface. When tested as specified in 4.4.2.4, the ruling edge of the straightedge shall return to its original position on the table.

3.21 Elevating mechanism. Each straightedge carriage shall be equipped with a 3-position, lever-operated cam for raising and lowering the straightedge from: (1) surface contact with the sheet; (2) approximately 1/4 inch above the sheet; and (3) high elevation for off-table position. An adjustment shall be provided for variations in the thickness of paper, plates, or negatives.

3.22 Ruler guide track. A track shall be provided on each straightedge carriage to accurately guide the ruling device holder and self-inking ruling mechanism (see 3.23 and 3.24). A line drawn with either the ruling device holder or the self-inking mechanism shall be straight within 0.0015 inch per foot of length when tested as specified in 4.4.2.5, and shall be parallel with the drawing edge of its respective straightedge.

3.23 Ruling device holder. A ruling device holder shall be provided for each straightedge carriage for ruling continuous parallel lines to within 3/32 inch of any edge of the working surface of the table. The holder shall be constructed for drawing lines on paper, tracing cloth, photographic film, and lithographic offset plates. The horizontal ruling device holder shall rule from left to right, and the vertical ruling device holder shall rule from bact to front. Horizontal and vertical ruling device holders shall be provided with conspicuous, distinguishing marks. Each ruling device holder shall be provided with a ruling pen, the blades of which shall conform to GG-P-136, and a 0.003-inch and a 0.010-inch stylus point.

3.24 Self-inking ruling mechanism. In addition to the ruling device holder specified in 3.23, a self-inking ruling mechanism shall be provided for each straightedge carriage. The self-inking mechanism shall rule continuous harilines (0.003 inch width) to within 0.003 inch of any edge of the working surface of the table. The self-inking ruling mechanism shall be provided with an ink pad, a roll assembly, and an ink wheel. The mechanism shall be constructed so that all pressure is governed by spring tension and the ink wheel will maintain a clear line on all surfaces, rough or smooth, and will not cut through sheets as thin as tissue.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:09Z
Check the source to verify that this is the current version before use.

3.25 Stops. Four movable and detachable stops, two for each straightedge carriage, shall be provided. Each stop shall be provided with an index for positioning the stop on the scale, and fine adjustment for limiting the stroke of either the ruling device holder or the self-inking ruling mechanism. The stops for the straightedge carriages shall be interchangeable.

3.26 Scales. All scales shall be or corrosion-resisting steel, shall be graduated in 1/32-inch divisions, and each inch graduation shall be numbered. In addition, the 1/8-inch graduations shall be marked with the proper figures expressed as the number of 32nds of an inch. All graduations shall be machine divided, clear and distinct, and of a definite length for easy legibility.

3.27 Horizontal scales. One horizontal scale shall be fastened in front of the front edge of the glass working surface, and one on the horizontal straightedge carriage. Both horizontal scales shall have the zero graduation at the center of the glass working surface. Numbering shall increase to the right and left, and shall extend to the ends of the glass working surface.

3.28 Vertical scales. One vertical scale shall be fastened on the left hand side (of the operator in normal working position) of the glass working surface, and one scale shall be fastened to the vertical straightedge carriage. Both vertical scales shall be numbered from front to back throughout the width of the glass working surface.

3.29 Electrical requirements. The table shall operate on 110-115 volt, 60 cycle, alternating current electrical service.

3.30 Cable. The table shall be provided with an insulated extension cable not less than 5 feet long, complete with a 2 pole, 3 wire connector plug conforming to W-C-596, Series D.

3.31 Fungus and moisture resistance. When specified (see 6.2), the electrical circuitry, including all components and connections, except as specified below, shall be protected from the effects of fungus growth and moisture by an overall treatment with a varnish conforming to MIL-V-173, Composition I or II, as applicable (see 3.31.1), with 1 percent copper 8-quinolinolate (by weight) based on the nonvolatile content of the varnish:

(a) Components or circuit elements that are inherently fungus and moisture resistant or which are hermetically sealed need not be treated.
(b) Components or circuit elements whose functions will be adversely affected by the varnish coating shall not be treated.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:09Z
Check the source to verify that this is the current version before use.

When used, the varnish shall be applied by spray, brush, or a combination of both to give a dry-film thickness of not less than 1 mil to component or element surfaces previously cleaned and prepared so that the surfaces are free from all foreign matter which would interferewith the adherence or function of the varnish.

3.31.1 Composition. Composition II shall be used only in the case when local air pollution regulations in the application of varnish precludes the use of Composition I. When Composition II is used, the supplier shall provide evidence to the Government that the use of Composition II is required, and shall certify that the Composition II materiual complies with Rule 66, Air Pollution Control District, County of Los Angeles, CA.

3.32 Lubrication. All moving parts shall be provided with suitable means of lubrication.

3.33 Identification marking. The table shall be identified in accordance with MIL-STD-130. The marking shall be applied to the table on plated conforming to MIL-P-514, Type I, Style 1, Composition C, of Type I, Grade A, Class 1 material. Plates shall be attached by screws, bolts, or rivets in a conspicuous protected location.

3.34 Instruction plates. Each table shall be equipped with instruction plates or diagrams, including warning and cautions, describing any special or important procedures to be followed in assembling, operating, or servicing the table. Instruction plates shall conform to MIL-P-514, Type III, Composition C, of Type I, Grade A, Class 1 material.

3.35 Treatment and painting. The portions of the table normally painted shall be cleaned, traeted, and painted in accordance with commercial practice, and the color shall be that commercally supplied.

3.36 Workmanship. All parts, components and assemblies of the tables including castings, molded parts, bearings, machined surfaces, and welded parts shall be cleaned and free from pits, scale, flux, and other harmful extraneous material. All edges shall be rounded or chamfered.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsiblity for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:09Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspections. Inspections shall be classified as follows:

(a) Quality conformance inspection (see 4.3).
(b) Inspection of preparation for delivery (see 4.5).

4.3 Quality conformance inspection.

4.3.1 Examination. Each table shall be examined for defects specified in 4.4.1. Presence of one or more defects shall be cause for rejection.

4.3.2 Tests. Each table shall be tested as specified in 4.4.2.1 through 4.4.2.7. Failure of any test shall be cause for rejection.

4.4 Inspection procedure.

4.4.1 Examination. The tables shall be examined for the following defects:

101. Material not as specified.
102. Dimensions of table not as specified.
103. Dimensions of glass working surface not as specified.
104. Glass working surface improperly mounted.
105. Access doors on lamp housing do not properly function.
106. Means for dissipating heat not provided in lamp housing.
107. Incorrect number or size of lamps provided.
108. Instruction plates and identification marking not as specified.
109. Workmanship not as specified.

4.4.2 Tests.

4.4.2.1 Gear tracks, stops, and retainers. Each carriage in turn shall be moved across the full length (or width) of the table. The meshing of the gears shall be observed to determine that they mesh properly without excessive play or tight spots. An upward pressure sufficient to lift the carriage shall be applied at intervals to each carriage to determine that the retainers retain the carriage on the track. Each carriage shall be moved against the stops to determine that the stops prevent the carriage from running off the track. Any evidence of imporper fitting of the gears, failure of retainers to hold gears on the tracks, or imporper placement of the stops shall constitute failure of the test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:09Z
Check the source to verify that this is the current version before use.

4.4.2.2 Sheet stops and grippers. Both sheet stops and grippers shall be moved along the entire length of the guide track. Sheets of film and paper shall be placed against the stops to determine that the stops properly position the film or paper with the clamping devices open. The clamping devices shall be secured on the sheets of film or paper to determine that the grippers hold both the film and paper securely. With the grippers in the secured position, both straightedge carriages in turn shall be moved across both stops and grippers, to determine that clearance is provided. Any evidence of binding when the sheet stops and grippers are moved along the guide track, failure of the clamping devices to hold the paper or film securely, or failure of straightedge carriages to pass freely over the sheet stops and grippers shall constitute failure of the test.

4.4.2.3 Side guide. The side guide shall be moved along the entire length of the track. The arm shall be pivoted into operational position and into a folded position. Both carriages shall be moved over the side guide in its folded position. Any evidence of binding when the side guide is moved along the track or failure of the carriages to pass freely over the folded side guide shall constitute failure of this test.

4.4.2.4 Position lock and elevating mechanism. Each carriage in turn shall be moved to a position near the center of the glass working surface and locked in position. A line of maximum length shall be drawn on a sheet of drawing paper securely fastened to the glass working surface with the self-inking ruling mechanism. The straightedge shall be raised to its first position above the paper, and then to its "high" position with the cam operated mechanism. The straightedge shall then be lowered to its position against the paper. Then the straightedge shall be raised and lowered 10 times to see that the ruling edge of the straightedge returns to its exact position along the drawn line. Nonconformance to 3.20 or 3.21 shall constitute failure of this test.

4.4.2.5 Ruling guide track and ruling device holder. While the carriage is clamped in position for the test specified in 4.4.2.4, a series of fine ink lines of maximum length shall be drawn with ruling device holder. Nonconformance to 3.22 or 3.23 shall constitute failure of the test.

4.4.2.6 Self-inking mechanism. The ink pad of the self-inking mechanism shall be filled with ink, and a series of continuous lines shall be drawn with both the vertical and horizontal straightedge carriages. Lines shall be drawn on various grades of drawing paper, including both smooth and rough surfaces. Nonconformance to 3.24 shall constitute failure of the test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:09Z
Check the source to verify that this is the current version before use.

4.4.2.7 Grid pattern test. A 4-inch rectangular grid pattern of maximum size shall be drawn on a good grade of drawing paper using the self-inking mechanism on each of the straightedge carriages. The grid pattern shall be laid out through the use of the vernier dial on both carriages. Non-conformance to 3.17 and 3.19 shall constitute failure of the test.

4.5 Inspection of preparation for delivery.

4.5.1 Quality conformance inspection of pack.

4.5.1.1 Unit of product. For the purpose of inspection, a completely processed pack prepared for shipment shall be considered a unit of product.

4.5.1.2 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.5.1.3 Examination. Samples selected in accordance with 4.5.1.2 shall be examined for the following defects. AQL shall be 2.5 percent defective.

110.	Materials, methods, and containers not as specified for Level A or B. Each incorrect container, method, or material shall constitute on defect.
111.	Disassembly not as specified for Level A.
112.	Components requiring a contact preservative not coated as specified for Level A.
113.	Surfaces coated with preservative not wrapped or covered as specified for Level A.
114.	Interior of drawer lock not treated with graphite as specified for Level A.
115.	Strapping not coated for Level A.
116.	Marking illegible, incomplete, or incorrect.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be Level A or C, as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Disassembly. The fluorescent lamps and lamp starters shall be removed from the table.

Source: https://assist.dla.mil -- Downloaded: 202640-18T07:09Z
Check the source to verify that this is the currentversion before use.

5.1.1.2 Preservatives. Preservatives specified herein shall conform to the applicable specifications listed in and shall be applied in accordance with MIL-P-116.

5.1.1.3 Components. Surfaces of components such as gears, gear tracks, retainers, frame, and scales requiring the application of a contact preservative in accordance with MIL-P-116, shall be coated with Type P-11 preservative. Coated surfaces shall be wrapped or covered with greaseproof barrier material conforming to MIL-B-121, Type I, Grade A, Class 2, and the wrap or cover secured in place with tape conforming to PPP-T-60, Type IV.

5.1.1.3.1 Straightedge carriages. Metal surfaces of straightedge carriages shall be coated with Type P-11 preservative, the carriages secured, and the carriages wrapped or covered with greaseproof barrier material conforming to MIL-B-121, Type I, Grade A, Class 2, secured in place with waterproof pressure-sensitive adhesive tape conforming to PPP-T-60, Type IV.

5.1.1.3.2 Ruling mechanisms. Metal surfaces of the ruling mechainisms shall be coated with Type P-11 preservative, applied by brushing to prevent the preservative from contacting the ink pad and roll. Each ruling mechanism shall be preserved in accordance with MIL-P-116, Method IC-1, placed in the table drawer and cushioned to prevent damage.

5.1.1.3.3 Ruling device holders and accessories. Metal surfaces of the ruling device holders and accessories shall be coated with Type P-11 preservative. Each ruling device holder and each of the accessories shall be preserved in accordance with MIL-P-116, Method IC-1, placed in the table drawer, and cushioned to prevent damage.

5.1.1.3.4 Lamp housing. Fluorescent lamp and starter sockets and the switch shall be sealed with waterproof, pressure-sensitive adhesive tape conforming to PPP-T-60, Type IV. The door hinges and catches shall be coated with Type P-7 preservative. The extension cable shall be coiled, the coil secured, placed in the lamp housing, and cushioned to prevent damage.

5.1.1.3.4.1 Fluorescent lamps. Each fluorescent lamp shall be wrapped with cellulosic cushioning material conforming to PPP-C-843, Type II, Class B. The lamps for each table shall be preserved together in accordance with MIL-P-116, Method III. The containers shall be close-fitting fiberboard boxes conforming to PPP-B-636, W5c or W6c, Style RSC. The boxes shall be closed and sealed in accordance with the appendix to the box specification. The preserved lamps shall be placed in the lamp housing and cushioned to prevent damage.

Source: https://assist.dla.mil -- Downloaded: 202640-18T07:09Z
Check the source to verify that this is the currentversion before use.

5.1.1.3.4.2 Fluorescent lamp starters. The lamp starters for each table shall be preserved in accordance with MIL-P-116, Method IC-1. The preserved starters shall be placed in the table drawer and cushioned to prevent damage.

5.1.1.3.5 Extra glass plates. Each extra glass plate shall be wrapped with cellulosic cushioning material conforming to PPP-C-843, Type II, Class B, secured with tape conforming to PPP-T-60, Type IV. The cushioned plates shall be preserved together in accordance with MIL-P-116, Method III. The container shall be a close-fitting fiberboard box conforming to PPP-B-636, W5c or W6c, Style RSC. The boxes shall be closed and sealed in accordance with the appendix to the box specification. The preserved plates shall be placed flat on the table top or on the table shelf and the package secured in place with waterproof pressure-sensitive adhesive tape conforming to PPP-T-60, Type IV.

5.1.1.3.6 Locks and keys. The interior of the drawer lock shall be treated with powdered graphite and the key hole covered with waterproof pressure-sensitive adhesive tape conforming to PPP-T-60, Type IV. The keys shall be coated with Type P-11 preservative, preserved in accordance with MIL-P-116, Method IC-1, and placed in the table drawer.

5.1.1.3.7 Technical publications. Technical publications for each table shall be preserved together in accordance with MIL-P-116, Method IC-1. The preserved publications shall be secured to the table top with tape conforming to PPP-T-60, Type IV.

5.1.1.3.8 Repair parts. The preservative application criteria of MIL-P-116 shall be used to preserve and package the repair parts using the most applicable submethod(s) listed therein. The parts shall be placed in the table drawer and cushioned to prevent movement.

5.1.1.3.9 Maintenance tools. Maintenance tools shall be preserved and packaged in accordance with PPP-P-40, Level A. The preserved and packaged tools shall be placed in the table drawer and cushioned to prevent movement.

5.1.2 Level C. The tables, components, accessories, repair parts, tools, and technical publications shall be preserved and packaged to afford protection against deterioration and damage form the supplier to the initial destination for immediate use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:09Z
Check the source to verify that this is the current version before use.

5.2 Packing. Packing shall be Level A, B, or C, as specified (see 6.2).

5.2.1 Level A. Each complete table shall be packed in a close-fitting box conforming to PPP-B-601, Overseas Type, style optional. The box shall be modified by the installation of skids in accordance with the box specification. Cushioning and blocking shall be provided. The table shall be covered with a full shroud fabricated of waterproof kraft wrapping paper conforming to PPP-B-1055, Class H-1. The box shall be strapped in accordance with the appendix to the ox specification, except that unless otherwise specified (see 6.2) strapping shall conform to QQ-S-781, Finish B, and shall be placed adjacent to the skids.

5.2.2 Level B. The tables shall be packed as specified for Level A, except the boxes shall be domestic type and the waterproof shroud shall not be required. Strapping need not be zinc coated.

5.2.3 Level C. The table, components, accessories, repair parts, tools, and technical publications shall be packed to assure carrier acceptance at lowest ratings in compliance with Uniform Freight Classification rules or National Motor Freight Classification rules.

5.3 Marking. In addition to any special marking required, packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The tables are intended to be used in layout, lineup, registering, masking, and opaquing of lithographic negatives, plates, copy, prints, or other materials as used in the photolihographic process.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Type of table required (see 1.2).
(c) Whether extra glass plates are required, and the number (see 3.15).
(d) When fungus- and moisture-resistance treatment is required (see 3.31).
(e) Level of preservation and packaging and level of packing required (see 5.1 and 5.2).
(f) When strapping other than as specified is required (see 5.2.1) and 6.6).

Source: https://assist.dla.mil -- Downloaded: 202610-18T07:09Z
Check the source to verify that this is the current version before use.

6.3 Data requirements. The contracting officer should include requirements for such data as technical publications, instructional materials, illustrated parts lists, and supplier's maintenance and operation manual to be furnished with each table.

6.4 Provisioning. The contracting officer should include provisioning requirements for repair parts and maintenance tools as necessary (including any special tools), and instructions regarding shipment of tables.

6.5 Classification changes. Changes in classification of the table between this revision of the specification and the previous edition are as follows:

Old Designation.	New Designation.
Size 1	Type 1
Size 2	Type 2

6.6 Strapping. Army policy requires the use of organic coated (Finish A) strapping for Army sponsored shipments.

Custodians:

Army - ME
Navy - SA

Review activity:

Navy - MC

Preparing activity:

Army - ME

Project No. 3610-0258

Source: https://assist.dla.mil -- Downloaded: 202610-18T07:09Z
Check the source to verify that this is the current version before use.