The documentation and process conversion measures necessary to comply with this amendment shall be completed by 16 May 2001.

INCH POUND

MIL-PRF-19500/240H
AMENDMENT 1
16 February 2001

PERFORMANCE SPECIFICATION

SEMICONDUCTOR DEVICE, DIODE, SILICON, RECTIFIER,
TYPES 1N645-1, 1N647-1, 1N649-1, 1N645UR-1, 1N647UR-1, 1N649UR-1
JAN, JANTX, AND JANTXV

JANS1N645-1, JANS1N647-1 and JANS1N649-1 are no longer processed to this specification. The preferred replacement part numbers are JANS1N6661, JANS1N6662, JANS1N6663. Devices processed to MIL-S-19500/587 as JANS1N6661, JANS1N6662, JANS1N6663 may be alternately marked as JANS1N645-1, JANS1N647-1 and JANS1N649-1 see 3.4.3.

This amendment forms a part of MIL-PRF-19500/240H, dated 24 February 2000 and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Replacement part note, delete last sentence.

PAGE 6

4.3.1, delete conditions information and substitute:

"

Type (1)	Method 1038 of MIL-STD-750 condition B T_A = +125°C, f = 60 Hz, (see 4.5.2)	Method 1038 of MIL-STD-750 condition B T_A = +25°C, f = 60 Hz, (see 4.5.2)	Method 1038 of MIL-STD-750 condition B T_A = +125°C	Method 1038 of MIL-STD-750 condition B T_A = +25°C
1N645-1	V_R = 225 V(pk), I_O = 200 mA	V_R = 225 V(pk), I_O = 400 mA	I_F = 200 mA	I_F = 400 mA
1N647-1	V_R = 400 V(pk), I_O = 200 mA	V_R = 400 V(pk), I_O = 400 mA	I_F = 200 mA	I_F = 400 mA
1N649-1	V_R = 600 V(pk), I_O = 200 mA	V_R = 600 V(pk), I_O = 400 mA	I_F = 200 mA	I_F = 400 mA

(1) Electrical characteristics for UR suffix devices are identical to the corresponding non-UR suffix devices unless otherwise specified. "

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Review activities:
Army - AR, AV, MI
Navy - AS, CG, MC

Preparing activity:
DLA - CC

(Project 5961-2425)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:49Z
Check the source to verify that this is the current version before use.