The documentation and process conversion measures necessary to comply with this amendment shall be completed by 16 November 1994

INCH-POUND

MIL-S-19500/241F
AMENDMENT 1
16 August 1994

MILITARY SPECIFICATION

SEMICONDUCTOR DEVICE, DIODE, SILICON, LOW LEAKAGE, GENERAL PURPOSE, SWITCHING
TYPES 1N3595, 1N3595US, 1N3595UR, 1N3595-1, 1N3595UR-1, AND 1N3595US-1
JAN, JANTX, JANTXV, JANS, JANHC, and JANKC

This amendment forms a part of MIL-S-19500/241F, dated 23 February 1994, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Implementation date, upper left corner, delete and susbstitute as printed herein.

Title, delete and substitute as printed below:

"SEMICONDUCTOR DEVICE, DIODE, SILICON, LOW LEAKAGE, GENERAL PURPOSE, SWITCHING
TYPES 1N3595-1, 1N3595UR-1, AND 1N3595US-1
JAN, JANTX, JANTXV, JANS, JANHC, and JANKC"

PAGE 2

Figure 1, title, delete "1N3595 and".

PAGE 7

4.3, delete screening table and notes and substitute as follows:

"

Screen (see table II of MIL-S-19500)	Measurement	
	JANS level	JANTX and JANTXV levels
3a	Temperature cycling	Temperature cycling
3c 1/	Thermal impedance (see 4.4.1 and 4.5.2)	Thermal impedance (see 4.4.1 and 4.5.2)
9	I_{R1} and V_{F1}	N/A
11	I_{R1}; V_{F1}; $\Delta V_F \leq \pm 50$ mV change from initial value; $\Delta I_R \leq \pm 0.5$ nA dc	I_{R1} and V_{F1}
12	See 4.3.1 t = 240 hours	See 4.3.1 t = 48 hours
13 2/	Subgroups 2 and 3 of table I herein; $\Delta V_{F1} \leq \pm 50$ mV change from initial value; $\Delta I_{R1} \leq \pm 0.5$ nA dc	Subgroup 2 of table I herein; $\Delta V_{F1} \leq \pm 50$ mV change from initial value $\Delta I_{R1} \leq \pm 0.5$ nA dc

1/ Thermal impedance may be performed any time after sealing provided temperature cycling is performed in accordance with MIL-S-19500, screen 3 prior to this thermal test.

2/ PDA = 5 percent for screen 13, applies to ΔI_{R1}, ΔV_{F1}. Thermal impedance ($Z_{\theta JX}$) is not required in screen 13."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:50Z
Check the source to verify that this is the current version before use.

PAGE 7 - Continued

4.4.1, add the following "The following test conditions shall be used for $Z_{\theta JX}$: $Z_{\theta JX}$ = 50°C/W maximum I_H = 1 A, t_H = 10 ms, I_m = 1 mA, t_{md} = 70 µs maximum."

PAGE 9

TABLE I, add the following inspection as the first subgroup 2 test:

"

Inspection 1/	MIL-STD-750		Symbol	Limits		Unit
	Method	Conditions		Min	Max	
Subgroup 2						
Thermal impedance	3101	See 4.4.1	$Z_{\theta JX}$		50	°C/W

"

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 17

Review activities:
Army - AR, MI, AV
Navy - AS, CG, MC
Air Force - 19, 85

Preparing activity:
DLA - ES

(Project 5961-1664)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:50Z
Check the source to verify that this is the current version before use.