The documentation and process conversion measures necessary to comply with this document shall be completed by 25 September 2015.

INCH-POUND

MIL-PRF-19500/251T
25 June 2015
SUPERSEDING
MIL-PRF-19500/251R
12 May 2010

PERFORMANCE SPECIFICATION SHEET

* TRANSISTOR, NPN, SILICON, SWITCHING,
TYPES 2N2218, AND 2N2219, JAN, JANTX, JANTXV, AND JANS

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-19500.

1. SCOPE

1.1 Scope. This specification covers the performance requirements for NPN, silicon, switching transistors. Four levels of product assurance (JAN, JANTX, JANTXV and JANS) are provided for each device type as specified in MIL-PRF-19500. RHA level designators “M”, “D”, “P“, “L”, “R”, “F”, “G”, and “H” are appended to the device prefix to identify devices, which have passed RHA requirements.

* 1.2 Package outlines. The device packages for the encapsulated device types are as follows: TO-39 and TO-5 in accordance with figure 1

1.3 Maximum ratings unless otherwise specified T_A = +25°C.

Types	P_T T_A = +25°C (1)	P_T T_C = +25°C (1)	V_{CBO}	V_{CEO}	V_{EBO}	I_C	T_{STG} and T_J	$R_{\theta JC}$ max (2)	$R_{\theta JA}$ max (2)
	W	W	V dc	V dc	V dc	mA dc	For all	°C/W	°C/W
2N2218, 2N2219	0.8	3.0	60	30	5	800	-65° to +200°C	50	195
2N2218A, 2N2219A	0.8	3.0	75	50	6	800		50	195
2N2218AL, 2N2219AL	0.8	3.0	75	50	6	800		50	195

(1) See derating curve, figures 2 and 3.
(2) For thermal impedance curves, see figures 4 and 5.

* Comments, suggestions, or questions on this document should be addressed to DLA Land and Maritime, ATTN: VAC, P.O. Box 3990, Columbus, OH 43218-3990, or emailed to Semiconductor@dla.mil . Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil .

AMSC N/A

FSC 5961

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:52Z
Check the source to verify that this is the current version before use.

1.4 Primary electrical characteristics.

Types	h_{FE} at V_{CE} = 10 V dc									
	h_{FE1} I_C = 100 μA dc		h_{FE2} I_C = 1.0 mA dc		h_{FE3} I_C = 10 mA dc		h_{FE4} (1) I_C = 150 mA dc		h_{FE5} (1) I_C = 500 mA dc	
	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max
2N2218	20		25	150	35		40	120	20	
2N2219	35		50	325	75		100	300	30	
2N2218A	30		35	150	40		40	120	20	
2N2219A	50		75	325	100		100	300	30	
2N2218AL	30		35	150	40		40	120	20	
2N2219AL	50		75	325	100		100	300	30	


Types	$\lvert h_{fe} \rvert$ I_C = 20 mA dc V_{CE} = 20 V dc f = 100 MHz		C_{obo} I_E = 0, V_{CE} = 10 V dc 100 kHz ≤ f ≤ 1 MHz		Switching			
					t_{on}		t_{off}	
			pF		ns		ns	
	Min	Max	Min	Max	Min	Max	Min	Max
2N2218	2.5	12.0		8		40		250
2N2219	2.5	12.0		8		40		250
2N2218A	2.5	12.0		8		35		300
2N2219A	2.5	12.0		8		35		300
2N2218AL	2.5	12.0		8		35		300
2N2219AL	2.5	12.0		8		35		300

Types	$V_{CE(sat)1}$ (1) I_C = 150 mA dc I_B = 15 mA dc		$V_{CE(sat)2}$ (1) I_C = 500 mA dc I_B = 50 mA dc		$V_{BE(sat)1}$ (1) I_C = 150 mA dc I_B = 15 mA dc		$V_{BE(sat)2}$ (1) I_C = 500 mA dc I_B = 50 mA dc	
	V dc		V dc		V dc		V dc	
	min	max	min	max	min	max	min	max
2N2218		0.4		1.6	0.6	1.3		2.6
2N2219		0.4		1.6	0.6	1.3		2.6
2N2218A		0.3		1.0	0.6	1.2		2.0
2N2219A		0.3		1.0	0.6	1.2		2.0
2N2218AL		0.3		1.0	0.6	1.2		2.0
2N2219AL		0.3		1.0	0.6	1.2		2.0

(1) Pulsed (see 4.5.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:52Z
Check the source to verify that this is the current version before use.

Symbol	Dimensions				Note
	Inches		Millimeters		
	Min	Max	Min	Max	
CD	.305	.335	7.75	8.51	
CH	.240	.260	6.10	6.60	
HD	.335	.370	8.51	9.40	
LC	.200 TP		5.08 TP		7
LD	.016	.019	0.41	0.48	8,9
LL	See note 14				
LU	.016	.019	0.41	0.48	8,9
L_1		.050		1.27	8,9
L_2	.250		6.35		8,9
P	.100		2.54		7
Q		.030		0.76	5
TL	.029	.045	0.74	1.14	3,4
TW	.028	.034	0.71	0.86	3
r		.010		0.25	10
α	45° TP		45° TP		7



NOTES:

1. Dimensions are in inches.
2. Millimeters are given for general information only.
3. Beyond r (radius) maximum, TW shall be held for a minimum length of .011 (0.28 mm).
4. Dimension TL measured from maximum HD.
5. Body contour optional within zone defined by HD, CD, and Q.
6. CD shall not vary more than .010 inch (0.25 mm) in zone P. This zone is controlled for automatic handling.
7. Leads at gauge plane .054 +.001 -.000 inch (1.37 +0.03 -0.00 mm) below seating plane shall be within .007 inch (0.18 mm) radius of true position (TP) at maximum material condition (MMC) relative to tab at MMC.
8. Dimension LU applies between L_1 and L_2. Dimension LD applies between L_2 and LL minimum. Diameter is uncontrolled in L_1 and beyond LL minimum.
9. All three leads.
10. The collector shall be internally connected to the case.
11. Dimension r (radius) applies to both inside corners of tab.
12. In accordance with ASME Y14.5M, diameters are equivalent to ϕx symbology.
13. Lead 1 = emitter, lead 2 = base, lead 3 = collector.
14. For L suffix devices (TO-5), dimension LL = 1.5 inches (38.10 mm) min. and 1.75 inches (44.45 mm) max. For non-L suffix types (TO-39), dimension LL = .5 inch (12.70 mm) min. and .750 inch (19.05 mm) max.

FIGURE 1. Physical dimensions (similar to TO-39, TO-5).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:52Z
Check the source to verify that this is the current version before use.

* 1.5 Part or Identifying Number (PIN). The PIN is in accordance with MIL-PRF-19500, and as specified herein. See 6.4 for PIN construction example, 6.5 for a list of available PINs.

* 1.5.1 JAN certification mark and quality level.

* 1.5.1.1 Quality level designators for encapsulated devices. The quality level designators for encapsulated devices that are applicable for this specification sheet from the lowest to the highest level are as follows: The base quality level "JAN", "JANTX" “JANTXV”, and "JANS".

* 1.5.2 Radiation hardness assurance (RHA) designator. The RHA levels that are applicable for this specification sheet from lowest to highest for JANS quality levels are as follows: "M", "D", "P", "L", “R”, “F’, “G”, and “H”. The RHA levels that are applicable for this specification sheet from lowest to highest for JANTXV quality levels are as follows: "R", and “F”.

* 1.5.3 Device type. The designation system for the device types covered by this specification sheet are as follows.

* 1.5.3.1 First number and first letter symbols. The transistors of this specification sheet use the first number and letter symbols "2N".

* 1.5.3.2 Second number symbols. The second number symbols for the transistors covered by this specification sheet are as follows: "2218” and “2219".

* 1.5.4 Suffix symbols. The following suffix letters are incorporated in the PIN in the order listed in the table as applicable:

	A blank first suffix indicates a TO-39 package, dimension LL = .5 inch (12.70 mm) min. and .750 inch (19.05 mm) max. (see figure 1).
A	Indicates alternate electrical characteristics.
L	Indicates a TO-5 package, dimension LL = 1.5 inches (38.10 mm) min. and 1.75 inches (44.45 mm) max. (see figure 1).

* 1.5.5 Lead finish. The lead finishes applicable to this specification sheet are listed on QML-19500.

2. APPLICABLE DOCUMENTS

* 2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3 and 4 of this specification, whether or not they are listed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:52Z
Check the source to verify that this is the current version before use.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL-PRF-19500 - Semiconductor Devices, General Specification for.

DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-750 - Test Methods for Semiconductor Devices.

* (Copies of these documents are available online at http://quicksearch.dla.mil).

2.3 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 General. The individual item requirements shall be as specified in MIL-PRF-19500 and as modified herein.

3.2 Qualification. Devices furnished under this specification shall be products that are manufactured by a manufacturer authorized by the qualifying activity for listing on the applicable qualified manufacturers list before contract award (see 4.2 and 6.3).

3.3 Abbreviations, symbols, and definitions. Abbreviations, symbols, and definitions used herein shall be as specified in MIL-PRF-19500 and as follows.

PCB ..... Printed circuit board
$R_{\theta JA}$ ..... Thermal resistance junction to ambient.
$R_{\theta JC}$ ..... Thermal resistance junction to case.

* 3.4 Interface requirements and physical dimensions. Interface requirements and physical dimensions shall be as specified in MIL-PRF-19500, and on figure 1.

3.4.1 Lead finish. Lead finish shall be solderable in accordance with MIL-PRF-19500, MIL-STD-750, and herein. Where a choice of lead finish is desired, it shall be specified in the acquisition document (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:52Z
Check the source to verify that this is the current version before use.

3.5 Radiation hardness assurance (RHA). Radiation hardness assurance requirements, PIN designators, and test levels shall be as defined in MIL-PRF-19500.

3.6 Electrical performance characteristics. Unless otherwise specified herein, the electrical performance characteristics are as specified in 1.3, 1.4, and table I.

3.7 Electrical test requirements. The electrical test requirements shall be as specified in table I.

3.8 Marking. Marking shall be in accordance with MIL-PRF-19500. The radiation hardened designator M, D, P, L, R, F, G, or H shall immediately precede (or replace) the device "2N" identifier (depending upon degree of abbreviation required).

* 3.9 Workmanship. Switching transistor devices shall be processed in such a manner as to be uniform in quality and shall be free from other defects that will affect life, serviceability, or appearance.

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. Qualification inspection (see 4.2).

b. Screening (see 4.3).

c. Conformance inspection (see 4.4 and table I and II).

4.2 Qualification inspection. Qualification inspection shall be in accordance with MIL-PRF-19500 and as specified herein.

4.2.1 Group E qualification. Group E inspection shall be performed for qualification or re-qualification only. In case qualification was awarded to a prior revision of the specification sheet that did not request the performance of table III tests, the tests specified in table III herein that were not performed in the prior revision shall be performed on the first inspection lot of this revision to maintain qualification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:52Z
Check the source to verify that this is the current version before use.

* 4.3 Screening (JAN, JANTXV, JANTX, and JANS levels). Screening shall be in accordance with table E-IV of MIL-PRF-19500 and as specified herein. The following measurements shall be made in accordance with table I herein. Devices that exceed the limits of table I herein shall not be acceptable.

Screen	Measurement	
	JANS level	JANTX and JANTXV levels
(1) 3c	Thermal impedance (see 4.3.2)	Thermal impedance (see 4.3.2)
9	I_{CBO2}, h_{FE4}	Not applicable
10	48 hours minimum	48 hours minimum
11	I_{CBO2}; h_{FE4}; ΔI_{CBO2} = 100 percent of initial value or 5 nA dc, whichever is greater. Δh_{FE4} = ±15 percent	I_{CBO2}, h_{FE4}
12	See 4.3.1	See 4.3.1
13	Subgroups 2 and 3 of table I herein; ΔI_{CBO2} = 100 percent of initial value or 5 nA dc, whichever is greater; Δh_{FE4} = ±15 percent	Subgroup 2 of table I herein; ΔI_{CBO2} = 100 percent of initial value or 5 nA dc, whichever is greater; Δh_{FE4} = ±15 percent

(1) Shall be performed anytime after temperature cycling, screen 3a; and does not need to be repeated in screening requirements for JANTX and JANTXV level devices.

4.3.1 Power burn-in conditions. Power burn-in conditions are as follows: V_{CB} = 10 - 30 V dc. Power shall be applied to achieve T_J = +135°C minimum using a minimum P_D = 75 percent of P_T maximum rated as defined in 1.3. T_A = 25°C ±10°C. With approval of the qualifying activity and preparing activity, alternate burn-in criteria (hours, bias conditions, TJ, and mounting conditions) may be used for JANTX and JANTXV quality levels. A justification demonstrating equivalence is required. In addition, the manufacturing site's burn-in data and performance history will be essential criteria for burn-in modification approval. Use method 3100 of MIL-STD-750 to measure T_J.

4.3.2 Thermal impedance. The thermal impedance shall be performed in accordance with method 3131 of MIL-STD-750 using the guidelines in that method for determining I_M, I_H, t_H, (and V_C where appropriate). Measurement delay time (t_{MD}) = 70 µs max. See table III, group E, subgroup 4 herein.

4.4 Conformance inspection. Conformance inspection shall be in accordance with MIL-PRF-19500, and as specified herein. If alternate screening is being performed in accordance with MIL-PRF-19500, a sample of screened devices shall be submitted to and pass the requirements of table I, group A1 and A2 inspection only (table E-VIb, group B, subgroup 1 is not required to be performed again if group B has already been satisfied in accordance with 4.4.2 herein).

4.4.1 Group A inspection. Group A inspection shall be conducted in accordance with MIL-PRF-19500, and table I herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:52Z
Check the source to verify that this is the current version before use.

* 4.4.2 Group B inspection. Group B inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E-VIa (JANS) of MIL-PRF-19500 and 4.4.2.1. See 4.4.2.2 for JAN, JANTX, and JANTXV group B testing.

4.4.2.1 Group B inspection (JANS), table E-VIa of MIL-PRF-19500.

Subgroup	Method	Condition
B4	1037	V_{CB} = 10 V dc, adjust device current, or power, to achieve a minimum ΔT_J of +100°C.
B5	1027	V_{CB} = 10 V dc; $P_D \geq$ 100 percent of maximum rated P_T (see 1.3). (NOTE: If a failure occurs, resubmission shall be at the test conditions of the original sample.) Option 1: 96 hours minimum sample size in accordance with MIL-PRF-19500, table E-VIa, adjust T_A or P_D to achieve T_J = +275°C minimum. Option 2: 216 hours minimum, sample size = 45, c = 0; adjust T_A or P_D to achieve a T_J = +225°C minimum.

4.4.2.2 Group B inspection, (JAN, JANTX, and JANTXV). Separate samples may be used for each step. In the event of a lot failure, the resubmission requirements of MIL-PRF-19500 shall apply. In addition, all catastrophic failures during CI, (conformance inspection), shall be analyzed to the extent possible to identify root cause and corrective action. Whenever a failure is identified as wafer lot or wafer processing related, the entire wafer lot and related devices assembled from the wafer lot shall be rejected unless an appropriate determined corrective action to eliminate the failures mode has been implemented and the devices from the wafer lot are screened to eliminate the failure mode.

Step	Method	Condition
1	1026	Steady-state life: 1,000 hours minimum, V_{CB} = 10 V dc, power shall be applied to achieve T_J = +150°C minimum using a minimum of P_D = 75 percent of maximum rated P_T as defined in 1.3. n = 45 devices, c = 0. The sample size may be increased and the test time decreased as long as the devices are stressed for a total of 45,000 device hours minimum, and the actual time of test is at least 340 hours.
2	1048	Blocking life, T_A = +150°C, V_{CB} = 80 percent of rated voltage, 48 hours minimum. n = 45 devices, c = 0.
3	1032	High-temperature life (non-operating), t = 340 hours, T_A = +200°C. n = 22, c = 0.

4.4.2.3 Group B sample selection. Samples selected from group B inspection shall meet all of the following requirements:

a. For JAN, JANTX, and JANTXV, samples shall be selected randomly from a minimum of three wafers (or from each wafer in the lot) from each wafer lot. For JANS, samples shall be selected from each inspection lot. See MIL-PRF-19500.

b. Shall be chosen from an inspection lot that has been submitted to and passed table I, subgroup 2, conformance inspection. When the final lead finish is solder or any plating prone to oxidation at high temperature, the samples for life test (subgroups B4 and B5 for JANS, and group B for JAN, JANTX, and JANTXV) may be pulled prior to the application of final lead finish.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:52Z
Check the source to verify that this is the current version before use.

* 4.4.3 Group C inspection, Group C inspection shall be conducted in accordance with the test and conditions specified for subgroup testing in table VII of MIL-PRF-19500, and in 4.4.3.1 (JANS) and 4.4.3.2 (JAN, JANTX, and JANTXV) herein for group C testing.

4.4.3.1 Group C inspection (JANS), table E-VII of MIL-PRF-19500.

Subgroup	Method	Condition
C2	2036	Test condition E.
C5	3131	$R_{\theta JA}$ and $R_{\theta JC}$ only, as applicable (see 1.3) and in accordance with thermal impedance curves.
C6	1026	1,000 hours at V_{CB} = 10 V dc; power shall be applied to achieve T_J = +150°C minimum and a minimum of P_D = 75 percent of maximum rated P_T as defined in 1.3. n = 45, c = 0. The sample size may be increased and the test time decreased as long as the devices are stressed for a total of 45,000 device hours minimum, and the actual time of test is at least 340 hours.

4.4.3.2 Group C inspection (JAN, JANTX, and JANTXV), table E-VII of MIL-PRF-19500.

Subgroup	Method	Condition
C2	2036	Test condition E.
C5	3131	$R_{\theta JA}$ and $R_{\theta JC}$ only, as applicable (see 1.3) and in accordance with thermal impedance curves.
C6		Not applicable.

4.4.3.3 Group C sample selection. Samples for subgroups in group C shall be chosen at random from any inspection lot containing the intended package type and lead finish procured to the same specification which is submitted to and passes table I tests herein for conformance inspection. When the final lead finish is solder or any plating prone to oxidation at high temperature, the samples for C6 life test may be pulled prior to the application of final lead finish. Testing of a subgroup using a single device type enclosed in the intended package type shall be considered as complying with the requirements for that subgroup.

4.4.4 Group D inspection. Conformance inspection for hardness assured JANS and JANTXV types shall include the group D tests specified in table II herein. These tests shall be performed as required in accordance with MIL-PRF-19500 and method 1019 of MIL-STD-750, for total ionizing dose or method 1017 of MIL-STD-750 for neutron fluence as applicable (see 6.2 herein), except group D, subgroup 2 may be performed separate from other subgroups. Group D inspection may also be performed ahead of the screening lot using die selected in accordance with MIL-PRF-19500 and related documents. Alternate package options may also be substituted for the testing provided there is no adverse effect to the fluence profile.

* 4.4.5 Group E inspection. Group E inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E-IX of MIL-PRF-19500 and as specified in table III herein.

4.5 Methods of inspection. Methods of inspection shall be as specified in the appropriate tables and as follows.

4.5.1 Pulse measurements. Conditions for pulse measurement shall be as specified in section 4 of MIL-STD-750.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:52Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection.

	Inspection 1/	MIL-STD-750		Symbol	Limit		Unit
		Method	Conditions		Min	Max	
	Subgroup 1 2/						
	Visual and mechanical examination 3/	2071	n = 45 devices, c = 0				
	Solderability 3/ 4/	2026	n = 15 leads, c = 0				
	Resistance to solvents 3/ 4/ 5/	1022	n = 15 devices, c = 0				
*	Salt atmosphere (corrosion)	1041	n = 6 devices, c = 0, (For laser marked devices only)				
	Temp cycling 3/ 4/	1051	Test condition C, 25 cycles. n = 22 devices, c = 0				
	Hermetic seal 4/ 6/ Fine leak Gross leak	1071	n = 22 devices, c = 0				
	Electrical measurements 4/		Table I, subgroup 2				
	Bond strength 3/ 4/	2037	Precondition T_A = +250°C at t = 24 hours or T_A = +300°C at t = 2 hours n = 11 wires, c = 0				
	Decap internal visual (design verification) 4/	2075	n = 4 devices, c = 0				
	Subgroup 2						
	Thermal impedance	3131	See 4.3.2	$Z_{\theta JX}$			°C/W
	Collector to base cutoff current	3036	Condition D	I_{CBO1}			
	2N2218, 2N2219		V_{CB} = 60 V dc			10	µA dc
	2N2218A, 2N2219A		V_{CB} = 75 V dc			10	µA dc
	2N2218AL, 2N2219AL		V_{CB} = 75 V dc			10	µA dc
	Emitter to base cutoff current	3061	Condition D	I_{EBO1}			
	2N2218, 2N2219		V_{EB} = 5 V dc			10	µA dc
	2N2218A, 2N2219A		V_{EB} = 6 V dc			10	µA dc
	2N2218AL, 2N2219AL		V_{EB} = 6 V dc			10	µA dc
	Breakdown voltage, collector to emitter	3011	Bias condition D; I_E = 10 mA dc; pulsed (see 4.5.1).	$V_{(BR)CEO}$			
	2N2218, 2N2219				30		V dc
	2N2218A, 2N2219A				50		V dc
	2N2218AL, 2N2219AL				50		V dc

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:52Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limit		Unit
	Method	Conditions		Min	Max	
Subgroup 2 - Continued						
Collector to emitter cutoff current	3041	Bias condition C	I_{CES}			
2N2218, 2N2219		V_{CE} = 30 V dc			10	nA dc
2N2218A, 2N2219A		V_{CE} = 50 V dc			10	nA dc
2N2218AL, 2N2219AL		V_{CE} = 50 V dc			10	nA dc
Emitter to base cutoff current	3061	Bias condition D; V_{EB} = 4 V dc	I_{EBO2}		10	nA dc
Collector to base cutoff current	3036	Bias condition D	I_{CBO2}			
2N2218, 2N2219		V_{CB} = 50 V dc			10	nA dc
2N2218A, 2N2219A		V_{CB} = 60 V dc			10	nA dc
2N2218AL, 2N2219AL		V_{CB} = 60 V dc			10	nA dc
Forward-current transfer ratio	3076	V_{CE} = 10 V dc; I_C = 0.1 mA dc; pulsed (see 4.5.1)	h_{FE1}			
2N2218				20		
2N2219				35		
2N2218A, 2N2218AL				30		
2N2219A, 2N2219AL				50		
Forward-current transfer ratio	3076	V_{CE} = 10 V dc; I_C = 1.0 mA dc; pulsed (see 4.5.1)	h_{FE2}			
2N2218				25	150	
2N2219				50	325	
2N2218A, 2N2218AL				35	150	
2N2219A, 2N2219AL				75	325	
Forward-current transfer ratio	3076	V_{CE} = 10 V dc; I_C = 10 mA dc; pulsed (see 4.5.1)	h_{FE3}			
2N2218				35		
2N2219				75		
2N2218A, 2N2218AL				40		
2N2219A, 2N2219AL				100		
Forward-current transfer ratio	3076	V_{CE} = 10 V dc; I_C = 150 mA dc; pulsed (see 4.5.1)	h_{FE4}			
2N2218				40	120	
2N2219				100	300	
2N2218A, 2N2218AL				40	120	
2N2219A, 2N2219AL				100	300	
Forward-current transfer ratio	3076	V_{CE} = 10 V dc; I_C = 500 mA dc; pulsed (see 4.5.1)	h_{FE5}			
2N2218				20		
2N2219				30		
2N2218A, 2N2218AL				20		
2N2219A, 2N2219AL				30		

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:52Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limit		Unit
	Method	Conditions		Min	Max	
Subgroup 2 - Continued						
Collector-emitter saturation voltage	3071	I_C = 150 mA dc; I_B = 15 mA dc; pulsed (see 4.5.1)	$V_{CE(sat)1}$			
2N2218, 2N2219					0.4	V dc
2N2218A, 2N2219A					0.3	V dc
2N2218AL, 2N2219AL					0.3	V dc
Collector-emitter saturation voltage	3071	I_C = 500 mA dc; I_B = 50 mA dc; pulsed (see 4.5.1)	$V_{CE(sat)2}$			
2N2218, 2N2219					1.6	V dc
2N2218A, 2N2219A					1.0	V dc
2N2218AL, 2N2219AL					1.0	V dc
Base-emitter saturation voltage	3066	Test condition A; I_C = 150 mA dc; I_B = 15 mA dc; pulsed (see 4.5.1)	$V_{BE(sat)1}$			
2N2218, 2N2219				0.6	1.3	V dc
2N2218A, 2N2219A				0.6	1.2	V dc
2N2218AL, 2N2219AL				0.6	1.2	V dc
Base-emitter saturation voltage	3066	Test condition A; I_C = 500 mA dc; I_B = 50 mA dc; pulsed (see 4.5.1)	$V_{BE(sat)2}$			
2N2218, 2N2219					2.6	V dc
2N2218A, 2N2219A					2.0	V dc
2N2218AL, 2N2219AL					2.0	V dc
Subgroup 3						
High temperature operation		T_A = +150°C				
Collector to base cutoff current	3036	Bias condition D	I_{CBO3}		10	µA dc
2N2218, 2N2219		V_{CB} = 50 V dc				
2N2218A, 2N2219A		V_{CB} = 60 V dc				
2N2218AL, 2N2219AL		V_{CB} = 60 V dc				
Low temperature operation		T_A = -55°C				
Forward-current transfer ratio	3076	V_{CE} = 10 V dc; I_C = 10 mA dc	h_{FE6}			
2N2218, 2N2219				15		
2N2218A, 2N2219A				35		
2N2218AL, 2N2219AL				35		

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:52Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limit		Unit
	Method	Conditions		Min	Max	
Subgroup 4						
Magnitude of common emitter small-signal short- circuit forward current transfer ratio	3306	V_{CE} = 20 V dc; I_C = 20 mA dc; f = 100 MHz	$\lvert h_{fe} \rvert$	2.5	12	
Small-signal short-circuit forward current transfer ratio	3206	V_{CE} = 10 V dc; I_C = 1 mA dc; f = 1 kHz	h_{fe}			
2N2218				25		
2N2219				50		
2N2218A, 2N2218AL				35		
2N2219A, 2N2219AL				75		
Open circuit output capacitance	3236	V_{CB} = 10 V dc; I_E = 0; 100 kHz ≤ f ≤ 1 MHz	C_{obo}		8	pF
Open circuit output capacitance	3240	V_{EB} = 0.5 V dc; I_C = 0; 100 kHz ≤ f ≤ 1 MHz	C_{ibo}		25	pF
Saturated turn-on time		(See figure 6)	t_{on}			
2N2218, 2N2219					40	ns
2N2218A, 2N2219A					35	ns
2N2218AL, 2N2219AL					35	ns
Saturated turn-off time		(See figure 7)	t_{off}			
2N2218, 2N2219					250	ns
2N2218A, 2N2219A					300	ns
2N2218AL, 2N2219AL					300	ns
Subgroups 5 and 6						
Not applicable						

1/ For sampling plan see MIL-PRF-19500.
2/ For resubmission of failed test in subgroup 1 of table I, double the sample size of the failed test or sequence of tests. A failure in table I, subgroup 1 shall not require retest of the entire subgroup. Only the failed test shall be rerun upon submission.
3/ Separate samples may be used.
4/ Not required for JANS devices.
5/ Not required for laser marked devices.
6/ This hermetic seal test is an end-point to temp-cycling in addition to electrical measurements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:52Z
Check the source to verify that this is the current version before use.

TABLE II. Group D inspection.

Inspection 1/ 2/ 3/	MIL-STD-750		Symbol	Limit		Unit
	Method	Conditions		Min	Max	
Subgroup 1 4/						
Neutron irradiation	1017	Neutron exposure V_{CES} = 0 V				
Collector to base cutoff current	3036	Condition D	I_{CBO1}			
2N2218, 2N2219		V_{CB} = 60 V dc			20	µA dc
2N2218A, 2N2219A		V_{CB} = 75 V dc			20	µA dc
2N2218AL, 2N2219AL		V_{CB} = 75 V dc			20	µA dc
Emitter to base cutoff current	3061	Condition D	I_{EBO1}			
2N2218, 2N2219		V_{EB} = 5 V dc			20	µA dc
2N2218A, 2N2219A		V_{EB} = 6 V dc			20	µA dc
2N2218AL, 2N2219AL		V_{EB} = 6 V dc			20	µA dc
Breakdown voltage, collector to emitter	3011	Bias condition D; I_E = 10 mA dc; pulsed (see 4.5.1).	$V_{(BR)CEO}$			
2N2218, 2N2219				30		V dc
2N2218A, 2N2219A				50		V dc
2N2218AL, 2N2219AL				50		V dc
Collector to emitter cutoff current	3041	Bias condition C	I_{CES}			
2N2218, 2N2219		V_{CE} = 30 V dc			20	nA dc
2N2218A, 2N2219A		V_{CE} = 50 V dc			20	nA dc
2N2218AL, 2N2219AL		V_{CE} = 50 V dc			20	nA dc
Emitter to base cutoff current	3061	Bias condition D; V_{EB} = 4 V dc	I_{EBO2}		20	nA dc
Collector to base cutoff current	3036	Bias condition D	I_{CBO2}			
2N2218, 2N2219		V_{CB} = 50 V dc			20	nA dc
2N2218A, 2N2219A		V_{CB} = 60 V dc			20	nA dc
2N2218AL, 2N2219AL		V_{CB} = 60 V dc			20	nA dc
Forward-current transfer ratio	3076	V_{CE} = 10 V dc; I_C = 0.1 mA dc; pulsed (see 4.5.1)	[h_{FE1}] 5/			
2N2218				[10]		
2N2219				[17.5]		
2N2218A, 2N2218AL				[15]		
2N2219A, 2N2219AL				[25]		
Forward-current transfer ratio	3076	V_{CE} = 10 V dc; I_C = 1.0 mA dc; pulsed (see 4.5.1)	[h_{FE2}] 5/			
2N2218				[12.5]	150	
2N2219				[25]	325	
2N2218A, 2N2218AL				[17.5]	150	
2N2219A, 2N2219AL				[37.5]	325	

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:52Z
Check the source to verify that this is the current version before use.

TABLE II. Group D inspection - Continued.

Inspection 1/ 2/ 3/	MIL-STD-750		Symbol	Limit		Unit
	Method	Conditions		Min	Max	
Subgroup 1 - Continued.						
Forward-current transfer ratio	3076	V_{CE} = 10 V dc; I_C = 10 mA dc; pulsed (see 4.5.1)	[h_{FE3}] 5/			
2N2218				[17.5]		
2N2219				[37.5]		
2N2218A, 2N2218AL				[20]		
2N2219A, 2N2219AL				[50]		
Forward-current transfer ratio	3076	V_{CE} = 10 V dc; I_C = 150 mA dc; pulsed (see 4.5.1)	[h_{FE4}] 5/			
2N2218				[20]	120	
2N2219				[50]	300	
2N2218A, 2N2218AL				[20]	120	
2N2219A, 2N2219AL				[50]	300	
Forward-current transfer ratio	3076	V_{CE} = 10 V dc; I_C = 500 mA dc; pulsed (see 4.5.1)	[h_{FE5}] 5/			
2N2218				[10]		
2N2219				[15]		
2N2218A, 2N2218AL				[10]		
2N2219A, 2N2219AL				[15]		
Collector-emitter saturation voltage	3071	I_C = 150 mA dc; I_B = 15 mA dc; pulsed (see 4.5.1)	$V_{CE(sat)1}$			
2N2218, 2N2219					0.46	V dc
2N2218A, 2N2219A					0.35	V dc
2N2218AL, 2N2219AL					0.35	V dc
Collector-emitter saturation voltage	3071	I_C = 500 mA dc; I_B = 50 mA dc; pulsed (see 4.5.1)	$V_{CE(sat)2}$			
2N2218, 2N2219					1.84	V dc
2N2218A, 2N2219A					1.15	V dc
2N2218AL, 2N2219AL					1.15	V dc
Base-emitter saturation voltage	3066	Test condition A; I_C = 150 mA dc; I_B = 15 mA dc; pulsed (see 4.5.1)	$V_{BE(sat)1}$			
2N2218, 2N2219				0.6	1.50	V dc
2N2218A, 2N2219A				0.6	1.38	V dc
2N2218AL, 2N2219AL				0.6	1.38	V dc
Base-emitter saturation voltage	3066	Test condition A; I_C = 500 mA dc; I_B = 50 mA dc; pulsed (see 4.5.1)	$V_{BE(sat)2}$			
2N2218, 2N2219					3.0	V dc
2N2218A, 2N2219A					2.3	V dc
2N2218AL, 2N2219AL					2.3	V dc

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:52Z
Check the source to verify that this is the current version before use.

TABLE II. Group D inspection - Continued.

Inspection 1/ 2/ 3/	MIL-STD-750		Symbol	Limit		Unit
	Method	Conditions		Min	Max	
Subgroup 2						
Total dose irradiation	1019	Gamma exposure				
2N2218, 2N2219		V_{CES} = 24 V				
2N2218A, 2N2219A		V_{CES} = 40 V				
2N2218AL, 2N2219AL		V_{CES} = 40 V				
Collector to base cutoff current	3036	Condition D	I_{CBO1}			
2N2218, 2N2219		V_{CB} = 60 V dc			20	µA dc
2N2218A, 2N2219A		V_{CB} = 75 V dc			20	µA dc
2N2218AL, 2N2219AL		V_{CB} = 75 V dc			20	µA dc
Emitter to base cutoff current	3061	Condition D	I_{EBO1}			
2N2218, 2N2219		V_{EB} = 5 V dc			20	µA dc
2N2218A, 2N2219A		V_{EB} = 6 V dc			20	µA dc
2N2218AL, 2N2219AL		V_{EB} = 6 V dc			20	µA dc
Breakdown voltage, collector to emitter	3011	Bias condition D; I_E = 10 mA dc; pulsed (see 4.5.1).	$V_{(BR)CEO}$			
2N2218, 2N2219				30		V dc
2N2218A, 2N2219A				50		V dc
2N2218AL, 2N2219AL				50		V dc
Collector to emitter cutoff current	3041	Bias condition C	I_{CES}			
2N2218, 2N2219		V_{CE} = 30 V dc			20	nA dc
2N2218A, 2N2219A		V_{CE} = 50 V dc			20	nA dc
2N2218AL, 2N2219AL		V_{CE} = 50 V dc			20	nA dc
Emitter to base cutoff current	3061	Bias condition D; V_{EB} = 4 V dc	I_{EBO2}		20	nA dc
Collector to base cutoff current	3036	Bias condition D	I_{CBO2}			
2N2218, 2N2219		V_{CB} = 50 V dc			20	nA dc
2N2218A, 2N2219A		V_{CB} = 60 V dc			20	nA dc
2N2218AL, 2N2219AL		V_{CB} = 60 V dc			20	nA dc
Forward-current transfer ratio	3076	V_{CE} = 10 V dc; I_C = 0.1 mA dc; pulsed (see 4.5.1)	[h_{FE1}] 5/			
2N2218				[10]		
2N2219				[17.5]		
2N2218A, 2N2218AL				[15]		
2N2219A, 2N2219AL				[25]		
Forward-current transfer ratio	3076	V_{CE} = 10 V dc; I_C = 1.0 mA dc; pulsed (see 4.5.1)	[h_{FE2}] 5/			
2N2218				[12.5]	150	
2N2219				[25]	325	
2N2218A, 2N2218AL				[17.5]	150	
2N2219A, 2N2219AL				[37.5]	325	

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:52Z
Check the source to verify that this is the current version before use.

TABLE II. Group D inspection - Continued.

Inspection 1/ 2/ 3/	MIL-STD-750		Symbol	Limit		Unit
	Method	Conditions		Min	Max	
Subgroup 2 - Continued.						
Forward-current transfer ratio	3076	V_{CE} = 10 V dc; I_C = 10 mA dc; pulsed (see 4.5.1)	[h_{FE3}] 5/			
2N2218				[17.5]		
2N2219				[37.5]		
2N2218A, 2N2218AL				[20]		
2N2219A, 2N2219AL				[50]		
Forward-current transfer ratio	3076	V_{CE} = 10 V dc; I_C = 150 mA dc; pulsed (see 4.5.1)	[h_{FE4}] 5/			
2N2218				[20]	120	
2N2219				[50]	300	
2N2218A, 2N2218AL				[20]	120	
2N2219A, 2N2219AL				[50]	300	
Forward-current transfer ratio	3076	V_{CE} = 10 V dc; I_C = 500 mA dc; pulsed (see 4.5.1)	[h_{FE5}] 5/			
2N2218				[10]		
2N2219				[15]		
2N2218A, 2N2218AL				[10]		
2N2219A, 2N2219AL				[15]		
Collector-emitter saturation voltage	3071	I_C = 150 mA dc; I_B = 15 mA dc; pulsed (see 4.5.1)	$V_{CE(sat)1}$			
2N2218, 2N2219					0.46	V dc
2N2218A, 2N2219A					0.35	V dc
2N2218AL, 2N2219AL					0.35	V dc
Collector-emitter saturation voltage	3071	I_C = 500 mA dc; I_B = 50 mA dc; pulsed (see 4.5.1)	$V_{CE(sat)2}$			
2N2218, 2N2219					1.84	V dc
2N2218A, 2N2219A					1.15	V dc
2N2218AL, 2N2219AL					1.15	V dc
Base-emitter saturation voltage	3066	Test condition A; I_C = 150 mA dc; I_B = 15 mA dc; pulsed (see 4.5.1)	$V_{BE(sat)1}$			
2N2218, 2N2219				0.6	1.50	V dc
2N2218A, 2N2219A				0.6	1.38	V dc
2N2218AL, 2N2219AL				0.6	1.38	V dc
Base-emitter saturation voltage	3066	Test condition A; I_C = 500 mA dc; I_B = 50 mA dc; pulsed (see 4.5.1)	$V_{BE(sat)2}$			
2N2218, 2N2219					3.0	V dc
2N2218A, 2N2219A					2.3	V dc
2N2218AL, 2N2219AL					2.3	V dc

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:52Z
Check the source to verify that this is the current version before use.

TABLE II. Group D inspection - Continued.


1/ Tests to be performed on all devices receiving radiation exposure.
2/ For sampling plan, see MIL-PRF-19500.
3/ Electrical characteristics apply to device types unless otherwise noted.
4/ See 6.2.e herein.
5/ See method 1019 of MIL-STD-750 for how to determine [h_{FE}] by first calculating the delta ($1/h_{FE}$) from the pre- and post-radiation h_{FE}. Notice the [h_{FE}] is not the same as h_{FE} and cannot be measured directly. The [h_{FE}] value can never exceed the pre-radiation minimum h_{FE} that it is based upon.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:52Z
Check the source to verify that this is the current version before use.

TABLE III. Group E inspection (all quality levels) - for qualification or re-qualification only.

Inspection	MIL-STD-750		Qualification
	Method	Conditions	
Subgroup 1			45 devices c = 0
Temperature cycling (air to air)	1051	Test condition C, 500 cycles	
Hermetic seal	1071		
Fine leak Gross leak			
Electrical measurements		See table I, subgroup 2 herein.	
Subgroup 2			45 devices c = 0
Intermittent life	1037	V_{CB} = 10 V dc, 6,000 cycles, forced air cooling allowed on cooling cycle only. Adjust device current, or power, to achieve a minimum ΔT_J of +100°C.	
Electrical measurements		Table I, subgroup 2 herein.	
Subgroup 4			
Thermal impedance curves		See MIL-PRF-19500, table E-IX, group E, subgroup 4.	
Subgroup 5			
Not applicable			
* Subgroup 6			11 devices
Electrostatic discharge (ESD)	1020		
Subgroup 8			45 devices c = 0
Reverse stability	1033	Condition B.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:52Z
Check the source to verify that this is the current version before use.




NOTES:

1. This is the true inverse of the worst case thermal resistance value. All devices are capable of operating at $\leq T_J$ specified on this curve. Any parallel line to this curve will intersect the appropriate power for the desired maximum T_J allowed.
2. Derate design curve constrained by the maximum junction temperature ($T_J \leq 200°C$) and power rating specified. (See 1.3 herein.)
3. Derate design curve chosen at $T_J \leq 150°C$, where the maximum temperature of electrical test is performed.
4. Derate design curve chosen at $T_J \leq 125°C$, and 110°C to show power rating where most users want to limit T_J in their application.

FIGURE 2. Derating for 2N2218, 2N2218A, 2N2218AL, 2N2219, 2N2219A, and 2N2219AL ($R_{\theta JC}$) (TO-39 and TO-5).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:52Z
Check the source to verify that this is the current version before use.




NOTES:

1. This is the true inverse of the worst case thermal resistance value. All devices are capable of operating at $\leq T_J$ specified on this curve. Any parallel line to this curve will intersect the appropriate power for the desired maximum T_J allowed.
2. Derate design curve constrained by the maximum junction temperature ($T_J \leq 200°C$) and power rating specified. (See 1.3 herein.)
3. Derate design curve chosen at $T_J \leq 150°C$, where the maximum temperature of electrical test is performed.
4. Derate design curve chosen at $T_J \leq 125°C$, and 110°C to show power rating where most users want to limit T_J in their application.

FIGURE 3. Derating for 2N2218, 2N2218A, 2N2218AL, 2N2219, 2N2219A, and 2N2219AL ($R_{\theta JA}$) (TO-39 and TO-5).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:52Z
Check the source to verify that this is the current version before use.




T_A = +25°C, 800 mW, Thermal resistance $R_{\theta JA}$ = 195°C/W

FIGURE 4. Thermal impedance graph ($R_{\theta JA}$) for 2N2218, 2N2218A, 2N2218AL, 2N2219, 2N2219A, and 2N2219AL (TO-39 and TO-5).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:52Z
Check the source to verify that this is the current version before use.


Maximum Thermal Impedance



T_C = +25°C, 3.0 W; Thermal resistance $R_{\theta JC}$ = 50°C/W

FIGURE 5. Thermal impedance graph ($R_{\theta JC}$) for 2N2218, 2N2218A, 2N2218AL, 2N2219, 2N2219A, and 2N2219AL (TO-39 and TO-5).


Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:52Z
Check the source to verify that this is the current version before use.



NOTES:

1. The rise time (t_r) of the applied pulse shall be ≤ 2.0 ns, duty cycle ≤ 2 percent and the generator source impedance shall be 50 ohms.
2. Sampling oscilloscope: Z_{in} ≥ 100 K ohms, C_{in} ≤ 12 pF, rise time ≤ .2 ns.

FIGURE 6. Saturated turn-on switching time test circuit.



NOTES:

1. The rise time (t_r) of the applied pulse shall be ≤ 2.0 ns, duty cycle ≤ 2 percent and the generator source impedance shall be 50 ohms.
2. Sampling oscilloscope: Z_{in} ≥ 100 K ohms, C_{in} ≤ 12 pF, rise time ≤ .2 ns.

FIGURE 7. Saturated turn-off switching time test circuit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:52Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the Military Service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory. The notes specified in MIL-PRF-19500 are applicable to this specification.)

6.1 Intended use. Semiconductors conforming to this specification are intended for original equipment design applications and logistic support of existing equipment.

* 6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

b. Packaging requirements (see 5.1).


c. Lead finish (see 3.4.1).

* d. The complete PIN, see 1.5 and 6.4.

e. For acquisition of RHA designed devices, table II, subgroup 1 testing of group D is optional. If subgroup 1 testing is desired, it must be specified in the contract.

* 6.3 Qualification. With respect to products requiring qualification, awards will be made only for products which are, at the time of award of contract, qualified for inclusion in Qualified Manufacturers List (QML 19500) whether or not such products have actually been so listed by that date. The attention of the contractors is called to these requirements, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. Information pertaining to qualification of products may be obtained from DLA Land and Maritime, ATTN: /VQE, P.O. Box 3990, Columbus, OH 43218-3990 or e-mail vqe.chief@dla.mil . An online listing of products qualified to this specification may be found in the Qualified Products Database (QPD) at https://assist.dla.mil.

* 6.4 PIN construction example. The PINs for encapsulated devices are construction using the following form.



Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:52Z
Check the source to verify that this is the current version before use.

* 6.5 List of PINs. The following is a list of possible PINs available on this specification sheet.

PINs for types 2N2218, and 2N2219			
JAN2N2218	JANTXV2N2218	JANTXVR2N2218	JANS#2N2218 (1)
JAN2N2218A	JANTXV2N2218A	JANTXVR2N2218A	JANS#2N2218A (1)
JAN2N2218AL	JANTXV2N2218AL	JANTXVR2N2218AL	JANS#2N2218AL (1)
JAN2N2219	JANTXV2N2219	JANTXVR2N2219	JANS#2N2219 (1)
JAN2N2219A	JANTXV2N2219A	JANTXVR2N2219A	JANS#2N2219A (1)
JAN2N2219AL	JANTXV2N2219AL	JANTXVR2N2219AL	JANS#2N2219AL (1)
JANTX2N2218	JANS2N2218	JANTXVF2N2218	
JANTX2N2218A	JANS2N2218A	JANTXVF2N2218A	
JANTX2N2218AL	JANS2N2218AL	JANTXVF2N2218AL	
JANTX2N2219	JANS2N2219	JANTXVF2N2219	
JANTX2N2219A	JANS2N2219A	JANTXVF2N2219A	
JANTX2N2219AL	JANS2N2219AL	JANTXVF2N2219AL	

(1) The # represents one of eight RHA designators available (M, D, P, L, R, F, G, or H).

* 6.6 Changes from previous issue. The margins of this specification are marked with asterisks to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

Custodians:
Army - CR
Navy - EC
Air Force - 85
NASA - NA
DLA - CC

Review activities:
Army - AR, MI, SM
Navy - AS, MC, SH
Air Force - 19, 71, 99

Preparing activity:
DLA - CC

(Project 5961-2015-018)

* NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil .

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:52Z
Check the source to verify that this is the current version before use.