# MILITARY SPECIFICATION

## CANISTER, MINE PRACTICE, M56 SUBSYSTEM

This specification is approved for use by all Departments and Agencies of the Department of Defense.

### 1. SCOPE

1.1 This specification covers the inspection, tests and assembly for the Mine Practice Canister Assembly used in the M56 Mine, Aircraft Dispersing Subsystem.

### 2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bid or requests for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-2550 - Ammunition, General Specification For

STANDARDS

FEDERAL

FED-STD-151 - Metals; Test Methods

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)
MIL-STD-109 - Quality Assurance Terms and Definitions
MIL-STD-286 - Propellants, Solid, Sampling, Examination and Testing
MIL-STD-810B- Military Standard Environmental Test Methods for Aerospace and Ground Equipment

FSC: 1345

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:38Z
Check the source to verify that this is the current version before use.

MIL-STD-1168- Lot Numbering of Ammunition
MIL-STD-1235- Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes.

DRAWINGS

U.S. ARMY PICATINNY ARSENAL

PRODUCT AND PACKAGING DRAWINGS

9255991 - Canister, Mine Practice
9294996 - Packaging and Marking For Shipping and Storage Container: M602 For Canister, Mine, Practice and Mine Canister Assembly; Training

(Copies of specifications; standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer).

2.2 Other publications. - The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on the date of invitation for bids shall apply.

CODE OF FEDERAL REGULATIONS, TITLE 49 - TRANSPORTATION, PARTS 0-190

(The Code of Federal Regulations is available from the Superintendent of Documents, U.S. Government Printing Office, Washington D.C. 20402. Orders shall specify CFR 0-190 (latest revision)).

3. REQUIREMENTS

3.1 Material. - Materials shall be in accordance with the applicable drawings and specifications.

3.2 Assembly. - The Mine Practice Canister Assembly shall comply with all requirements specified on drawing (dwg.) No. 9255991, as applicable, all associated drawings and with all requirements specified in applicable specifications.

3.3 Obturator Seal. - The leak rate through the obturator seal in the cylinder with the rivets in place but prior to riveting shall not exceed twenty (20) cubic feet per hour when

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:38Z
Check the source to verify that this is the current version before use.

a pressure of twenty plus two pounds per square inch (20 + 2 psi) is applied through the cylinder propagation hole.

3.4 Workmanship. - All parts and assemblies shall be fabricated and finished in a thorough, workmanlike manner. They shall be free of burrs, chips, sharp edges, cracks, unblended radii, surface defects, dirt, grease, rust, corrosion products, and other foreign matter. The cleaning method used shall not be injurious to any parts, nor shall the parts be contaminated by the cleaning agents. All marking and stamping shall be neat and sharply defined.

3.5 Submission of results of contractor-conducted examinations and tests. - The contractor shall forward copies of the result of any of his examinations or tests to the designated address as specified in 6.4.

3.6 First article inspection. - This specification makes provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

## 4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for Inspection.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to MIL-STD-109 to define terms used herein. The provisions of MIL-A-2550 shall apply.

4.1.1 Submission of Product.-At the time each completed lot of items deliverable under the contract is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted.

a. A statement that the lot complies with all of the quality assurance provisions specified in this specification.



Source: https://assist.dla.mil -- Downloaded: 202640-22T19:38Z
Check the source to verify that this is the current version before use.

b. Drawing and specification number and date, together with identification and date of changes thereto.

c. A statement that all material purchased by the contractor meets requirements, when such material is controlled by Government or commercial specifications referenced in any of the contractual documents, and that certificates of conformance are on file and available for review.

d. Number of items in the lot.

e. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agents authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.2 First Article Inspection

4.2.1 Submission.-Prior to the start of regular production the contractor shall submit a first article sample (see 6.1c) to a Government approved facility as designated by the contracting officer for evaluation in accordance with the provisions of 4.2.2 and 4.2.3. The first article sample shall consist of:

| Component | No. of Parts |
|---|---|
| Plug, End (9289305) | 5 |
| Body, Dummy (9289304) | 5 |
| Body, Assembly (Dummy) (9289303) | 5 |
| Fin and Retainer Assembly (9289306) | 5 |
| Canister, Mine Practice (9255991) | 5 |

All parts and materials including packaging and packing shall be obtained from the same source of supply as will be used in regular production. Prior to submission, the contractor shall inspect the sample to the degree necessary to assure that it conforms to the requirements of the contract and submit a record of this inspection with the sample, including a certificate of conformance for materials. A sample containing known defects will not be submitted unless specifically authorized by the Contracting Officer. A first article sample, or portion thereof, as directed by the Contracting Officer, shall be submitted whenever there is a lapse in production for a period in excess of 90 days or whenever a change occurs in



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:38Z
Check the source to verify that this is the current version before use.

manufacturing process, material used, drawing or specification such as to significantly affect product uniformity as determined by the Government.

4.2.2 Inspections to bePerformed. - The components, subassemblies and assemblies will be subjected by the Government to any or all of the examinations and tests specified in this specification and any or all of the requirements of the applicable drawings.

4.2.3 Rejection. - If any component, sub-assembly or assembly fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate its inspection upon any failure of an inert component, sub-assembly or assembly to comply with any of the stated requirements.

4.3 Inspection provisions

4.3.1 Lot formation.-The term "inspection lot" as used in this specification is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance with applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer in one unchanged process using the same materials and methods in accordance with the same drawings, same drawing revisions, same specifications and same specification revisions and complies with the provisions for submission of product as specified in MIL-STD-105. Changes to the process, specifications, or drawings not affecting safety, performance, interchangeability, or storage, as determined by the Government, shall not be deemed to alter the homogeneity of an inspection lot. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein regardless of the type of sampling procedure which is being applied to determine conformance with requirements. Lot numbering, as required, shall be in accordance with MIL-STD-1168.

4.3.2 Examination.-The examinations listed in the following subparagraphs shall be performed on inspection lots (see 4.3.1) of the components or assemblies designated in the appli-



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:38Z
Check the source to verify that this is the current version before use.

cable paragraph headings. Inspection for critical defects (and major defects, when so specified) shall be 100 percent. Sampling plans for major and minor defects shall be in accordance with MIL-STD-105 except that continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the Government. Instead of applying the AQL's designated herein to the groups of major and minor defects listed, the contractor may elect to apply an AQL of 0.40 percent for each major defect and an AQL of 0.65 percent for each minor defect. When this method is elected, it shall be applied to all of the major and minor defects listed in the applicable sub-paragraph of this section, except where 100 percent inspection is specified, and be documented as part of the contractor's inspection system. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.3.4.

4.3.2.1 Plug, End: (see dwg. 9289305 covering a detail of dwg. 9255991).

| Categories | Defects | Method of Inspection | Code No. (see 6.2) |
|---|---|---|---|
| Critical: None defined. | | | |
| Major: None defined. | | | |
| Minor: | AQL 1.50 percent | | |
| 101. | Diameter | Gage | 01001 |
| 102. | Thickness | Gage | 01002 |
| 103. | Evidence of poor workmanship (see 3.4) | Visual | 01003 |

4.3.2.2 Body, Dummy: (see dwg. 9289304 covering a detail of dwg. 9255991).

| Categories | Defects | Method of Inspection | Code No. |
|---|---|---|---|
| Critical: None defined. | | | |
| Major: | AQL 0.40 percent | | |
| 101. | Overall length, max | Gage | 02001 |
| 102. | Location of rivet holes (4 places) | Gage | 02002 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:38Z
Check the source to verify that this is the current version before use.

| | | | |
|---|---|---|---|
| Minor: | | AQL 4.00 percent | |
| 201. | Diameter of rivet holes | Gage | 02003 |
| 202. | Diameter of screw holes | Gage | 02004 |
| 203. | Diameter of large opening | Gage | 02005 |
| 204. | Diameter of end plug recess min (2 places) | Gage | 02006 |
| 205. | Depth of end plug recess, min | Gage | 02007 |
| 206. | Bottom radius | Gage | 02008 |
| 207. | Major height, max | Gage | 02009 |
| 208. | Location of pressure plate | Gage | 02010 |
| 209. | Evidence of poor workmanship (see 3.4) | Visual | 02011 |

4.3.2.3 Body Assembly (Dummy): (see dwg. 9289303 covering a detail of dwg. 9255991).

| Categories | Defects | Method of Inspection | Code No. |
|---|---|---|---|
| Critical: | None defined. | | |
| Major: | AQL 0.40 percent | | |
| 101. | Pin and retainer assembly loose or missing | Visual | 03001 |
| Minor: | AQL 1.50 percent | | |
| 201. | End plugs not properly staked | Visual | 03002 |
| 202. | Tapping screws loose or missing | Visual | 03003 |
| 203. | Evidence of poor workmanship (see 3.4) | Visual | 03004 |

4.3.2.4 Pin and Retainer Assembly: (see dwg. 9289306 covering a detail of dwg. 9255991).

| Categories | Defects | Method of Inspection | Code No. |
|---|---|---|---|
| Critical: | None defined. | | |
| Major: | None defined. | | |
| Minor: | AQL 1.50 percent | | |
| 201. | Any fin damaged or missing | Visual | 04001 |
| 202. | Any fin spring missing | Visual | 04002 |
| 203. | Any rod end not properly swaged | Visual | 04003 |
| 204. | Evidence of poor workmanship (see 3.4) | Visual | 04004 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:38Z
Check the source to verify that this is the current version before use.

4.3.2.5 Canister, Mine Practice: (see dwg. 9255991).

| Categories | Defects | Method of Inspection | Code No. |
|---|---|---|---|
| Critical: | | | |
| 1. | Any cartridge shorting clip damaged or missing | Visual | 05001 |
| Major: | 100 percent inspection | | |
| 101. | Any cartridge terminal damaged or missing | Visual | 05002 |
| 102. | Cartridge O-Ring missing | Visual | 05003 |
| 103. | Improper torque on cartridge | Visual | 05004 |
| Major: | AQL 0.40 percent | | |
| 101. | Obturator missing | Visual | 05005 |
| 102. | Any rivet missing | Visual | 05006 |
| Minor: | AQL 1.00 percent | | |
| 201. | Canister markings incorrect, illegible or missing | Visual | 05007 |
| 202. | Evidence of poor workmanship (see 3.4) | Visual | 05008 |

4.3.3 Testing

4.3.3.1 Obturator Seal (see 3.3) - Major Defect - Code No. 05009. - The lot shall be tested 100 percent for the specified requirement in accordance with 4.4.1 using equipment specified in 4.3.4. All mines classed defective shall be removed from the lot.

4.3.3.2 Cartridge Torquing (dwg. 9255991) - Major Defect - Code No. 05010. - One hundred and twenty-five (125) canisters shall be randomly selected from each lot and tested for the torquing requirement in accordance with 4.4.2 using equipment specified in 4.3.4. The lot shall be rejected if two (2) or more samples are classed defective.

4.3.3.3 Cartridge Bridgewire Resistance (see dwg. 9287785 covering a detail of dwg. 9255991) - Major Defect - Code No. 05011. The lot shall be tested 100 percent for the specified requirement in accordance with 4.4.3 using equipment specified in 4.3.4 All assemblies classed defective shall be removed from the lot.



Source: https://assist.dla.mil -- Downloaded: 202610-22T19:38Z
Check the source to verify that this is the current version before use.

4.3.4 Inspection Equipment.-Inspection equipment required to perform the inspections prescribed in this specification is identified in the Examination (4.3.2) and Test Method (4.4) paragraphs herein. See 6.3 for details concerning responsibilities for inspection design and approval.

4.4 Test Methods and Procedures

4.4.1 Obturator Seal. - The canister assembly shall be mounted in an approved fixture and tested for the specified leakage rate. The assembly shall be classed defective if it fails to comply with all of the applicable requirements. (Non-destructive test).

4.4.2 Cartridge Torquing. - The cartridge shall be torqued into the cylinder using an approved torque wrench and adapter socket. Any assembly failing to comply with all of the requirements shall be classed defective. (Non-destructive test)

4.4.3 Cartridge Resistance (In Cylinder). - Each canister assembly shall have the primer to canister resistance measured using an approved digital ohmmeter. Any canister failing to comply with all of the specified requirements shall be classed defective. (Non-destructive test)

5. PREPARATION FOR DELIVERY

5.1 Preservation and Packaging

5.1.1 Level A. - The practice mine canister assemblies shall be preserved and packaged in accordance with dwg. 9294996.

5.1.2 Packaging. - The cartridge assembly shall be packaged in accordance with the Code of Federal Regulations, CFR 49 parts 0-190.

5.2 Packing

5.2.1 Level A. - The practice mine canister assemblies shall be packed in accordance with dwgs. 9294996 and CFR 49 parts 0-190.

5.3 Marking. - Marking of the carton shall comply with level A, dwg. 9294996. Markings shall also specify the part nomenclature and Class of Explosive as well as a note, HANDLE CAREFULLY.



Source: https://assist.dla.mil -- Downloaded: 202640-22T19:38Z
Check the source to verify that this is the currentversion before use.

5.4 Shipping. - When components of more than one lot are shipped as a carload, each lot shall be kept separate, and the division between lots clearly indicated to prevent mixing of the lots in transit.

6. NOTES

6.1 Ordering data.-Procurement documents shall specify the following:

a. Title, number and date of this specification.
b. Data cards. - Data cards shall be prepared for each lot in accordance with the information specified in Standard MIL-STD-1167.
c. Provisions for submission of first article samples.

6.2 Inspection code numbers.-The five digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government. They should be cited as references on drawings of equipment designs submitted by the contractor to the Government for approval (see 6.3.3).

6.3 Inspection Equipment Designs.-Inspection equipment designs are of two types - Government Special Inspection Equipment (SIE) designs and contractor designs. SIE designs are designated by drawing numbers under the "Method of Inspection" headings in Section 4. Design responsibility for all other inspection equipment is assigned to the contractor. The contractor need not furnish any design when a complete Government SIE design is provided. Unless otherwise specified, however, the contractor may submit alternate or modified contractor designs of SIE in accordance with 6.3.2 and 6.3.3 should he elect to do so.

6.3.1 SIE designs.-SIE designs may consist of any of the following:

a. Detailed drawings which completely depict all information necessary for the fabrication and use of the item of inspection equipment.
b. A source control drawing or a specification control drawing as defined in MIL-STD-100.
c. An envelope drawing, as defined in MIL-STD-100, which establishes the criteria which a detailed design shall meet. When envelope drawings are specified, the contractor shall prepare designs which comply with the criteria therein.



Source: https://assist.dla.mil -- Downloaded: 202640-22T19:38Z
Check the source to verify that this is the currentversion before use.

6.3.2 Contractor designs.-Contractor designs are required for all inspection equipment for which SIE designs are not specified and may include commercial equipment which the contractor proposes to use. (Commercial equipment is defined as unmodified equipment which is cataloged and available for purchase by the general public). Contractor designs shall include appropriate operating instructions, calibration procedures and maintenance procedures. Commercial equipment shall be fully described by catalog listings or other means which provide sufficient information to permit identification and evaluation by the Government and may include illustrations and engineering data. Designs shall be prepared for any special fixture(s) required to be used with commercial equipment, or with SIE designs if not otherwise covered thereby (see 6.3.1c). Designs shall be of the category and form (per MIL-D-1000) specified in the Contract Data Requirements Lists (DD Form 1423). The contractor is referred to MIL-HDBK-204, "Inspection Equipment Design" for guidance. The specification number and the applicable five digit defect code number (or other specific identifying information) from Section 4 of this specification shall be referenced on each contractor design together with the component or assembly drawing number and revision letter to which the specific design applies.

6.3.3 Submission of Designs for Approval.-Contractor designs shall be approved by the Government prior to fabricating or procuring the equipment. Designs shall be submitted for approval to Picatinny Arsenal, ATTN: SARPA-QA-A-M, Dover, New Jersey 07801 in accordance with the stipulations, time frame and distribution specified in the Contract Data Requirements List (DD Form 1423) or in the contract. The contractor must include in his sub-designs which will be utilized. Partial submission of inspection designs is permissible and encouraged. However, the completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will normally be accomplished within one month after receipt.

6.4 Submission of results of contractor conducted examinations and tests (see 3.8). - The contractor shall send his results to:

Commander
Picatinny Arsenal
ATTN: SARPA-QA-A-M
Dover, New Jersey 07801

Custodian:
Army-PA

Preparing Activity:
Army-PA

Project Number: 1345-A-100



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:38Z
Check the source to verify that this is the current version before use.

# STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

**DD FORM 1 JAN 72 1426** REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:38Z
Check the source to verify that this is the current version before use.