MILITARY SPECIFICATION

FUZE, MINE, COMBINATION M10A2, PARTS FOR

1. SCOPE

1.1 This specification covers the metal parts for one type of fuze, designated as Mine, Combination, Practice, M10A2.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposala, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-2550 – Ammunition and Special Weapons; General Specification for.

MIL-P-10025 – Packing and Marking for Domestic Shipment of Inert Ammunition Components; General Specification for.

MIL-I-45208 – Inspection Requirements, General Specification for.

MIL-I-45607 – Inspection Equipment, Supply and Maintenance of.

STANDARDS

MILITARY

MIL-STD-105D – sampling Procedures and Tables for Inspection by Attributes.

MIL-STD-109 – Quality Assurance - Terms and Definitions.

MIL-STD-171 – Systems for Preparation Painting, and Finishing and Wood Surfaces.

MIL-STD-1235 – Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

FSC 1345

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:04Z
Check the source to verify that this is the current version before use.

DRAWINGS

ORDNANCE CORPS

8866643 — Fuze, Mine, Combination, M 10 A 2, Assembly.

8882274 — Box, Packing, for Fuze, Mine, Combination, M10A2, Less Igniter Assembly.

PUBLICATIONS

ORDNANCE CORPS

IEL-9200011 — Index of Inspection Equipment Lists.

(Copies of specifications, **standards,** drawings and publications required by suppliers in connection **with** specific procurement functions should he obtained from the procuring activity **or as** directed by the contracting officer.)

3. REQUIREMENTS

3.1 Material. Materials and parts shall be in accordance with applicable drawings and specifications.

3.2 Assembly. The parts assembly shall comply with all requirements specified on Drawing (dwg.) 8866643 and with all requirements specified in applicable specifications.

3.3 Embrittlement of springs. Pressure springs, pull springs, firing pin springs and release pin springs shall not break when extended to the minimum point of permanent distortion when tested as specified in 4.4.3.

3.4 Nonfunctioning. The metal parts assembly shall not function when a load, not to exceed 3.0 pounds, is applied to the release pin ring parallel to the axis of the **release** pin and when a load, not to exceed 8.0 pounds, is applied to any one prong or equally distributed upon all three prongs parallel to the axis of the assembly when tested as specified in 4.4.1.

3.5 Functioning. The metal parts assembly shall function when a load, not to exceed 10 pounds is applied to the release pin ring parallel to the axis of the release pin and when a load, not to exceed 20 pounds is applied to any one prong or equally distributed upon all three prongs parallel to the axis of the head assembly. The test shall be performed as specified in 4.4.2,

3.6 Workmanship. All parts shall be fabricated and finished in a thorough, workmanlike manner. They shall be free of burrs, chips, sharp edges, cracks, unblended radii, surface defects, dirt, grease, rust, corrosion, and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent. All required markings shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 General quality assurance provisions. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified, the supplier may utilize his own or any other inspection facilities and services acceptable to the Government. Inspection records of the examinations and tests shall be kept complete and available to the Government as specified in the contract or order. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements. Reference shall be made to Standard MIL-STD-109 in order to define terms used herein. The provisions **of** Specification MIL-A-2550 shall apply.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:04Z
Check the source to verify that this is the current version before use.

4.1.1 *Contractor* quality ***assurance*** **system.** The contractor shall provide and maintain an effective quality assurance system in compliance with the requirements of Specification MIL-I-45208. The contractors quality assurance system shall contain a procedure for the reporting of critical defective found during the course of his inspection and during inspection by the Government. Any critical defect encountered, unless annotated by an asterisk (*) to the right of the characteristic code number (see 6.2), will be ***reported*** within 48 hours. A monthly summary report covering those critical defects annotated by an asterisk will be furnished. The agencies to whom the reports will be furnished are identified in paragraph 6.6. The reports shall contain, as a minimum, the following information:

(a) Contractor and contract number.

(b) Number and ***revision*** date ***of*** ***specification.***

(c) Characteristic Code Number.

(d) Lot or serial number.

(e) Number of defectives ***found.***

(f) Assignable cause or analysis of occurrence.

(g) Corrective action taken **or** recommended. When the corrective action is beyond the control *of* the contractor or the scope of contract, the report shall contain the contractor's recommendation to the Government.

4.1.2 ***Submission of*** product. At the time the completed lot ***of*** product is submitted to the Government for acceptance the ***con***tractor shall supply the following information accompanied by **a** ***certificate*** which attests that the information provided is correct and applicable to the product being submitted:

(a) A statement that the lot complies with ***all*** quality assurance pro. visions ***of*** the approved current written description of the system.

(b) Number of units of **product** inspected.

(c) Results obtained for all inspection performed

(d) Drawing. specification number and date, together with an identification **and** date of changes.

(e) Certificates of compliance on 811 material purchased directly by the contractor when such material is controlled by Government specifications referenced is **any** of the contractual documents.

(f) Number of items in the lot. .

(g) Date submitted.

The certificate shall be signed by a responsible agent ***of*** the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation ***of*** the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.1.3 Government verification Using the contractor's written quality assurance procedure, this detail specification, the applicable drawings and other contractual documents as a guide, the Government inspector will verify at unscheduled intervals all quality assurance operations performed by the contractor. Verification will be in accordance with Specification MIL-I-45208 and will be performed to the extent necessary to assure compliance with the contrac-

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:04Z
Check the source to verify that this is the current version before use.

tual requirements. Severity of Government inspection of individual characteristic will be directly related to the seriousness of the classification assigned. In no instance will a characteristic classified "critical" be accepted soley on the basis of the contractor's records.

4.2 Initial production inspection.

4.2.1 Submission. Prior to normal production the contractor shall submit an initial production sample consisting of (*) consecutively produced assemblies and complete sets of parts (i.e. 50 each of every individual component and subassembly), which have been produced by the production process which the contractor been use in f fulfilling the contract, to a Government-approved facility designated by the contracting officer. All parts and materials shall be obtained from the same source of supply as will be used in regular production. The initial production sample shall be accompanied by certificates of analyses for all materials A sample l hmll also be submitted whenever a change occurs in manufacturing process, material used, drawing, specification, or source of supply such as to significantly affect product uniformity as determined by the Government.

4.2.2 Inspections to be performed. Each assembly and component shall be inspected by the Government for all the inspection specified in 4.3.2 and 4.8.9 of this specification and for all additional requirements of the applicable drawings.

4.2.3 Rejection. If any assembly 'r component fails to comply with the applicable requirements, the initial production sample shall be rejected. In the event of rejection, the Government reserves the right to require the contractor to take corrective action' and submit new or supplemental quantities until such time as an acceptable sample is submitted, or until otherwise directed by the contracting officer.

4.3 Inspection provisions.

4.3.1 Lot formation. A lot shall consist of parts produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification, and same specification revision. Drawing, specifications, and process changes not affecting safety performance or fit, as determined by the Government shall not necessitate changing the lot number.

4.3.2 Examination. Sampling plans and procedures for the following classifications of defects shall be in accordance with Standard MIL-STD-165D except that inspection for critical defects, when listed, shall be 100 percent. Continuous sampling plans in accordance with Standard MIL-STD-1235 may be used if approved by the procuring activity. Also, at the option of the procuring activity, AQL's and sampling plans may be applied to the individual characteristics listed using an AQL of 0.26 percent for each major defect and an AQL of 0.40 percent for each minor defect. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.8.4.

4.6.2.1 Gasket (see dwg.) 8866649 covering a detail of dwg. 8866648

Categories	*Defects*	*Method of inspection*
Critical: None defined		
Major:	**AQL 0.25 percent**	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:04Z
Check the source to verify that this is the current version before use.

101. Inside diameter		Gage	01001
Minor:	**AQL 1.50 percent**		
201. Outside diameter		Gage	01002
202. Thickness		Gage	01003
203. Evidence of poor workmanship (see 3.6)		Visual	01004

4.3.2.2 Prong (see dwg. 8666665 covering a detail of dwg. 8666643).

Categories	*Defects*	*Method of inspection*	*Code No.*
Critical:	**None defined**		
Major:	**AQL 0.65 percent**		
101. Diameter		Gage	02001
102. Length		Gage	02002
103. Length to top of flat		Gage	02003
104. Length of flat		Gage	02004
105. Width of flat		Gage	02005
Minor:	**AQL 0.40 percent**		
201. Evidence of poor workmanship (see 3.6)		Visual	02006

4.3.2.8 Spring, pressure (see dwg. 8866657 covering a detail of dwg. 8866643).

Categories	*Defects*	*Method of inspection*	*Code No.*
Critical:	**None defined**		
Major:	**AQL 0.65 percent**		
101. Inside diameter		Gage	03001
102. Outside diameter		Gage	03002
103. Solid length		Gage	03003
104. Load at compressed length of .44 inch		Measure	03004
105. Load at compressed length of .25 inch		Measure	03005
Minor:	**AQL 0.40 percent**		
201. Evidence of poor workmanship (see 3.6)		Visual	03006

4.3.2.4 Spring, pull (see dwg. 8866658 covering a detail of dwg. 8866643).

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:04Z
Check the source to verify that this is the current version before use.

Categories	Defects	Method of inspection	Code No.
Critical:	**None defined**		
Major:	**AQL 0.40 percent**		
	101. Inside diameter	Gage	04001
	102. Outside diameter	Gage	04002
	103. Solid length	Gage	04003
	104. Load at compressed length of .2 inch	Measure	04004
Minor:	**AQL 0.40 percent**		
	201. Evidence of poor workmanship (see 3.6)	Visual	04005

4.3.2.5 *Spring, firing pin* (see dwg. 8866659 covering a detail of dwg. 8866643).

Categories	Defects	Method of inspection	Code No.
Critical:	**None defined**		
Major:	**AQL 0.40 percent**		
	101. Inside diameter	Gage	05001
	102. Outside diameter	Gage	05002
	103. Solid height	Gage	05003
	104. Load at compressed length of .84 inch	Measure	05004
Minor:	**AQL 0.40 percent**		
	201. Evidence of poor workmanship (see 3.6)	Visual	05005

4.3.2.6 *Ring, pin, release* (see dwg. 8866660 covering a detail of dwg. 8866643).

Categories	Defects	Method of inspection	Code No.
Critical:	**None defined**		
Major:	**None defined**		
Minor:	**AQL 1.50 percent**		
	201. Inside diameter	Gage	06001
	202. Wire thickness	Gage	06002
	203. Evidence of poor workmanship (see 3.6)	Visual	06003

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:04Z
Check the source to verify that this is the current version before use.

4.3.2.7 *Plug* (see dwg. 8866646 covering a detail of dwg. 8866643).

Categories	*Defects*	*Method of inspection*	*Code No.*
Critical: None defined			
Major:	AQL 0.65 percent		
101.	Outside diameter	Gage	07001
102.	Inside diameter	Gage	07002
103.	Total length	Gage	07003
104.	Length of straight portion of outside diameter	Gage	07004
105.	Angle of taper	Gage	07005
106.	Concentricity of inside diameter with straight portion of outside diameter	Gage	07006
Minor:	AQL 0.40 percent		
201.	Evidence of poor workmanship (see 3.6)	Visual	07007

4.3.2.8 *Pin, release* (see dwg. 8866648 covering a detail of dwg. 8866643).

Categories	*Defects*	*Method of inspection*	*Code No.*
Major:	AQL 1.50 percent		
101.	Body diameter	Gage	08001
102.	Height to flat on body	Gage	08002
103.	Diameter of release pin shaft	Gage	08003
104.	Diameter of firing pin hole	Gage	08004
105.	Width of firing pin slot	Gage	08005
106.	Length to end of firing pin slot	Gage	08006
107.	Total length	Gage	08007
108.	Length of body	Gage	08008
109.	Length of hemicylindrical portion	Gage	08009
110.	Length to hemicylindrical portion	Gage	08010
111.	Angle of taper	Gage	08011
112.	Diameter of cotter pin hole	Gage	08012
113.	Length from cotter pin hole to firing pin hole	Gage	08013
114.	Radii missing	Visual	08014
Minor:	AQL 1.50 percent		
201.	Diameter of release pin ring hole	Gage	08015

Source: https://assist.dla.mil -- Downloaded: 202640-23T00:04Z
Check the source to verify that this is the currentversion before use.

202. Length from firing pin hole to release pin ring hole		Gage	08016
203. Evidence of poor workmanship (see 3.6)		Visual	08017

4.3.2.9 *Pin, firing* (see dwg. 8866654 covering a detail of dwg. 8866643).

Categories	*Defects*	*Method of inspection*	*Code No.*
Critical:	**None defined**		
Major:	**AQL 1.50 percent**		
101.	Total length	Gage	09001
102.	Length to top end of flat	Gage	09002
103.	Length from safety pin hole to top end of flat	Gage	09003
104.	Length of flat	Gage	09004
105.	Diameter of safety pin hole	Gage	09005
106.	Outside diameter	Gage	09006
107.	Thickness of flat	Gage	09007
108.	Diameter of tip	Gage	09008
109.	Radius of tip	Gage	09009
110.	Length of tip	Gage	09010
111.	Diameter of washer retainer	Gage	09011
112.	Length of washer retainer	Gage	09012
113.	Radii from flat to shank inadequate	Visual	09013
Minor:	**AQL 2.50 percent**		
201.	Flat on lower shank, max	Gage	09014
202.	Flat on washer retainer, max	Gage	09015
203.	Profile of upper end	Gage	09016
204.	Angular relation of flat to safety pin hole	Gage	09017
205.	Evidence of poor workmanship (see 3.6)	Visual	09018

4.3.2.10 *Washer* (see dwg. 8866656 covering a detail of dwg. 8866643).

Categories	*Defects*	*Method of inspection*	*Code No.*
Critical:	**None defined**		
Major:	**AQL 0.65 percent**		
101.	Inside diameter	Gage	10001
102.	Outside diameter described by points	Gage	10002

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:04Z
Check the source to verify that this is the current version before use.

103.	Diameter described by bases of points	Gage	10003
104.	Thickness	Gage	10004
105.	Radii missing or inadequate	Visual	10005

Minor: AQL 0.40 percent

201.	Evidence of poor workmanship (see 3.6)	Visual	10006

4.3.2.11 *Pin, safety, firing pin* (see dwg. 8866661 covering a detail of dwg. 8866643).

Categories	*Defects*	*Method of inspection*	*Code No.*

Critical: None defined

Major: AQL 0.65 percent

101.	Thickness	Gage	11001
102.	Length of opening at end	Gage	11002
103.	Width of opening at end	Gage	11003
104.	Radius at closed end	Gage	11004
105.	Radius at mid point	Gage	11005

Minor: AQL 1.50 percent

201.	Length exclusive of closed end	Scale	11006
202.	Length to curved mid portion	Scale	11007
203.	Evidence of poor workmanship (see 3.6)	Visual	11008

4.3.2.12 *Head* (see dwg. 8866644 covering a detail of dwg. 8866643).

Categories	*Defects*	*Method of inspection*	*Code No.*

Critical: None defined

Major: AQL 2.50 percent

101.	Inside diameter at top	Gage	12001
102.	Diameter of trigger pin hole	Gage	12002
103.	Distance to outside of trigger pin keyway	Gage	12003
104.	Width of trigger pin keyway	Gage	12004
105.	Height of inside diameter at top	Gage	12005
106.	Length to release pin hole	Gage	12006
107.	Outside diameter	Gage	12007
108.	Concentricity of outside diameter with inside diameter at top	Gage	12008

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:04Z
Check the source to verify that this is the current version before use.

109.	Length to firing pin spring boss	Gage	12009
110.	Length of case boss	Gage	12010
111.	Length to groove in case boss	Gage	12011
112.	Diameter of case boss	Gage	12012
113.	Diameter at base of case boss groove	Gage	12013
114.	Diameter of firing pin spring boss	Gage	12014
115.	Diameter of small release pin hole	Gage	12015
116.	Profile of large release pin hole	Gage	12016
117.	Diameter of pull spring recess	Gage	12017
118.	Height to outside of release pin boss	Gage	12018
119.	Width of cotter pin slot	Gage	12019
120.	Height to outer end of pull spring release	Gage	12020
121.	Depth of large release pin hole	Gage	12021
122.	Diameter of firing pin hole	Gage	12022
123.	Length from bottom of cotter pin slot to outside of release pin boss	Gage	12023
124.	Length of taper for trigger pin	Gage	12024
125.	Angle of taper for trigger pin	Gage	12025
126.	Diameter at top of taper for trigger pin	Gage	12026
127.	Concentricity of firing pin hole with inside diameter at top	Gage	12027
128.	Concentricity of top of taper for trigger pin with inside diameter at top	Gage	12028
129.	Wall thickness at top end	Gage	12029

Minor: AQL 2.50 percent

201.	Length of chamfer at top	Gage	12030
202.	Length of firing pin spring boss	Gage	12031
203.	Chamfer at bottom missing or inadequate	Visual	12032
204.	Radii missing or inadequate	Visual	12033
205.	Evidence of poor workmanship (see 3.6)	Visual	12034

4.3.2.13 *Case* (see dwg. 8866645 covering a detail of dwg. 8866643).

Categories	*Defects*	*Method of inspection*	*Code No.*

Critical: None defined

Major: AQL 1.00 percent

101.	Length	Gage	13001
102.	Outside diameter	Gage	13002

Source: https://assist.dla.mil -- Downloaded: 202640-23T00:04Z
Check the source to verify that this is the current version before use.

103.	Inside diameter of body	Gage	13003
104.	Diameter of top counterbore	Gage	13004
105.	Length of top counterbore	Gage	13005
106.	Length to beginning of thread	Gage	13006
107.	Length to end of thread	Gage	13007
108.	Inside diameter of counterbore at bottom	Gage	13008
109.	Minor diameter of thread	Gage	13009
110.	Pitch diameter of thread	Gage	13010

Minor: AQL 1.00 percent

201.	Chamfer at top missing or inadequate	Visual	13011
202.	Evidence of poor workmanship (see 3.6)	Visual	13012

4.3.2.14 *Pin, trigger* (see dwg. 8866647 covering a detail of dwg. 8866643).

Categories	*Defects*	*Method of inspection*	*Code No.*
Critical:	None defined		
Major:	AQL 2.50 percent		
101.	Outside diameter at top	Gage	14001
102.	Diameter of firing pin hole	Gage	14002
103.	Concentricity of top outside diameter with firing pin hole	Gage	14003
104.	Height to outside of key	Gage	14004
105.	Diameter of pressure spring boss	Gage	14005
106.	Concentricity of pressure spring boss with firing pin hole	Gage	14006
107.	Outside diameter at bottom	Gage	14007
108.	Concentricity of outside diameter at bottom with firing pin hole	Gage	14008
109.	Width of key	Gage	14009
110.	Diameter of straight portion of plug hole	Gage	14010
111.	Concentricity of straight portion of plug hole with firing pin hole	Gage	14011
112.	Angular spacing of prong grooves	Gage	14012
113.	Lateral offset of ends of prong grooves	Gage	14013
114.	Profile of prong groove	Gage	14014
115.	Taper angle of plug hole	Gage	14015
116.	Length of straight portion of plug hole	Gage	14016
117.	Length of pressure spring boss	Gage	14017
118.	Taper angle of key	Gage	14018
119.	Thickness of end of key	Gage	14019

Source: https://assist.dla.mil -- Downloaded: 202640-23T00:04Z
Check the source to verify that this is the current version before use.

120.	Length of key projection	Gage	14020
121.	Length to pressure spring shoulder	Gage	14021
122.	Depth of plug hole	Gage	14022
123.	Total length	Gage	14023
124.	Lip for crimping inadequate (alternate construction)	Visual	14024

Minor: AQL 0.40 percent

201.	Evidence of poor workmanship (see 3.6)	Visual	14025

4.3.2.15 *Assembly, metal parts* (see dwg. 8866643).

Categories	*Defects*	*Method of inspection*	*Code No.*
Critical:			
1.	Safety pin missing or loose	Visual	15001
2.	Cotter pin missing or loose	Visual	15002
Major:	AQL 0.65 percent		
101.	Head crimp inadequate, cracked or not for 360°	Visual	15003
102.	Case crimp inadequate, not for 360° or not permitting free turning of head	Visual	15004
103.	Components missing, insecure or incorrectly assembled	Visual	15005
104.	Contact surfaces of trigger pin and release pin not greased	Visual	15006
105.	Trigger pin crimp inadequate, cracked, or not for 360°	Visual	15007
Minor:	AQL 0.40 percent		
201.	Evidence of poor workmanship (see 3.6)	Visual	15008

4.3.2.16 *Carton, sealed* (see dwg. 8882278).

Categories	*Defects*	*Method of inspection*	*Code No.*
Critical:	None defined		
Major:	AQL 0.40 percent		
101.	Contents move when carton is shaken	Manual	16001
102.	Carton damaged so that contents are exposed or liable to become exposed	Visual	16002
103.	Closure insecure	Visual-Manual	16003
Minor:	AQL 0.40 percent		

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:04Z
Check the source to verify that this is the current version before use.

201. Marking misleading or unidentifiable	**Visual**	**16004**

4.3.2.17 *Box* (see dwg. 8882274).

Categories	*Defects*	*Method of inspection*	*Code No.*
Critical:	**None defined**		
Major:	**AQL 0.40 percent**		
101.	**Contents move when box is shaken**	**Manual**	**17001**
102.	**Strapping insecure**	**Manual-Visual**	**17002**
108.	**Fasteners insecure**	**Manual-Visual**	**17003**
Minor:	**AQL 0.40 percent**		
201.	**Marking misleading or unidentifiable**	**Visual**	**17004**

Testing

4.3.3.1 Nonfunctioning (see 3.4) – Critical defect – Code No. 15008. This test shall be performed 100 percent. Assemblies failing to meet the specified requirement shall be classed defective and removed from the lot. Tine test shall be performed as specified in 4.4.1 using equipment in accordance with 4.3.4.

4.3.3.2 Functioning (3.5) – Major defeet – Code No. 15009. Beginning with the first lot and continuing until three consecutive lots have complied with the acceptance criteria specified, the sampling plan for this test shall be in accordance with Standard MIL-STD-105D using code letter K and AQL of 0.10 per cent. The test shall be performed as specified in 4.4.2 using equipment in accordance with 4.3.4 Assemblies failing to meet the specified requirements shall be classed defective.

4.3.32.1 Functioning (see 3.5) Major defect – Normal production. After three consecutive lots have met the criteria of 4.3.8.2 the sampling plan for this test shall be in accordance with Standard MIL-STD-105D using code letter H and AQL of 0.26 percent.

4.393.3 Spring embrittlement (see 3.3) Major defect.

Component	Drawing	Code No.
Pressure spring	8866667	03007
Pull spring	8866868	04006
Firing pin spring	8866659	06006
Release pin ring	8866660	06004

Beginning with the first lot produced and continuing until three consecutive lots have complied with the acceptance criteria Specified, the sampling plan for this test shall be in accordance with MIL-STD-105D using code letter L and an AQL of 0.10 per cent. The test shall be performed as specified in 4.4.8 using equipment in accordance with 4.3.4. Any spring which fails to comply with the specified requirement shall be classed defective.

4.3.3.3.1 Spring Embrittlement (see 3.3) – Major defect – Normal production. After three consecutive lots have met the criteria of 4.3.3.3, the sampling plan for this test shall be in accordance with Standard MIL-STD-105D using code letter K and an AQL of 0.40 percent.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:04Z
Check the source to verify that this is the current version before use.

4.3.3.4 Plating of components (see applicable drawing). For each component determination of compliance with the applicable requirements for plating shall be in accordance with the provisions of Standard MIL-STD-171, except that sampling, thickness, environmental, and acceptance criteria as applicable shall be as modified herein. In all tests actual components shall be used (separate panels or specimens are not permitted).

	Code Numbers			
Component	Drawing	Thickness	Salt Spray	Adhesion
Prong	8866655	02007	02008	02009
Spring, pressure	8866657	03008	03009	03010
Spring, pull	8866658	04007	04008	04009
Spring, firing pin	8866659	05007	05008	05009
Ring, pin, release	8866660	06005	06006	06007
Pin, release	8866648	08018	08019	08020
Pin, firing	8866654	09019	09020	09021
Washer	8866656	10007	10008	10009
Pin, safety, firing pin	8866661	11009	11010	11011

4.3.3.4.1 Plating thickness test (drop test) – Major defect. A random sample of five units shall be selected from each lot of plated component for this test. A minimum of four readings shall be taken on each unit. If this minimum plating thickness on any single article is less than 70 percent of the specified thickness, (0.00015 inches) the lot shall be rejected. The minimum thickness measured on each article shall be recorded, and the average value computed by dividing the sum of the minimum thicknesses by five. If the average minimum thickness is less than the specified thickness the lot shall be rejected. The test shall be performed using equipment in accordance with 4.9.4.

4.3.3.4.2 Salt spray test – Major defect. A random sample of five units shall be selected from each lot of plated components for this test. Failure of one or more sample units to meet the applicable requirement shall be cause for rejection. The teat shall be performed as specified in 4.4.4 using equipment in accordance with 4.3.4.

4.3.3.4.3 Plating adhesion test – Major defect. A random sample of five units shall be selected from each lot of plated components for this test. Failure of one or more sample units to comply with the applicable requirement shall be cause for rejection. The test shall be performed using equipment in accordance with 4.3.4.

4.3.3.5 Surface treatment of components (ace applicable drawing) – Major defect. A random sample of five units shall be selected from each lot of treated components for this test. Failure of one or more sample units to meet the requirements shall be cause for rejection. For aluminum parts the corrosion resistance test in accordance with Specification MIL-A-5625A shall be performed. For zinc parts the salt spray test in accordance with Specification MIL-T-12879 shall be performed. In all tests actual components shall be used (separate panels or specimens are not permitted).

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:04Z
Check the source to verify that this is the current version before use.

Component	*Drawing*	*Code No.*
Head	**8866644**	**12035**
Case	**8866645**	**13013**
Plug	**8866646**	**07008**
Pin, trigger	**8866647**	**14026**

4.3.4 Inspection Equipment. Index of Inspection Equipment Lists Number IEL-9200011 identifies the inspection equipment required to perform the examinations and tests prescribed in this section. The contractor shall design inspection equipment in accordance with the instruction in paragraph 6.3

4.3.4.1 Government rights to documentation. Inspection equipment drawings and lists provided and revised in accordance with the requirements of the IEL may be used by DOD activities for design, procure ment, manufacture, testing, evaluation, production and receiving inspection, overhaul, shipping, storage, identification of stock, ordering and storage of replacement of parts, inspection of items at overhaul, general maintenance of equipment, construction, survey and wherever inspection equipment drawings are needed.

4.3.4.2 Supply and maintenance Supply and maintenance of the equipment listed on the IEL shall be in accordance with Specification MIL-I-45607.

4.3.4.3 Government we of contractor's inspection equipment. The contractor shall as required make available to the Government all inspection equipment necessary for determining conformance with contract requirements. Operation of the equipment and verification of its accuracy shall be supplied by the contractor, as required by the Government in performance of its examination or test.

4.4 Test methods and procedures.

4.4.1 Nonfunctioning. The firing pin safety pin and the cotter pin shall be removed from the parts assembly. The assembly shall be subjected to a pull, not to exceed three pounds, applied to a rate of one foot minimum per minute, to the release pin ring parallel to the axis of the release pin. The assembly shall then be subjected to a pressure, not to exceed eight pounds, applied at a rate of one foot, minimum, per minute, to any one prong or equally distributed to all three prongs parallel to the axis of the head assembly. Observation shall be made for functioning as evidence of noncompliance with 8.4 (see 6.4) .

4.4.2 Functioning The cotter pin and the safety pin shall be removed in that order. The sample shall be divided in half. One-half of the sample shall be subjected to a pull, not to exceed 10 pounds, applied at a rate of one foot per minute, to the release pin ring parallel to the axis of the release pin. The remaining half of the sample shall be subjected to a pressure, not to exceed 20 pounds, applied at a rate of one foot maximum, per minute, to the prongs' parallel to the axis of the assembly. Observation shall be made for functioning as evidence of compliance with 3.5. Fuzes so tested shall not be returned to the lot. Undamaged components may be used in future production.

4.4.3 Spring embrittlement. The springs and rings shall be pulled to the minimum point of permanent distortion by any method approved by the procuring activity. Springs and rings so tested shall be scrapped.

4.4.4 Salt spray resistance. The test shall be performed as specified in QQ-Z-325 for zinc plated parts and as specified in QQ-P-416 for cadmium plated parts with the exception that exposure shall consist of 24 hours white salts and 48 hours red rust. Parts so tested shall be scrapped or replated.

5. PREPARATION FOR DELIVERY

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:04Z
Check the source to verify that this is the current version before use.

5.1.1 Level C. The parts and assemblies for Fuze, Mine, Combination M10A2 shall be packaged in accordance with Specification MIL-P-10025 in such a manner that no damage will occur during shipment.

5.2 Packing.

5.2.1 Level C. The parts and assemblies for Fuze, Mine, Combination M10A2 shall be packed in accordance with Drawing 8882274 and Specification MIL-P-10025. Separately designated items shall not be packed together as a single assembly.

5.3 Data cards. Data card information shall be as specified in Specification MIL-A-2250.

5.4 Shipping. When component parts from more than one lot are shipped as a carload, each lot shall be kept separate and the division between lots clearly indicated to prevent mixing of lots in transit.

55 Marking and labeling. Marking of cartons shall be in accordance with Specificaiton MIL-P-10025.

6. NOTES

6.1 Ordering data. Procurement documents shall specify the following:

(a) Title, number and date of this specification.

6.2 Inspection code numbers. 'The five digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government.

6.3 Inspection equipment. The contractor shall design inspection equipment as required by the referenced Inspection Equipment Lists (IEL) in accordance with the instructions of 6.3.1 through 6.3.7.

6.3.1 Inspection Equipment Lists. Inspection Equipment Lists indicate the availability of inspection equipment designs by showing in the "number" column of the list of inspection equipment (00 Form 1242-3) the numbers of drawings of existing equip ment designs or codes as indicated in 6.3.2. Design action required of the contractor with respect to the different types of drawings that may be listed is described in 6.3.3 and 6.3.4 Action required by the contractor with respect to commercial inspection equipment is described in 6.3.5 The contractor will be required to prepare detailed drawings in accordance with 6.8.6 for all the equipment coded as "contractor design" in the number column. Those contractor designs must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.7.

6.3.2 Inspection Equipment List codes. The inspection equipment as defined in 6.3.3. 6.3.4, 6.3.5, and 6.3.6 will be designated in the Inspection Equipment List by the following codes:

CDOF – Contractor's design responsibility on Ordnance format ; ORDM-608-12.

CDCF — Contracotr's design responsibility on contractor format.

OD — Ordnance design.

ODMU — Ordnance design. m a n d a - tory for use.

CE — Commercial equipment.

SCD — Specification Control Drawing.

6.3.3 Ordnance designs. Ordnance designs are reflected on detailed drawings which completely depict all the information necessary for the fabrication of the item

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:04Z
Check the source to verify that this is the currentversion before use.

of inspection equipment. The contractor need provide no design when an Ordnance design is listed for an item of inspection equipment. Ordnance designs fall into two basic classifications; mandatory and nonmandatory. When an Inspection Equipment List references mandatory Ordnance designs, the contractor shall comply with, and use these designs accordingly. The contractor may, however, in connection with nonmandatory designs and with the approval of the Government, design alternate inspection equipment or use comparable commercial equipment to facilitate his operations. Such contractor prepared designs or commercial equipment selections must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.7.

6.3.4 Spec- fication control drawings. Specification control drawings depict the minimum equipment requirements in outline, descriptive, diagrammatic, or pictorial form only and specify the required performance or other characteristics. Contractors must prepare detailed drawings (see 6.3.6) of their designs in support of specification control drawings. These contractor prepared designs must be approved by the Government prior to the fabrication or procuring of the equipment. Commercial equipment meeting the requirements of specification control drawings may be approved if described in sufficient detail to permit identification and evaluation by the Government. Designs shall be submitted for approval as specified in 6.3.7.

6.3.5 Commercial equipment. Commercial equipment is inspection equipment that has universal application for a specific function. It is comprised of items commonly used by industry and government. Contractors are not required to furnish drawings of commercial inspection equipment but a list of such equipment must be approved by the Government. Lists shall be submitted for approval to the inspection element of the agency administering the contract.

6.3.6 Contractor designs. Contractor designs are designs of inspection equipment for which the Government has assigned design responsibility to the contractor. Contractor designs shall be supported by detailed drawings which depict all information necessary to completely fabricate, calibrate and operate an item of inspection equipment. This requires that the necessary views, dimensions, materials, finish, notes, operating and calibration instructions be properly depicted in accordance with approved practices to the extent that further calculation or clarification will not be required Contractor designs identified as CDCF may be developed on the format the contractor normally employs in his equipment design procedure provided such format reflects the detail and information specified above. Contractor designs identified as CDOF shall comply with the format and requirements of ORDM 608-12, and, in addition, contain the detail and information specified above.

6.3.7 Submission of contractor designs Designs shall be submitted for approval to the Commanding officer, Picatinny Arsenal, ATTN: SMUPA-ND. Design review will normally be accomplished within one month after receipt by Picatinny Arsenal. Partial submission of inspection equipment designs is permissible and encouraged. However, the Arsenal completion date for design review will be based on the date of the final submission of designs.

6.4 Functioning. The fuze assembly, less igniter assembly, shall be considered to have functioned if the firing pin is released and capable of clearing the assembly when tested.

6.5 Submission of critical defect reports. For U.S. Army Munitions Command procurements, one copy of each critical defect report will be furnished the cognizant Gov-

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:04Z
Check the source to verify that this is the current version before use.

ernment inspection agency; the Army Ammunition Procurement and Supply Agency, ATTN : SMUAP-RO; Picatinny Arsenal, ATTN : SMUPA-ND.

6.5.1 Reporting to other services. For other than U.S. Army Munitions Command procurements, critical defects reporting shall be as prescribed by the contracting officer.

Custodian:

Army—MU

Preparing activity:

Army—MU

Project No. 1345-A068

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:04Z
Check the source to verify that this is the current version before use.