MILITARY SPECIFICATION

LOADER, WEAPONS, AIR LAUNCHED, A/S32K-lD

This amendment forms a part of military specification MIL-L-85532 (AS), dated 13 April 1983, and is approved for use within the Naval Air Systems Command, Department of the Navy and is available for use by all departments and agencies of the Department of Defense.

PAGE 2

2.1.1 Specifications, federal, delete last line: "MIL-B-83769/6 Battery, Storage, Lead Acid."

PAGE 3

2.1.1 Standards, military, delete: "MIL-STD-808 Finish, Protective and Codes, For Finishing Schemes For Ground and Ground Support Equipment."

2.1.1 Specifications, military, delete: "MIL-STD-838, Lubrication of Military Equipment."

2.1.1 Drawings, Naval Air Systems Command, add: "1378AS305 Lubrication Chart."

PAGE 6

3.7.2 Delete second sentence and substitute: "It shall have six wheels, one pair on each outrigger and two on the rear steer/drive axle."

3.7.2.1 At the end of line a, add: "(Maximum). "

PAGE 7

3.7.2.l.d Change 6600 to "6700" pounds.

3.7.2.4 Delete the last two sentences of this paragraph.

3.7.2.5 Delete the third sentence. Add to last sentence: ", in accordance with drawing 1378AS305."

PAGE 8

3.7.3.2.1 Delete 3.7.3.2.1 in its entiretv and substitute:
"3.7.3.2.1 Battery. Lead Acid batteries supplied for the loaders' electrical system shall conform to S.A.E. Group 31 standards with 525 cold cranking amps (minimum) capacity."

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-23T11:02Z
Check the source to verify that this is the current version before use.

PAGE 8 (Cent'd)

3.7.3.3 In the second and third line, delete "an oil bath" and substitute: "a dry element."

3.7.3.3.1 Delete the last two sentences.

PAGE 9

3.7.3.6 In the last line, delete "144" and substitute: "142."

3.7.4.1 In the fourth line, delete "89" and substitute: "86."

3.7.4.1.1 In the second line, delete "30" and substitute: "25." In the third line, delete "89" and substitute: "86."

3.7.4.1.5 In the fourth line, delete "89" and substitute: "86."

PAGE 11

3.8.4 In the third line, delete "Class IIIC" and substitute: "Class C1, Group II."

PAGE 12

3.10.2 Delete the last sentence and substitute: "All stenciling instructions are listed on 1378AS225."

3.10.3 At the end of the first sentence, add: ", if required by the acquisition activity."

PAGE 13

3.12 Add new paragraph:
"3.12 Workmanship. The loader A/S32K-1D for air lauched weapons shall conform 'to the quality established by this specification and the documents referenced. All metal components shall be free from burrs and sharp edges. By visual inspection, the loader shall be produced in accordance with current manufacturing techniques and processes. All safety markings and features shall be verified.

PAGE 14

4.1.1 Delete existing paragraph and substitute:
"4,1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government For acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material."

Source: https://assist.dla.mil - Downloaded: 2026-10-23T11:02Z
Check the source to verify that this is the current version before use.

PAGE 16

4.8.2.1 Delete Para. 4.8.2.1 and substitute:
"4.8.2.1 Speed. Each production loader shall be timed once through an 88 foot time trap during the road test conducted in accordance with 4.8.2.5. Every 50th production loader shall be given a complete test."

4.8.2.4 Delete Para. 4.8.2.4 and substitute:
"4.8.2.4 Turning radius. Every 50th production loader shall be tested In accordance with test method No. 2 of Appendix A."

PAGE 17

4.8.2.5 Add to the end of the paragraph: "Each production loader shall be tested for at least five miles while loaded with 4500 lbs. Every 50th production loader shall be given a complete test."

4.8.2.6 Add to the end of the paragraph: "Each production loader shall be tested on a 20% Grade for three minutes with the service brakes applied and containing a load of 4500 lbs. Every 50th production loader shall be given a complete test."

4.8.2.10 In the last line, delete "144" and substitute: "142."

4.8.2.11 Delete lines 3 and 4, substitute: "25 feet per minute using the rear controls and the engine running at 2400 RPM, from 2 to 86 inches above the ground. It shall be demonstrated . . ." Add to the end of the paragraph: "Every 50th production loader shall be given a complete test."

PAGE 18

4.8.2.11.3 In the third line, delete "89" and substitute: "86." Add to the end of the paragraph: "Every 50th production loader shall be given a complete test."

4.8.3 Add to the end of the paragraph: "Every production loader shall be tested by completing one full cycle while carrying a load of 4500 lbs. (Less the fail safe test of Para. 4.2.8.2.11) after the overload test of Para. 4.8.2.11.2. Every 50th production loader shall be given a complete test."

PAGE 22

Table 1. Third item from the bottom, delete "X" for the quality conformance test portion of the overload test.

PAGE 28

3b. Delete "10"" and substitute: "13."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:02Z
Check the source to verify that this is the current version before use.

PAGE 29

3c. Delete "501" and substitute: “501. 1.”

PAGE 30

Test Method 3.K(3) Delete (3) and substitute: “(4)” and add new paragraph (3); “(3) Perform cycling as listed in Para. 4.8.3 except only 10 cycles are required instead of 250.”

PAGE 31

Test Method No. 4, Para. 2 Add the following to the end of the line: “, to be maintained throughout testing.”

PAGE 32

Test Method No. 4, Para. h (3) Renumber Para. (3) and substitute: “(4)” and add new Para. (3): “(3) perform cycling as listed in Paragraph 4.8.3, except only 10 cycles are required Instead of 250.”

PAGE 33

Test Method No. 5, Para. 2.a Delete “507” and substitute: “507.1. ”

lest Method No. 5, Para. 2.c Delete “507” and substitute: “507.1” and in the second line, delete: “MIL-STD-810.”

Preparing Activity
Navy - AS
(Project No. 1740-N159)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:02Z
Check the source to verify that this is the current version before use.