MILITARY SPECIFICATION

BATTERY, DUMMY STORAGE

1. SCOPE

1.1 This specification covers special requirements, quality assurance provisions, and the preparation for delivery criteria for one type of Battery, Dummy Storage used with the Atomic Demolition Charge Training equipment.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-P-116 - Preservation, Methods of

STANDARDS

MILITARY

AN340B4 - Nut
AN515B4-14 - Screw
AN545-4-3 - Screw
AN960B4 - Washer
MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-750 - Test Methods for Semi-Conductor Devices
MIL-STD-1168 - Lot Numbering of Ammunition
MIL-STD-1169(MU) - Packaging, Packing, and Marking for Shipments of Inert Ammunition Components
MS35223-15 - Screw

DRAWINGS

ORDNANCE CORPS

8808362 - Packing and Marking for Storage and Shipments
8850745 - Battery Cable Coder Transmitter

FSC 1195

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

8850764 - Dummy Battery Assembly Wire Transmitter
8850765 - Dummy Battery Wire Transmitter
8850767 - Bracket, Mounting, Dummy Battery
8851140 - Wire Insulated Red
8851141 - Wire Insulated Black
8851235 - Fastener
8851236 - Grommet
8851655 - Rectifier
8851871 - Terminal
8864854 - Carton, Packing, Ammunition, for Dummy Storage Battery
ET-8850764 - Equipment Tabulation

(Copies of specifications, standards, drawings, and publication required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specification listed on the applicable drawing.

3.2 Assembly. The dummy battery shall comply with all requirements specified on Drawing (dwg.) 8850764, with all requirements specified herein, and with the requirements of applicable specifications to the extent specified on the drawing and herein.

3.3 Rectifier (see dwg 8851655).

3.3.1 Forward voltage drop. The forward voltage drop shall not exceed 1.2 volts when the rectifier is supplied with 1.00 amperes (amp), minimum current in the forward direction. Forward voltage drop shall be tested in accordance with 4.4.1.1.

3.3.2 Reverse amperage. The amperage in the reverse direction shall not exceed 0.50 milliamperes when a potential of 400 volts, minimum is supplied to the rectifier. The rectifier shall be tested in accordance with 4.4.1.2.

3.4 Workmanship.

3.4.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

3.4.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.4.3 Burrs. Parts shall be free from burrs.

3.4.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

3.4.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agents.

3.4.6 Electrical. Cable assemblies and wires shall be dressed in such a manner as to prevent pinching or chafing of the wire insulation. Ends of wires shall be free from burrs, sharp edges, or points. All parts shall be free from flux, chips, dirt, grease, rust or foreign material.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First article inspection. Not applicable.

4.3 Product acceptance inspection.

4.3.1 Lot formation. A lot shall consist of parts and assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification and process changes not affecting safety, performance, storage, or interchangeability, as determined by the Government, shall not necessitate changing the lot interfix number. The criteria and procedures for the assignment of lot numbers shall be in accordance with MIL-STD-1168.

4.3.1.1 Inspection lot. An inspection lot shall be the quantity of parts, subassemblies, or assemblies from the same lot, which are submitted to inspection for Government acceptance.

4.3.2 Product inspection examination. Critical characteristics shall require 100 percent inspection of all items in the inspection lot. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristic table and inspected for all characteristics in the applicable classification. Any characteristic in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed as long . All characteristic inspections are performed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

Table I
Major Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	1121-∞	45
26-27	22	48-51	30	113-131	38		

Table II
Minor Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-9	all	14-16	12	28-33	16	77-121	20
10	9	17-18	13	34-41	17	122-273	21
11	10	19-22	14	42-54	18	274-∞	22
12-13	11	23-27	15	55-76	19		

4.3.2.1 Classification of characteristics. Critical, major, and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.3.2.1.1 Screw (see AN515B4, AN545-4-3, and MS35223-15); nut (see AN340B4); washer (see AN960B4) wire insulated red (see dwg 8851140); wire insulated black (see 8851141); fastener (see dwg 8851235); grommet (see dwg 8851236); rectifier (see dwg 8851655); terminal (see dwg 8851871) covering details of dwgs 8850745, 8850765 and 8850764.

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:
101. Objective evidence (see 6.2) for part in accordance with applicable dwg or specification.....Visual

Minor:
201. Workmanship (see 3.4).....Visual-Manual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

4.3.2.1.2 Battery cable coder transmitter (see dwg 8850745) covering a detail of dwg 8850764.

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Total length	*Measure
102.	Proper assembly of terminals	Visual
Minor:		
201.	Workmanship (see 3.4)	Visual-Manual

* Measure with suitable scale

4.3.2.1.3 Dummy battery wire transmitter (see dwg 8850765) covering a detail of dwg 8850764.

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Diode installed correctly	Visual
102.	Painting	Visual
103.	Any part missing or incorrectly installed	Visual
104.	Location of black portions	*Measure
105.	Length	*Measure
106.	Width	*Measure
107.	Depth of indented portions	*Measure
108.	Height	*Measure
109.	Material (see 3.1)	Visual
Minor:		
201.	Workmanship (see 3.4)	Visual-Manual

* Measure with suitable scale

4.3.2.1.4 Bracket, mounting, dummy battery (see dwg 8850767) covering a detail of dwg 8850764.

Categories	Characteristics	Method of inspection
Critical: None defined.		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

Major:
101. Location of large hole.....*Measure
102. Diameter of 2 small holes, max.....Gage
103. Location of 2 small holes.....*Measure
104. Length.....*Measure
105. Length of short formed section.....*Measure
106. Length of long formed section.....*Measure
107. Material (see 3.1).....Visual
108. Objective evidence (see 6.2) for protective finish in accordance with dwg 8850767.....Visual

* Measure with suitable scale

Minor:
201. Workmanship (see 3.4).....Visual-Manual

4.3.2.1.5 Dummy battery assembly wire transmitter (see dwg 8850764).

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:
101. Wires tight and properly assembled.....Visual
102. Fasteners properly assembled.....Visual
103. Location of brackets.....*Measure

* Measure with suitable scale

Minor:
201. Workmanship (see 3.4).....Visual-Manual

4.3.2.1.6 Carton, packing, ammunition, for dummy storage battery (see dwg 8864854 and section 5).

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:
101. Bottom carton sealing strips.....Visual
102. Battery tight in carton.....Visual
103. Corners blunted on carton.....Visual-Manual
104. Proper sealing of bag.....Visual
105. Objective evidence (see 6.2) for heat seal test in accordance with MIL-P-116.....Visual
106. Air exhausted from bag.....Manual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

107. No split, crack or hole in bag.....Visual
108. Marking.....Visual
109. Packaging materials (see 3.1).....Visual

Minor:
201. Workmanship (see 3.4).....Visual-Manua

4.3.2.1.7 Packing and Marking for Storage and Shipments (see dwg. 8808362 and section 5).

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:
101. Gross load weight, max.....*Measure
102. Contents tight in package.....Manual
103. Correctly packed.....Visual-Manua
104. Package material (see 3.1).....Visual

* Determine weight with a suitable scale

Minor:
201. Marking.....Visual
202. Workmanship (see 3.4).....Visual-Manua

4.3.3 Testing. All the tests in this paragraph shall be performed.

	Test	Test Classification
a.	Rectifier	Major

None of these tests are considered destructive and samples so tested may be returned to the lot.

4.3.3.1 Rectifier (see 3.3). Each rectifier shall be tested in accordance with 4.4.1. If any rectifier fails to comply with 3.3, the rectifier shall be rejected and removed from the lot.

4.3.4 Acceptance inspection equipment.

4.3.4.1 Critical and major characteristics and tests. Inspection and testing shall be performed with the acceptance inspection equipment, operating instructions, and calibration instructions specified on the Equipment Lists (EL). EL's for assemblies are listed on the Equipment Tabulation, ET-8850764. When either of the conditions listed below exist, the contractor shall design required equipment or specify suitable commercial equipment. The contractor shall obtain approval of such designs, operating instructions, and special calibration instructions as specified in 6.3 prior to use on the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

a. Any deviation from equipment or procedures specified on the EL is desired.
b. The code "CD" is listed in the "Part or Identifying Number" column on the EL.

4.3.4.2 Minor characteristics and tests. Acceptance inspection equipment for minor characteristics is not specified on EL's. The acceptance inspection equipment, operating instructions and calibration instructions used by the contractor for minor classification inspection shall be approved by the Government representative authorized by the procuring agency.

4.4 Test methods. The tolerances specified herein are absolute with no allowance for test equipment inaccuracy. The tolerances used by the manufacturer shall be equal to the absolute tolerances less the accuracy tolerances of the test equipment used.

4.4.1 Rectifier (see 3.3).

4.4.1.1 Forward voltage drop (see 3.3.1). The forward voltage drop shall be tested with approved test equipment in accordance with Table III.

Table III
Forward voltage test

Positive	Negative
black wire	red wire

4.4.1.2 Reverse amperage (see 3.3.2). The reverse leakage shall be tested in accordance with MIL-STD-750, method 4016.2 and Table IV.

Table IV
Reverse amperage test

Positive	Negative
red wire	black wire

5.0 PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.1.1 Level A. The battery shall be packaged in accordance with dwgs 8864854 and 8808362 using the specified moisture barrier.

5.1.2 Level C. The battery shall be packaged in accordance with dwgs 8864854 and 8808362 except that the moisture barrier may be omitted.

5.2 Packing.

5.2.1 Level A and C. The battery shall be packed in accordance with dwgs 8864854 and 8808362.

5.3 Marking. Marking shall be as specified in accordance with dwgs 8864854 and 8808362, as applicable.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

a. Title, number, and date of this specification.
b. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

6.2 Objective evidence. Records of contractor quality control an inspections which can be verified.

6.3 Acceptance inspection equipment. The contractor shall obtain approval of equipment designs, operating instructions, and calibration instructions from the Commanding Officer, Picatinny Arsenal, Dover, New Jersey 07801, ATTN: SMUPA-NR4.

Custodian:
Army - MU

Preparing Activity:
Army - MU

Project No. 1195-A057

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.