MIL-C-50765(MU)
1 November 1971

MILITARY SPECIFICATION
CARTRIDGE DELAY, CCU-17/B, CCU-18/B, CCU-19/B, ASSEMBLY

1. SCOPE

1.1 This specification covers Cartridge, Delay: CCU-17/B, CCU-18/B, CCU-19/B Assembly, for use in cartridge actuated devices.

2. APPLICABLE DOCUMENTS:

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS:

Military

MIL-A-2550	- Ammunition and Special Weapons, General Specification for.
MIL-E-5272	- Environmental Testing, Aeronautical and Associated Equipment, General Specification for.
MIL-C-60539	- Coating, Anodic, Conventional, for Aluminum and Aluminum Alloys.

STANDARDS:

Military

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-109	- Quality Assurance Terms and Definitions.
MIL-STD-171	- Finishing of Metal and Wood Surfaces
MIL-STD-413	- Visual Inspection Guide for Rubber O-Rings.

DRAWINGS:

C8798714	- Carton, Packing, Ammunition for Cartridge Delay
C8798715	- Box, Packing, Ammunition for Cartridge Delay
D11738733	- Cartridge Delay, CCU-17/B Assembly
D11738735	- Cartridge Delay, CCU-18/B Assembly
D11738737	- Cartridge Delay, CCU-19/B Assembly

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

FSC 1377

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:36Z
Check the source to verify that this is the currentversion before use.

2.2 Other publications.- The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated the issue in effect on date of invitation for bid or request for proposal shall apply:

ASA-B-46.1 - Surface Texture

(Application for copies should be addressed to the American National Standards Institute (ANSI) 1430 Broadway, New York, New York 10018).

3. REQUIREMENTS

3.1 General.- Materials, parts and assemblies shall conform to the applicable drawings (See 6.1 and 6.3) and referenced specifications.

3.2 Protective finish.- Protective finish shall be in accordance with MIL-C-60539 and MIL-STD-171 as referenced on applicable drawings.

3.3 Moisture content of lead azide.- The moisture content of the lead azide at the time of loading shall not exceed 0.50 percent.

3.4 Vibration.- The assembled cartridge shall withstand vibration as prescribed in MIL-E-5272, Procedure XII without evidence of any disintegration of the primer, delay charge, or relay charge, or derangement of any component.

3.5 Primer sensitivity.

3.5.1 The primer, when primed into Delay Element Housings, shall all-fire when drop tested at an energy level of 26.0 inch ounces.

3.5.2 The primer, when primed into Delay Element Housings, shall not fire when drop tested at an energy level of 4.0 inch ounces.

3.6 Shock.- The assembled cartridge shall be temperature conditioned in accordance with Table I, inserted into an acceptable test fixture and shocked 750g in either direction along the major axis. The shock load shall be applied during cartridge function and shall not fail to comply with delay times specified in Table I.

3.7 Airtightness.- The cartridge shall be sealed such that leakage shall not occur in excess of 1×10^{-4} cc/sec.

3.8 Functional.

3.8.1 The cartridge shall not fail to fire.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:36Z
Check the source to verify that this is the current version before use.

3.8.2 Ballistics.- The cartridge when tested shall comply with the requirements specified in Table I.

TABLE I
Delay Times, Seconds (See 6.2)

Temperature	CCU-17/B 1 Sec. Delay	CCU-18/B 2 Sec. Delay	CCU-19/B 4 Sec. Delay
-65° to -70°F	1.2 max	2.4 max.	4.8 max.
65° to 75°F	1.0 ± 0.10	2.0 ± 0.20	4.0 ± 0.40
200° to 205°F	0.8 min.	1.6 min.	3.2 min.

3.9 Workmanship.- Workmanship shall be in accordance with the requirements of the applicable drawings, referenced specifications and the following:

3.9.1 Metal defects.- The metal part shall be free from cracks, splits, cold shuts, inclusions, porosity or other metal defects.

3.9.2 Burr.- The part shall not have a burr which might interfere with the assembly or function of the item or which might be injurious to personnel handling the item.

3.9.3 Foreign matter.- The part or assembly shall not contain chips, dirt, grease, oil, rust, corrosion or other foreign matter.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Quality Assurance terms and definitions.- References shall be made to MIL-STD-109 to define the quality assurance terms used.

4.1.2 Inspection. - Inspection shall be in accordance with MIL-A-2550.

4.2 First Article Sample.

4.2.1 Initial production sample.- At the beginning of regular production, a sample shall be submitted in accordance with contract requirements and shall consist of 54 assembled cartridges, 10 sets of unassembled components (including explosive components) for visual and dimensional examination and tests, and 100 primed delay housings for primer sensitivity test.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:36Z
Check the source to verify that this is the current version before use.

4.2.1 Continued

The sample shall be manufactured using the same materials, equipment, process and procedures as used in regular production. All parts and materials, including packaging and packing shall be the same as used for regular production and shall be obtained from the same source of supply.

4.2.1.1 Examination and tests.- After examination and provisional acceptance at source, the sample shall be inspected for all requirements of the drawings and specifications at a Government laboratory or such other facility specified in the contract.

4.2.1.2 Ballistics.- The sample for ballistics tests shall be temperature conditioned and tested to determine compliance with 3.8. The sample for testing shall consist of the following:

TABLE III

Temperature	Vibrated	Shock	Not Vibrated
-65° to -70°F	4	4	10
65° to 75°F	4	4	10
200° to 205°F	4	4	10

4.2.1.3 Initial production sample failure.- Failure of the sample to comply with the requirements of the drawings and specifications shall result in sample disapproval.

4.3 Inspection provisions.

4.3.1 Lot.

4.3.1.1 Submission of product.- The product shall be submitted in accordance with MIL-STD-105.

4.3.1.2 Size of Lots.- A lot shall consist of an identifiable group of assembled units and shall include:

a. Components produced by a homogeneous process.
b. Primers from not more than one lot.
c. Delay assemblies from not more than one lot.
d. Relay assembly from not more than one lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

4.3.2 Examination.- One hundred percent examination shall be performed for all critical defects. Examination for major and minor defects shall be performed on a defect basis in accordance with the classification of defects contained herein, using sampling plan and associated criteria in Tables IV and V. For an individual defect (single characteristic) the criteria in Table IV shall be used. For total defects within a major or minor class, the criteria in Table V, shall be used. All non-conforming material shall be rejected. Inspection for Rubber O-rings shall be in accordance with MIL-STD-413. The roughness comparison specimen prescribed in ASA-B-36.1 shall be used as a basis of comparison for surface roughness determination. Four power magnification may be used in performing visual examination for such defects as burr and foreign matter.

TABLE IV

		Major		Minor	
Lot Size	Sample Size	Accept	Reject	Accept	Reject
1-300	100% Examination				
301 - 1300	110	1	2	2	3
1301 - 3200	150	2	3	3	4
3201 - 8000	225	3	4	4	5
8001 - 22000	300	4	5	5	6

TABLE V

Total Allowable Defects per Sample Size

Sample Size for Major Defects	110	150	225	300
Number of Defects in Class				
2-3	1	2	3	4
4-7	2	3	4	5
8-19	3	4	5	7
20-43	4	5	8	10
over 43	6	8	11	14
Sample Size for Minor Defects	**110**	**150**	**225**	**300**
2-3	2	3	4	5
4-7	3	4	5	7
8-16	4	5	8	10
17-48	6	8	11	14
over 48	8	11	17	20

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

4.3.2.1 Ring, Seal Drawing B11738770 covering a detail of the applicable Cartridge Delay Assembly.

Categories	Defect	Method of Inspection
CRITICAL		
	None defined.	
MAJOR		
101.	Inside Diameter	Gage
102.	Cross-section diameter	Gage
MINOR		
201.	Length of protrusion, max.	Gage
202.	Width of protrusion, max.	Gage

4.3.2.2 Cup Relay, Drawing B11738771 covering a detail of the applicable Cartridge Delay Assembly.

Categories	Defect	Method of Inspection
CRITICAL		
	None defined.	
MAJOR		
101.	Inside diameter	Gage
102.	Outside diameter	Gage
103.	Thickness through bottom, min.	Gage
104.	Metal Defective	Visual
MINOR		
201.	Total length	Gage
202.	Thickness through bottom, max.	Gage
203.	Protective finish inadequate or defective	Visual

4.3.2.3 Body Delay, Drawing C11738773 covering a detail of the applicable Cartridge Delay Assembly.

Categories	Defect	Method of Inspection
CRITICAL		
	None defined.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

4.3.2.3 Continued

Categories	Defects	Methods of Inspection
MAJOR		
101.	Pitch diameter of thread, min.	Gage
102.	Major diameter of thread, min.	Gage
103.	True position of pitch diameter of thread with small outside diameter	Gage
104.	True position of large outside diameter with small outside diameter	Gage
105.	Total length	Gage
106.	Depth of cavity	Gage
107.	Large outside diameter	Gage
108.	Diameter of cavity	Gage
109.	Metal defective	Visual
110.	Burr	Visual
111.	Foreign matter	Visual
112.	Protective finish inadequate or improper	Visual
MINOR		
201.	Small outside diameter	Gage
202.	Diameter of hole	Gage
203.	Width of slots	Gage
204.	Length of thread	Gage
205.	Length to small outside diameter	Gage
206.	Angles incorrect	Gage
207.	Length of slots	Gage
208.	Thread damage	Visual
209.	Surface finish improper	Visual

4.3.2.4 Housing, Delay Element, Drawing D11738774, covering a detail of the applicable Cartridge Delay Assembly.

CRITICAL		
	None defined.	
MAJOR		
101.	Pitch diameter of small external thread, min.	Gage
102.	Major diameter of small external thread, min.	Gage
103.	Pitch diameter of internal thread, max.	Gage
104.	Minor diameter of internal thread, max.	Gage
105.	Pitch diameter or large external thread, min.	Gage
106.	Major diameter of large external thread, min.	Gage
107.	True position of large cavity with pitch diameter of internal thread.	Gage

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:36Z
Check the source to verify that this is the current version before use.

4.3.2.4 Continued

Categories	Defect	Method of Inspection
108.	True position of pitch diameter of small external thread with cavity at small end.	Gage
109.	Run out of cavity at small end with large cavity below internal thread	Gage
110.	Depth of cavity at small end	Gage
111.	Diameter of large cavity below internal thread	Gage
112.	Length to flange from small end	Gage
113.	Length to flange from large end	Gage
114.	Diameter between (hexagon) flange and large external thread, min.	Gage
115.	Total length	Gage
116.	Diameter of cavity at small end	Gage
117.	Diameter of thru hole	Gage
118.	Length of internal thread	Gage
119.	Depth of small cavity below internal thread	Gage
120.	Depth of large cavity below internal thread	Gage
121.	Depth of internal thread cavity	Gage
122.	Angle in counterbore at small end	Gage
123.	Angle at mouth of cavity at small end	Gage
124.	Runout of counterbore with cavity at small end	Gage
125.	Thread damage	Visual
126.	Protective finish inadequate or defective	Visual
127.	Burr	Visual
128.	Foreign matter	Visual
129.	Metal defective	Visual
MINOR		
201.	Pitch diameter of large external thread max.	Gage
202.	Pitch diameter of small external thread, max.	Gage
203.	Pitch diameter of internal thread, min.	
204.	Diameter of small cavity below internal thread	Gage
205.	Length of large external thread	Gage
206.	Width across flange	Gage
207.	Length from small external thread to flange, max.	Gage
208.	Outside diameter of counterbore at small end	Gage
209.	Inside diameter of counterbore at small end	Gage
210.	Depth of counterbore at small end	Gage
211.	Surface finish improper	Visual

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:36Z
Check the source to verify that this is the current version before use.

4.3.2.5 Relay Assembly, Drawing B11738772, covering a detail of the applicable Cartridge, Delay Assembly Drawing.

Categories	Defects	Method of Inspection
CRITICAL		
1.	Charge missing	Visual
MAJOR		
101.	Metal defective	Visual
102.	Protective finish inadequate or defective	Visual
103.	Foreign matter	Visual
MINOR		
201.	Outside diameter	Gage
202.	Charge height	Gage

4.3.2.6 Body, Delay Assembly, Drawing D11738734, D11738736 or D11738738, covering a detail of the applicable Cartridge, Delay Assembly Drawing.

CRITICAL		
1.	Improper assembly	Visual
2.	Flash hole missing or obstructed	Visual
3.	Metal defective	Visual
4.	Protective finish inadequate or defective	Visual
5.	Delay charge missing.	Visual
6.	Marking missing, incorrect, or illegible	Visual
MAJOR		
101.	Foreign matter	Visual
MINOR		

None defined.

4.3.2.7 Cartridge Delay Assembly, Drawing D11738733, D11738735, or D11738737

CRITICAL		
1.	Any part missing	X Ray 1/ Visual
2.	Improper assembly	X Ray 1/ Visual
3.	Metal Defective	Visual
4.	Marking missing, incorrect or illegible	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

4.3.2.7 (Cont'd)

Categories	Defect	Method of Inspection
101.	Foreign matter	Visual
102.	Total length (max)	Gage
103.	Thread damaged	Visual
104.	Primer crimp less than 360°	Visual

MINOR

None defined

1/ The cartridge shall be X-rayed with the sides of the housing perpendicular to the rays. The X-ray negatives, properly identified, shall be forwarded to the procuring activity.

4.3.2.8 Carton, Sealed, Drawing C8798714.

CRITICAL

None defined.

MAJOR

None defined.

MINOR

201.	Contents loose	Manual/Visual
202.	Quantity of contents incorrect	Visual
203.	Separators or filler missing	Visual
204.	Carton sealing defective, improper or missing	Visual
205.	Cut or damaged through impregnated carton	Visual
206.	Marking missing, incorrect or illegible	Visual

4.3.2.9 Box, sealed wooden packing, Drawing C8798715

CRITICAL

None defined.

MAJOR

None defined.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

4.3.2.9 (Cont'd)

Categories	Defect	Method of Inspection
MINOR		
201.	Contents loose	Manual/Visual
202.	Hardware missing, loose, broken or improperly engaged	Visual
203.	Strapping missing, loose, broken or improperly assembled	Visual
204.	Contents of box exposed	Visual
205.	Box damaged	Visual
206.	Marking missing, incorrect or illegible	Visual
207.	Car seal missing, unsealed	Visual

4.3.3 Inspection Testing.-The following tests shall be performed in accordance with the provisions of 4.4.

4.3.3.1 Protective finish.-The number of specimens and acceptance criteria for protective finish tests shall be in accordance with MIL-STD-105. and the applicable military standard referenced on the drawing.

4.3.3.2 Moisture content of lead azide.-The moisture content of the lead azide shall be determined at the time of loading at least once for each eight hours of production or portion thereof. The moisture content of the sample shall be determined as specified in 4.4.2. If the moisture content exceeds the requirements specified in 3.3, the lead azide shall be rejected. Any components containing lead azide that is found to have excessive moisture shall be rejected.

4.3.3.3 Vibration.-Twelve of the assembled cartridges of the initial production lot shall be subjected to vibration in accordance with 4.4.3. After vibration test, the 12 cartridges shall be x-rayed as directed in Note 1/ 4.3.2.7. Evidence of any disintegration of the primer, lead azide, delay charge or derangement of any component shall be cause for rejection of the lot as indicated in 3.4. When a change occurs in the lot of primers, lead azide, or delay charge after the initiation of production, 12 assembled cartridges from any subsequent production lot shall be tested in accordance with this paragraph.

4.3.3.4 Shock.-Twelve of the cartridges of the initial production sample shall be subjected to this test. Failure of any cartridge to comply with the requirement of 3.6 shall be cause for rejection of the lot of cartridges.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

4.3.3.5 Airtightness.-Each cartridge shall be subjected to the specific pressure differential. Failure of any cartridge to comply with the requirements shall be cause for rejection of that cartridge.

4.3.3.6. Primer sensitivity.-A sample of 100 primed delay housings from each production lot shall be tested for sensitivity.

4.3.3.6.1 All fire.-50 delay housings, less delay assemblies shall be tested at the 26-inch ounce energy level in accordance with 3.5.1. Any cartridge failing to comply with the 3.5.1 shall be cause for rejection of the lot.

4.3.3.6.2 No fire.-50 delay housings, less delay assemblies shall be tested at the 4.0 inch-ounce level in accordance with 3.5.2. Any cartridge failing to comply with 3.5.2 shall be cause for rejection of the lot.

4.3.3.7 Functional.

4.3.3.7.1 Ballistics.-30 assemblied cartridges from the initial production lot and 30 assembled cartridges from each subsequent production lot shall be grouped and temperature conditioned in accordance with 4.4.7.1.1 and Table VI. Failure of any cartridge to comply with the requirements of 3.8 shall be cause for rejection of lot.

TABLE VI

Temperature	Sample Size
-65° to -70° F	10
65° to 75° F	10
200° to 205° F	10

4.3.4 Inspection equipment.-The examination and tests shall be made using equipment approved by the Government.

4.4 Test methods and procedures.

4.4.1 Protective finish.-Test procedure for protective finish shall be in accordance with the applicable specifications listed on the drawings. The delay housings and delay body shall be sectioned longitudinally to expose the critical surface to the salt spray.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:36Z
Check the source to verify that this is the current version before use.

4.4.2 Moisture content of lead azide.-A tared, dried, aluminum dish, 2 inches in diameter, shall be covered with a sheet of polytetrofluorethylene, 2 ½ inches square, and sufficiently flat to form a tight cover, and placed in a sulfuric acid disiccator. An accurately weighed portion of approximately two grams of the sample shall be transferred to a moisture dish and the contents and the dish shall be transferred to an oven and dried at 95° Centigrade (C), plus or minus 2°C for 2 hours. After drying, the dish shall be quickly transferred to the sulfuric acid desiccator and allowed to cool to room temperature. The polytetrofluroethylene cover shall be placed on the dish and the assembly weighed. The loss in weight shall be calculated to percentage of moisture content in the lead azide to determine compliance with 3.3 as follows:

$$\text{Percentage of moisture} = \frac{(A-B)}{A} \times 100$$

where:
A = the weight of the sample before drying

B = the weight of the sample after drying

4.4.3 Vibration.-The method and procedure for performing the vibration test shall be in accordance with MIL-E-5272, Procedure XII.

4.4.4 Shock.-The 12 assembled cartridges shall be mounted in an approved fixture and fired. Two cartridges shall be fired in each direction at the 3 temperatures specified in Table I. At the time of the firing of each cartridge, the cartridge shall be shocked at 750g in accordance with 3.6. This shock test shall be performed on the initial production sample only, and need not be repeated on subsequent production lots, except where a new initial production sample is required.

4.4.5 Airtightness.-The method and procedure for determining airtightness shall be by use of equipment approved by the Government.

4.4.6 Primer sensitivity.-Drop test 100 primed delay housings from the initial production sample and 100 delay housings from each production lot at 13 inches, using a steel ball 15/16 inches in diameter, and weighing 1.94 ounces, plus/minus 0.02 ounces, in a primer sensitivity machine with a cartridge holder approved by the procuring activity.

4.4.7 Functional.

4.4.7.1 Ballistics.-Cartridges of the sample shall be grouped and temperature conditioned in accordance with 4.4.7.1.1 and rigidly supported in the test fixture for ballistic test. The sample shall be tested within 5 minutes after removal from the conditioning chamber. When this time limit is exceeded, the sample shall be reconditioned in accordance with 4.4.7.1.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

4.4.7.1.1 Temperature conditioning.-A standard inert cartridge containing a temperature sensitive element shall be placed in the conditioning chamber at the same time as the sample. The conditioning time shall be a minimum of one hour longer than the time necessary to bring the element contained in the inert cartridge to the required temperature.

5. PREPARATION FOR DELIVERY

5.1 Packing and Marking.-Level A - Packing and marking shall be in accordance with dwgs. C8798714 and C8798715 as applicable.

6. NOTES

6.1 Ordering Data.-Procurement documents should specify the following:

a. Title, number, and date of this specification

b. Delay time and the applicable Cartridge Delay Assembly Drawing Number (See 2.1 and 6.3)

6.2 Delay time.-Delay time is defined as the time that elapses between the impact of the firing pin on the primer and the flash of the relay assembly.

6.3 Cartridge Delay Assemblies.-covered by this specification are identified as follows:

a. Cartridge Delay, CCU-17/B Assembly - 1 Second Delay, Drawing D11738733

b. Cartridge Delay, CCU-18/B Assembly - 2 Second Delay, Drawing D11738735

c. Cartridge Delay, CCU-19/B Assembly - 4 Second Delay, Drawing D11738737

6.4 Storage and Shipping Information

Explosive Hazard Classification - Class I
Storage Compatibility - Group B, E, or N
Department of Transportation (DOT) Hazard - Class C
DOT Marking - "Explosive Power Device - Class C - Handle Carefully, Keep Fire Away".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

6.5 Hazard notice.-The cartridges described herein and certain of their components are flammable and/or explosive and consequently present hazards in manufacture handling, storage, and shipment. The contractor should recognize these hazards and take appropriate measures to guard and protect against fire, explosion, adverse environment, corrosive atmosphere, rough handling and electrically induced incidents.

Custodian:

Army - MU

Preparing Activity:

Army - MU (FA)

Project No. 1377-A488

☆ U. S. GOVERNMENT PRINTING OFFICE: 1971-714-160/13030

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
Department of the Army

OFFICIAL BUSINESS

Commanding Officer
Frankford Arsenal
ATTN: SMUFA-T1000
Philadelphia, Pa. 19137

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:36Z
Check the source to verify that this is the current version before use.