INCH-POUND

MIL-F-48382A (AR)
AMENDMENT 1
27 January 1989

MILITARY SPECIFICATION

FUZE, M934E6, IMPACT SWITCH FOR

This Amendment forms part of Military Specification MIL-F-48382A (AR), dated 1 July 1985, and is approved for use within the U.S. Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 4

Add new paragraph 3.2.11 as follows:

"3.2.11 Solderability. The solderability shall meet the requirements of MIL-STD-202, Method 208."

Delete page 7 in its entirety.

Add new page 7A.

Add new page 7B.

Delete page 17 in its entirety.

Add new page 17.

Delete page 18 in its entirety.

Add new page 18.

PAGE 20

4.5.5 Particle impact noise detection (PIND).

Delete "along S-T axis" and substitute "perpendicular to the M-N axis"

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:24Z
Check the source to verify that this is the current version before use.

4.5.10 Shock-operating.

Delete "free-fall".

Delete "Parallel to the M-N axis in an N to M direction" and substitute "Parallel to the M-N axis in a direction to move the switch weight towards contact."

Add new paragraph 4.5.11 as follows:

"4.5.11 Solderability. Solderability shall be performed as specified in MIL-STD-202, Method 208, with the exception that the aging requirement shall be one hour."

6.4 Submission of designs for approval.

Delete "Dover, NJ 07801-5000." and substitute "Picatinny Arsenal, NJ 07806-5000.".

Custodian:
Army-AR:

Preparing Activity:
Army-AR:
(Project 1336-A568)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:24Z
Check the source to verify that this is the current version before use.

TABLE 1 FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
	SWITCH ASSEMBLY, IMPACT, AND COMPONENTS	1 OF 2	9297012
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	SWITCH ASSEMBLY, IMPACT Group A 1/	6			
	Soft Solder at Screw End Missing or Improper			3.4	Visual
	Adhesive at Terminal Stud Missing or Improper			3.4	Visual
	Insulation Dimension			3.3	Gage
	Insulation of Contact			3.4	Visual
	Soldering in Accordance with MIL-S-45743			3.4	Visual
	Marking			3.4	Visual
	Workmanship			3.7	Visual
	Steady State Acceleration Sensitivity			3.2.1	4.5.1/Gage
	Velocity Change Sensitivity			3.2.2	4.5.2/Gage
	Resistance			3.2.3	4.5.3/Gage
	Insulation Resistance			3.2.4	4.5.4/Gage
	Particle Detection			3.2.5	4.5.5/Gage
	Solderability			3.2.11	4.5.11

NOTES:

1/ Destructive Test

2/ 1/2 Hot 1/2 Cold. The units subjected to hot temperature shall be subjected to hot operating temperature. The units subjected to cold temperature shall be subjected to cold operating temperature.

3/ Inititate test within 5 minutes of removal from temperature chamber, with temperatures per note 2 (above).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:24Z
Check the source to verify that this is the current version before use.

TABLE 1 FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET OF	DRAWING NUMBER
	SWITCH ASSEMBLY, IMPACT, AND COMPONENTS		2 2	9297012
				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH / PARAGRAPH REFERENCE /INSPECTION METHOD
	Group B 1/			
	Environmental Sequence	12		
	Soft Solder at Screw End Missing or Improper			3.4 Visual
	Adhesive at Terminal Stud Missing or Improper			3.4 Visual
	Insulation Dimension			3.3 Gage
	Insulation of Contact			3.4 Visual
	Soldering in Accordance with MIL-S-45743			3.4 Visual
	Marking			3.4 Visual
	Workmanship			3.7 Visual
	Temperature 2/			3.2.8 4.5.8
	Transportation Vibration 2/			3.2.6 4.5.6
	Vibration-Acceleration Operating 2/			3.2.9 4.5.9
	Handling Shock 3/			3.2.7 4.5.7
	Shock, Operating 3/			3.2.10 4.5.10
	Steady State Acceleration Sensitivity			3.2.1 4.5.1/Gage
	Velocity Change Sensitivity			3.2.2 4.5.2/Gage
	Resistance 3/			3.2.3 4.5.3/Gage
	Insulation Resistance			3.2.4 4.5.4/Gage
	Particle Detection			3.2.5 4.5.5/Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:24Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET OF	DRAWING NUMBER
4.4.2.8	SWITCH ASSEMBLY, IMPACT	1 2	9297012
			NEXT HIGHER ASSEMBLY 9297045

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	SWITCH ASSEMBLY, IMPACT Group A				
Major					
101	Softer Solder at Screw End Missing or Improper		0.25%	3.4	Visual
102	Adhesive at Terminal Stud Missing or Improper		0.25%	3.4	Visual
103	Insulation Dimension		0.25%	3.3	Gage
104	Insulation of Contact		0.25%	3.4	Visual
105	Solder in Accordance with MIL-S-45743		0.25%	3.4	Visual
106	Steady State Acceleration Sensitivity		100%	3.2.1	4.5.1
107	Velocity Change Sensitivity		100%	3.2.2	4.5.2/Gage
108	Resistance		100%	3.2.3	4.5.2/Gage
109	Insulation Resistance		100%	3.2.4	4.5.4/Gage
110	Particle Detection		100%	3.2.5	4.5.5/Gage
Minor					
201	Marking		0.40%	3.4	Visual
202	Workmanship		0.40%	3.7	Visual

NOTES:

1/Destructive Test.
2/1/2 Hot 1/2 Cold. The units subjected to hot temperature shall be subjected to hot operating temperature. The units subjected to cold temperature shall be subjected to cold operating temperature.
3/Initiate test within 5 minutes of removal from temperature chamber, with temperatures per note 2 (above).
4/Test sample 5% of the lot but not less than 5 units, with no defects permitted.

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T19:24Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.8	SWITCH ASSEMBLY, IMPACT	2	2	9297012
				NEXT HIGHER ASSEMBLY: 9297045

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Group B 1/ Environmental Sequence	4/			
Major					
111	Temperature 2/			3.2.8	4.5.8
112	Transportation Vibration 2/			3.2.6	4.5.6
113	Vibration-Acceleration Operating 2/			3.2.9	4.5.9
114	Handling Shock 3/			3.2.7	4.5.7
115	Shock, Operating 3/			3.2.10	4.5.10
116	Steady State Acceleration Sensitivity 3/			3.2.1	4.5.1/Gage
117	Velocity Change Sensitivity 3/			3.2.2	4.5.2/Gage
118	Resistance 3/			3.2.3	4.5.3/Gage
119	Insulation Resistance			3.2.4	4.5.4/Gage
120	Particle Detection			3.2.5	4.5.5/Gage
Minor					
203	Marking			3.4	Visual
204	Workmanship			3.7	Visual
205	Solderability			3.2.11	4.5.11

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:24Z
Check the source to verify that this is the current version before use.