MIL-F-52651A(ME)
2 April 1975
SUPERSEDING
MIL-F-52651(ME)
23 June 1969

MILITARY SPECIFICATION

FIRE FIGHTING EQUIPMENT SET: TRUCK MOUNTED; STRUCTURAL, CLASS 530-SERIES, PACKAGING OF

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers requirements for preservation, packaging, packing, and marking of a Fire Fighting Equipment Set: Truck Mounted; Structural, Class 530-Series (SC 4210-97-CL-E05).

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

Federal

U-A-500	- Ammonia, Aromatic (Inhalants).
QQ-S-781	- Strapping, Steel, and Seals.
PPP-B-566	- Boxes, Folding, Paperboard.
PPP-B-601	- Boxes, Wood, Cleated-Plywood.
PPP-B-636	- Boxes, Shipping, Fiberboard.
PPP-C-650	- Crates, Wood, Open and Covered.
PPP-P-40	- Packaging and Packing of Hand Tools.
PPP-T-60	- Tape: Packaging, Waterproof.

FSC 4210

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:28Z
Check the source to verify that this is the current version before use.

Military

MIL-P-116	- Preservation-Packaging, Methods of.
MIL-P-775	- Packaging of Hose, Hose Assemblies; Rubber, Plastic, Fabric, or Metal (Including Tubing); and Fittings, Nozzles, and Strainers.
MIL-C-52155	- Charges, Fire Extinguisher, Antifreeze, Calcium-Lithium Chloride Base and Lithium Chloride Base.

STANDARDS

Military

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-281	- Automobiles, Trucks, Truck Tractors, Trailers and Trailer Dollies; Preservation and Packaging of.

(Copies of specifications and standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, ATTN: Tariff Publishing Officer, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Associations, Inc., ATTN: Tariff Order Section, 1616 P Street, NW, Washington, DC 20036.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:28Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Materials. Materials shall be as specified herein and in applicable specifications and standards. Materials not specified shall be selected by the supplier and shall be subject to all provisions of this specification. Materials shall be free of defects.

3.2 Preproduction pack. The supplier shall furnish a preproduction pack for examination within the time frame specified (see 6.2) to prove prior to starting production packaging and packing, that the applied preservation, packaging, packing, and marking comply with the requirements of this specification. Examination shall be as specified in Section 4 and shall be subject to surveillance and approval by the Government (see 6.3).

3.3 Preservation and packaging. Preservation and packaging shall be Level A, B, or C, as specified (see 6.2).

3.3.1 Level A.

3.3.1.1 Preservative. Preservative specified herein shall conform to the applicable specification listed in and shall be applied in accordance with MIL-P-116.

3.3.1.2 Methods. Methods of preservation, indicated by symbols herein, shall conform to the corresponding symbols in MIL-P-116.

3.3.1.3 Unprotected surfaces. Unpainted exterior metal surfaces of components requiring the application of a contact preservative in accordance with MIL-P-116 shall be coated with Type P-1 preservative.

3.3.1.4 Axes, wrecking bar, boltcutter, mattocks, hand shovels, handles and spanner wrenches. Each item shall be preserved and packaged in accordance with PPP-P-40, Level A.

3.3.1.5 Hoses, couplings, nipples, nozzles, reducers, strainers, playpipes, nozzle tips, and siamese connection valves. Each item shall be preserved and packaged in accordance with MIL-P-775, Level A.

3.3.1.6 Batteries. The batteries shall be preserved together, Method IA-14. The inner container shall be a substantial commercial container or the supplier's carton, or box conforming to PPP-B-566, variety plain, type and style optional. The outer container shall conform to PPP-B-636, W6c.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:28Z
Check the source to verify that this is the current version before use.

3.3.1.7 Fire extinguishers. Each extinguisher shall be packaged in a close-fitting box conforming to PPP-B-636, W5c. The contents shall be cushioned and secured to prevent damage by free movement within the box. The boxes shall be waterproof sealed in accordance with Method V of the appendix to the box specification.

3.3.1.8 Gaskets. Gaskets of like description shall be preserved together Method IC-2. The container shall be the supplier's commercial carton or a close-fitting box conforming to PPP-B-566, variety plain, type and style optional.

3.3.1.9 Pails. Pails shall be nested together and packaged in a close-fitting box conforming to PPP-B-636, W5c. The box shall be waterproof sealed with tape as specified in 3.3.1.7.

3.3.1.10 Scissors. Each scissor shall be preserved Method IA-8. One scissor shall be placed in each first aid kit.

3.3.1.11 Ammonia inhalant solution. The ammonia inhalant solution shall be unit packaged in accordance with U-A-500, Level A. One unit package shall be placed in each first aid kit.

3.3.1.12 First aid kit. Each first aid kit case, with its components, scissors and ammonia inhalant solution placed therein, shall be packaged in a close-fitting box conforming to PPP-B-636, W5c. The boxes shall be waterproof sealed as specified in 3.3.1.7.

3.3.1.13 Lanterns. Each lantern contained in a vendor's carton or in a box conforming to PPP-B-566, variety plain, type and style optional, shall be preserved Method IC-2.

3.3.1.14 Paulins. Each paulin shall be neatly and compactly folded and packaged in close-fitting boxes conforming to PPP-B-636, W5c. The boxes shall be waterproof sealed as specified in 3.3.1.7.

3.3.1.15 Straps. Each strap shall be preserved Method IC-1.

3.3.1.16 Rope. The rope shall be coiled, the coil secured with cotton tape or twine, and the coil packaged in a close-fitting box conforming to PPP-B-636, W5c. The box shall be waterproof sealed as specified in 3.3.1.7.

3.3.1.17 Pike pole. The pointed end and the hook of the pole shall be protected with pieces of hardboard or 1/4-inch plywood, secured in place with tape conforming to PPP-T-60, Type IV, Class 1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:28Z
Check the source to verify that this is the current version before use.

3.3.1.18 Fire extinguisher charges. Each charge shall be packaged in accordance with MIL-C-52155, Level A.

3.3.1.19 Foam liquid. The foam liquid in 5-gallon pails shall not require packaging.

3.3.1.20 Ladders. Ladders shall not require preservation and packaging.

3.3.1.21 Truck chassis. The truck chassis, when furnished (MAP only), shall be preserved and packaged in accordance with MIL-STD-281, Level A (mobile).

3.3.1.22 Consolidated packaging. The preserved and packaged components (except the ladders) of the set shall be consolidated packaged together in close-fitting boxes conforming to PPP-B-601, Overseas Type, Grade B. When a truck chassis is furnished, the size and configuration of the boxes shall be determined by the available space for placing and securing the boxes on the fire truck. When the boxes are to be secured to the truck, strapping shall not be required. When a truck is not furnished, the components of the set (except the ladders), preserved and packaged as specified herein, shall be consolidated packaged in boxes specified herein. The boxes shall be strapped in accordance with the appendix to the box specification.

3.3.2 Level B. Components of the set shall be preserved and packaged as specified for Level A with the following exceptions: Boxes, used for consolidated packaging, conforming to PPP-B-601, shall be Domestic Type. The truck chassis, when furnished, shall be preserved and packaged in accordance with MIL-STD-281, Level B (mobile).

3.3.3 Level C. The components of the set shall be preserved and packaged to afford protection against deterioration and damage from the supplier to the initial destination. Consolidated packaging shall not be required. The supplier's commercial practice is acceptable provided it fulfills these requirements. The truck chassis, when furnished, shall be preserved and packaged in accordance with MIL-STD-281, Level C (mobile).

3.4 Packing. Packing shall be Level A, B, or C, as specified.

3.4.1 Level A. When a truck is furnished, the ladders shall be placed in the racks provided on the truck and shall be secured in place. The other components of the set, preserved, packaged, and consolidated packaged as specified in 3.3, shall be positioned and secured to the truck in any available space that will not increase cubage, cause damage to the truck or components, or in any way interfere with lifting, steering, or towing of

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:28Z
Check the source to verify that this is the current version before use.

the truck. Securing of the consolidated packages to the truck shall be with strapping conforming to QQ-S-781, Class 1, Type I, Finish B, Size 3/4 inch; or by bolting, when practical. The truck with the ladders and consolidated containers attached shall be shipped unboxed (mobile). When a truck is not furnished, the set components, except the ladders, preserved and packaged as specified in 3.3, shall be packed in a crate conforming to PPP-C-650, Type V, Style A, Class 1. The ladders shall be packed together in a crate conforming to PPP-C-650, Type II, Style A. Blocking, bracing, and anchoring of contents, and closure and strapping of the crates, shall be in accordance with the appendix to the crate specification.

3.4.2 Level B. Packing shall be as specified for Level A, except Type V crates shall be Style B, open and Type II crates shall be Style B.

3.4.3 Level C. The components of the set, except the ladders preserved and packaged as specified in 3.3, shall be packed in containers that will assure carrier acceptance and safe delivery from the supplier to the initial destination at the lowest ratings of the carrier. Containers as a minimum shall comply with Uniform Freight Classification rules or with National Motor Freight Classification rules. Ladders shall be secured in the retracted position and shall not require packing. When a truck is furnished, the ladders shall be secured in the racks provided on the truck. The containers containing the other components of the set shall be secured in any available space on the truck in a manner not to increase cubage or interfere when the truck is lifted with slings, or interfere with steering or towing the truck. The truck shall be shipped unboxed (mobile). Any containers that cannot be secured to the truck shall be shipped separately from, but at the same time as the truck.

3.5 Marking. In addition to any special marking required by the contract or purchase order as specified (see 6.2), packages, shipping containers, and unboxed (mobile) trucks shall be marked in accordance with MIL-STD-129.

3.6 Workmanship. Workmanship shall provide maximum protection to the set components, by application of the requirements specified herein, to prevent corrosion, deterioration, and mechanical or physical damage to the components during handling, shipment, and storage.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:28Z
Check the source to verify that this is the current version before use.

other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Material inspection. The supplier is responsible for insuring that supplies and materials used are manufactured, examined, and tested in accordance with referenced specifications and standards.

4.2 Classification of inspections. Inspections shall be classified as follows:

(a) Preproduction pack inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).

4.3 Preproduction pack inspection.

4.3.1 Examination. The preproduction pack shall be examined for the defects listed in 4.5.1. Presence of one or more defects shall be cause for rejection of the preproduction pack.

4.4 Quality conformance inspection.

4.4.1 Inspection stages. Inspection shall be in three stages as follows:

(a) The first stage shall include inspection of procedures, methods, materials, containers, and packaging marking, prior to placing the packages into consolidated containers.
(b) The second stage shall include inspection of closure and marking of consolidated containers, and the arrangement, blocking, and bracing of consolidated containers in the shipping container.
(c) The third stage shall include inspection of the closed, strapped, and marked shipping containers prepared for shipment, and the securing of the consolidated containers to the truck when a truck is furnished.

4.4.2 Unit of product. For the purpose of inspection, a completed pack of any one level prepared for shipment, shall be considered a unit of product.

4.4.3 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.4.4 Examination. Samples selected in accordance with 4.4.3 shall be examined for the defects marked "X" for the applicable level in 4.5.1. Acceptable Quality Level (AQL) shall 2.5 percent defective.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:28Z
Check the source to verify that this is the current version before use.

4.5 Inspection procedure.

4.5.1 Examination. Packs shall be examined for the following defects:

Table I. Classification of Defects.

No.	Defect	Level A	Level B	Level C
101.	Materials, methods, and containers not as specified. Each incorrect material, method, and container shall constitute one defect (3.1, 3.3, 3.4).	X	X	X
102.	Unpainted exterior surfaces of components not coated with preservative as specified (3.3.1.3, 3.3.2).	X	X	-
103.	Tools not preserved and packaged in accordance with the reference document as specified (3.3.1.4, 3.3.2).	X	X	-
104.	Hose and fittings not preserved and packaged in accordance with the referenced document as specified (3.3.1.5, 3.3.2).	X	X	-
105.	Fire extinguishers not packaged as specified (3.3.1.7, 3.3.2).	X	X	-
106.	Pails not nested together and not packaged as specified (3.3.1.9, 3.3.2).	X	X	-
107.	Ammonia inhalant not packaged in accordance with referenced document (3.3.1.11, 3.3.2).	X	X	-
108.	Components of the first aid kit, scissors and ammonia inhalant solution not placed in the first aid kit case and the case not packaged as specified (3.3.1.12, 3.3.2).	X	X	-
109.	Lanterns not preserved as specified (3.3.1.13, 3.3.2).	X	X	-
110.	Paulins not folded and not packaged as specified (3.3.1.14, 3.3.2).	X	X	-
111.	Rope not coiled, coil not secured, and not packaged as specified (3.3.1.16, 3.3.2).	X	X	-
112.	Pointed end and hook of pike pole not protected as specified (3.3.1.17, 3.3.2).	X	X	-
113.	Fire extinguisher charges not packaged as specified (3.3.1.18, 3.3.2).	X	X	-
114.	Truck chassis not preserved in accordance with the referenced document as specified (3.3.1.21, 3.3.2, 3.3.3).	X	X	X
115.	Fiber boxes not waterproof sealed as specified (3.3.1.7, 3.3.1.9, 3.3.1.12, 3.3.1.14, 3.3.1.16).	X	X	-
116.	Consolidated packaging not as specified (3.3.1.22, 3.3.2).	X	X	-
117.	Boxes not secured to the truck when a truck is furnished (3.4.1, 3.4.2, 3.4.3).	X	X	X
118.	Strapping not zinc coated (Finish B) (3.4.1).	X	-	-
119.	Marking illegible, incomplete, or incorrect (3.5).	X	X	X

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:28Z
Check the source to verify that this is the current-version before use.

5. PREPARATION FOR DELIVERY

(This section not applicable to this specification.)

6. NOTES

6.1 Intended use. This specification is intended to be used for direct reference in contracts or purchase orders for the preservation, packaging, packing, and marking of a Fire Fighting Equipment Set: Truck Mounted; Structural, Class 530-Series (NSN 4210-00-393-0353).

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Time frame required for submission of the preproduction pack (see 3.2).
(c) Level of preservation and packaging and level of packing required (see 3.3 and 3.4). Level B preservation and packaging is intended to provide economical but limited protection and should be specified only when it has been determined the set components will be shipped in covered carriers and held in covered storage.
(d) Any special marking required (see 3.5).

6.3 Preproduction pack. Any changes or deviations of production packs from the approved preproduction pack will be subject to the approval of the contracting officer. Approval of the preproduction pack will not relieve the supplier of his obligation to preserve, package, pack, and mark the set components in accordance with this specification.

Custodian:

Army - ME

Preparing activity:

Army - ME

Review activity:

Army - SM

Project No. 4210-A070

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:28Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE MIL-F-52651A(ME) Fire Fighting Equipment Set: Truck Mounted; Structural, Class 530-Series, Packaging Of

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:28Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
US Army Mobility Equipment Research
and Development Center
ATTN: STSFB-DS
Ft. Belvoir, Va. 22060

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:28Z
Check the source to verify that this is the current version before use.