MILITARY SPECIFICATION

INTEGRATED ELECTRONIC CENTRALS
AN/ASQ-88, AN/ASQ-88A, AN/ASQ-88B and AN/ASQ-108

This amendment forms a part of Military Specification MIL-I-81036(WP) dated 15 January 1966 and has been approved by Naval Air Systems Command, Department of the Navy.

By this amendment basic MIL-I-81036 (WEP) is changed to MIL-I-81036 (AS) and throughout the specification, Bureau of Naval Weapons shall be changed to Naval Air System Command.

*Page 1, Specification Title: Delete and substitute the title of this amendment.

*Page 1, paragraph 1.2: Delete and substitute

"1.2 Classification - The Integrated Electronic Centrals shall be of four types which together shall include the following equipments:

Item	Name	Designation	MTBF	Test Plan MIL-STD-781
1	Receiver- Transmitter, Radio	RT-546A/ASQ-19	170	III
2	Receiver-Transmitter, Radio	RT-546B/ASQ-19	170	III
3	Receiver-Transmitter, Radio	RT-793/ASQ	200	III
4	Receiver-Transmitter, Radio	RT-793A/ASQ	200	III
5	Receiver-Transmitter, Radar Decoder, Pulse	RT-736/ASQ-88 KY-531/ASQ-88	200	III
6	Coder-Receiver-Transmitter	KY-532/ASQ	450	IV
7	Coder-Receiver-Transmitter	KY-532A/ASQ	450	IV
8	Amplifier-Power Supply-Receiver	AM-2349/ASQ-19 AM-2349(A)/ASQ-19	400	IV
9	Antenna	AS-909/ARA-48 AS-909(A)/ARA-48	2500	VI
10	Control, Central	C-6248/ASQ-88	900	V
11	Control, Radio Set	C-6684/ASQ	1000	V

FSC 5895

Source: https://assist.dla.mil -- Downloaded: 20261O-23T04:55Z
Check the source to verify that this is the current version before use.

Item	Name	Type Designation	MTBF	MIL-STD-781 Test Plan
12	Control, Radio Set	C-6685/ASQ	5000	V
13	Intercommunication Station	LS-460/AIC	4000	VI
14	Indicatior, Frequency Channel	ID-808/ASQ	2700	VI
15	Indicator, Frequency Channel	ID-1311/ASQ	2700	VI
16	Intercommunication Station	LS-460A/AIC or LS-460B/AIC	4000	VI

*"1.2.1 Types - Electronic Centrals covered by this specification shall include the following equipments. Each Central shall consist of the items and quantities as specified below:

*Items Required for Each Central

AN/ASQ-88	AN/ASQ-88A	AN/ASQ-88B	AN/ASQ-108
Item 1	Item 3	Item 4	Itme 2
5	5	5	5
6	7	7	6
8	8	8	8
9	9	9	9
10(2)	11(2)	11(2)	10(2)
13(2)	12(2)	12(2)	14(2)
14(2)	13(2)	15(2)	16(2)
	15(2)	16(2)	

*Item numbers correspond to items of paragraph 1.2. Quantity of each item is one unless otherwise designated by quantity in parenthesis.

*Page 1, Add paragraph 1.2.2

"1.2.2 Associated Equipment - The Centrals shall operate with the following associated equipment:

*Item	Type Designation
Indicator, Bearing Distance-Heading	ID-663/U
Control, Transponder Set	C-6280(P)/APX
Control, Radar Set	C-1159/APX-6B
Control, Radar Set	C-1272A/APA-89
Equipment	Juliet 28 (AN/ASQ-88B and AN/ASQ-108)
Juliet Control	C-8057/ARC (AN/ASQ-88B and AN/ASQ-108)

Source: https://assist.dla.mil -- Downloaded: 202610-23T04:55Z
Check the source to verify that this is the currentversion before use.

*Controls C-1159/APX-6B and C-1272A/APA-89 are used in Centrals An/ASQ-88 and AN/ASQ-108 whereas control C-6280(P)/APX is used in Centrals AN/ASQ-88A and AN/ASQ-88B."

*Page 3, paragraph 3.3.2.3: Add "KY-532/ASQ, RT-793A/ASQ
RT-793/ASQ, RT546A/ASQ-19
AM-2349A/ASQ-19

*Page 4, paragraph 3.3.2.4: Delete and substitute

"3.3.2.4 Reliability in Mean Time Between Failure-The Centrals shall have a specification mean (operating) time between failures of 55 hours when tested and accepted as outlined under the requirements of 4.4.3. For individual equipments purchased separately the requirements shall be as shown in 1.2."

Page 4, parapraph 3.3.6.1: Delete and substitute

"3.3.6.1 Short Duration-Short duration interference shall not exceed the limits of specification MIL-I-6181B except that an additional 69 db, 43 db and 58 db shall be added to the limits of curves 1, 16 and 17 using a 1 kc bandwidth respectively for tests conducted in accordance with Paragraph 3.1.1 (MIL-I-6181B).

*Page 5, paragraph 3.3.10: Add

Amplifier-Power Supply-Receiver-Antenna	AS-909A/ARA-48	Class 2
"Coder-Receiver-Transmitter	KY-532/ASQ	Class 2
Control, Radio Set	C-6684/ASQ	Class 1
Control, Radio Set	C-6685/ASQ	Class 1
Indicator, Frequency Channel	ID-1311/ASQ	Class 1
Receiver-Transmitter, Radio	RT-793/ASQ	Class 1
Receiver-Transmitter, Radio	RT-793A/ASQ	Class 1
Receiver-Transmitter, Radio	RT-546B/ASQ-19	See 3.3.10.3.
Intercommunication Station	LS-460A/AIC or LS-460B/AIC	Class 1"

Page 6, paragraph 3.3.13: Delete

*Page 6, paragraph 3.4.1: Delete "RT-546A/ASQ-19" and substitute

"RT-546A/ASQ-19, RT-546B/ASQ-19, RT-793/ASQ or RT-793A/ASQ"

Page 6, paragraph 3.4.4: Delete "KY-532A/ASQ" and substitute

"KY-532/ASQ or KY-532A/ASQ"

*Page 6, paragraph 3.4.5: Add

"for the AN/ASQ-88 AN/ASQ-108."

*Page 6, paragraph 3.4.6: Add

"for the AN/ASQ-88 and AN/ASQ-108; and ID-1311/ASQ Specification MIL-I-22768 for the AN/ASQ-88A and AN/ASQ-88B."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:55Z
Check the source to verify that this is the current version before use.

*Page 7, paragraph 3.4.7: Delete "LS-460/AIC" and substitute

"LS-460/AIC, LS-460A/AIC or LS-460B/AIC"

*Page 7: Add

"3.4.8 Communications Control-The remote control functions required for the operation of the communication receiver and auxiliary receiver function shall meet the requirements of Control, Radio Set C-6684/ASQ Specification MIL-C-81441 for the AN/ASQ-88A and AN/ASQ-88B.

3.4.9 TACAN Control-The remote control function requirement for the operation of the UHF Navigation function shall meet the requirements of Control Radio Set C-6685/ASQ Specification MIL-C81442 for the AN/ASQ-88A and AN/ASQ-88B.

3.4.10 Control Radio Set - The remote control function required for the operation of Juliet shall meet the requirements of Control, Radio Set/C-8057/ARC Specification MIL-C-81470(AS).

Page 7, paragraph 4.2.2: Delete last sentence

Page 11, paragraphs 4.4.3, 4.4.3.1 and 4.4.3.2: Delete and substitute

"4.4.3 Reliability Assurance Tests-Reliability Assurance Tests shall be conducted using MIL-STD-781. A Qualification Phase and Sampling Phase Test shall be conducted.

4.4.3.1 Qualification Phase-Prior to the acceptance of equipments under the contract or order, a minimum of three (3) equipments shall be tested as outlined in MIL-STD-781, under the section entitled "Qualification Phase of Production Reliability Tests". The maximum number of equipments to be used shall be those listed in Table 5 of MIL-STD-781. For the Qualification Phase, Test Level E shall be used. The Accept-Reject Criteria for Test Plan III shall be used.

4.4.3.2 Reliability Sampling Phase Tests-Samples of the equipment shall be tested as outlined in MIL-STD-781, under the Section entitled "Sampling Phase of Production Reliability Tests". For the Sampling Phase, Test Level E shall be used. The accept-reject criteria for Test Plan III shall be → used to determine the length of the tests until an accept or reject decision is reached).

4.4.3.2.1 Lot Size for Sampling Phase-The entire contract quantity (with the exception of those equipments used in the Qualification Phase) shall be evaluated as one lot. The test program shall start the first month after the Qualification Phase has been completed. Samples shall be selected and placed on test in the same manner as though one month's production was a lot. The samples shall be tested until an accept or reject decision is reached. In the meantime other equipments constructed shall be shipped. The test results shall be summarized monthly for the procuring activity. The procuring activity reserves the right to stop the acceptance of equipment at any time after one or more reject decisions have been reached,

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:55Z
Check the source to verify that this is the current version before use.

pending a review of the contractor's effort to improve the equipment, the equipment parts, the equipment quality control etc., so that the entire contract quantity will show an accept decision."

*Page 11, paragraph 4.4.3.3(1): Add

"or RT-546B"

*Page 12, paragraph 4.4.3.4(1)

Delete - "AM-2349 or AS-909"
Add - "AM-2349 or AM-2349A
AS-909 or AS-909A"

*Page 12, paragraph 4.4.3.4(3)

Add - "LS-460A or LS-460B"

*Page 13, paragraph 4.4.3.4(5)

Add - or KY-533/ASQ

*Page 13, paragraph 4.4.3.4: Add

"(6) UHF Communications - RT-793 or RT-793A

Characteristic	Specification Requirement	Acceptance Requirement (if lower)
Receiver Sensitivity Main Receiver	Standard 4 uv/10 db Service 7 uv/10 db	9.9 uv/10 db
Guard Reciever	Standard 5 uv/10 db Service 10 uv/10 db	14.1 uv/10 db
Audio Capability	Standard not less than 250 mw Service not less than 79 mw	Not less than 79 mw
RF Power Output	Standard not less than 16 w Service not less than 7 w	Not less than 5 w
Modulation Capability (input to clipping)	Not less than 80%	Not less than 70%
Tone Modulation Capability	Not less than 80%	Not less than 70%

Source: https://assist.dla.mil -- Downloaded: 202610-23T04:55Z
Check the source to verify that this is the current version before use.

Characteristic	Specification Requirement	Acceptance Requirement (if lower)
Side Tone Level	Standard not less than 250 mw Service not less than 50 mw	Not less than 50 mw

*Page 18, Figure 1 title: Add

"or RT-546B/ASQ-19".

*Page 19, Figure 2 title: Add

"AN/ASQ-88A, AN/ASQ-88B or AN/ASQ-108"

*Page 20, 21 and 22: Figures 3, 4 and 5: Delete

*Page 24, paragraph 6.5(4), after the first sentence: Delete and substitute

"MIL-E-5400E
MIL-I-6181B"

Pages 24 and 25, paragraphs 6.9 and 6.9.1: Delete

Page 25, paragraph 6.11, under SPECIFICATIONS Military: Add

"MIL-R-81443	Receiver-Transmitter, Radio, RT-793/ASQ
MIL-C-81441	Control, Radio Set, C-6684/ASQ
MIL-C-81442	Control, Radio Set, C-6685/ASQ
MIL-R-7893	Radar Identification Set AN/APX-6B
MIL-C-7953	Coder Group AN/APA-89"
MIL-C-81470(AS)	Control Radio Set C-8057/ARC"

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:55Z
Check the source to verify that this is the current version before use.