MIL-P-50574B (AR)
3 November 1978
SUPERSEDING
MIL-P-50574A (PA)
30 October 1973

MILITARY SPECIFICATION

PROJECTILE, 155MM, HE ROCKET ASSISTED, M549 & M549A1, ACCESSORIES FOR

This specification is approved for use by the U.S. Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification contains requirements not covered by the drawings and provides quality assurance provisions for the fabrication of accessories required in loading and assembling of the 155MM Rocket Assisted Projectile, M549.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification For

STANDARDS

MILITARY

MIL-STD-1169 - Packaging, Packing and Marking for Inert Ammunition

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC: 1320

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

DRAWINGS

US ARMY RESEARCH AND DEVELOPMENT COMMAND (ARRADCOM)

PRODUCT AND PACKAGING DRAWINGS

9235989 - Trap
9235990 - Spacer, Grain
9235991 - Cushion, Grain Forward
9235992 - Cushion, Grain, Aft
9235993 - Ring Seal
9235994 - Obturator
9276682 - Rocket, Off Cap Assembly
9276683 - Cap
9276684 - Plate
9280059 - Support, Grain
9280060 - Grain Support Bonding Assembly
9280897 - Packing and Marking for Box, Amm. Fiberboard, for Ring, Shear Seal for Cartridge 155MM, M549

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity as directed by the Contracting Officer).

2.2 Other publications.-The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

E8 - Tension Testing of Metallic Materials
E18 - Tests for Rockwell Hardness of Metallic Materials

(Copies may be purchased directly from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pa. 19103).

3. REQUIREMENTS

3.1 Material.-Materials shall be in accordance with applicable drawings and specifications.

3.2 Parts.-The parts shall comply with all requirements specified on drawings listed in paragraph 2.1 and associated

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

drawings and with all requirements specified in applicable specifications and standards.

3.3 Molding defects.-The molded component shall be free of porosity, foreign inclusions, ripples, voids, surface imperfections, and excess flashing.

3.4 Stamping defects.-Stamped components shall be free of cuts, tears, creases, ragged edges and foreign matter.

3.5 Obturator breaking load.-The obturator shall exhibit a minimum breaking load of 400 pounds when tested as specified in 4.5.3.

3.6 First article inspection.-This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.7 Workmanship.-Allparts shall be fabricated and finished in a thorough workmanlike manner. They shall be free of burrs, chips, sharp edges, cracks, unblended radii, tears, holes, nicks, surface defects, dirt, grease, rust, corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent. All required markings shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions.-Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections.-The following types of inspection shall be conducted on this item:

a. First Article Inspection
b. Quality Conformance Inspection

4.3 First article inspection

4.3.1 Submission.-The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

Part Description	Drawings	Quantity
Trap	9235989	10
Spacer, Grain	9235990	20 Consecutively produced from each set of dies
Cushion, Grain Forward	9235991	20 Consecutively produced from each set of dies
Cushion, Grain Aft	9235992	20 Consecutively produced from each set of dies
Ring Seal	9235993	10
Obturator	9235994	20 Consecutively produced from each cavity of each mold
Rocket-Off Cap Assembly	9276682	10
Cap	9276683	10
Plate	9276684	10
Support, Grain	9280059	20 Consecutively produced from each set of dies
Grain Support Bonding Assembly	9280060	10

4.3.2 Inspections to be performed.- See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection - See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 2	DRAWING NUMBER
	Projectile, 155MM, HE, Rocket Assisted, M549, Accessories For		See Below
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Trap (Dwg. 9235989)				
	Examination for Defects	10	-	3.2	4.4.2.1/4.4.2.2
	Yield Strength and Elongation	See Note a	-	3.2	4.5.2
	Spacer, Grain (Dwg. 9235990)				
	Examination for Defects	20	-	3.2	4.4.2.5
	Cushion, Grain Forward (Dwg. 9235991)				
	Examination for Defects	20	-	3.2	4.4.2.6
	Cushion, Grain Aft (Dwg. 9235992)				
	Examination for Defects	20	-	3.2	4.4.2.7
	Ring Seal (Dwg. 9235993)				
	Examination for Defects	10	-	3.2	4.4.2.8
	Obturator (Dwg. 9235994)				
	Examination for Defects	20	-	3.2	4.4.2.9
	Test for Breaking Load	7	-	3.5	4.5.3

NOTES: Note a. Two from the highest and two from the lowest hardness reading.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-50574B (AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
	CONTINUATION SHEET				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Rocket-Off Cap Assembly (Dwg. 9276682) Examination for Defects	10	-	3.2	4.4.2.12
	Cap (Dwg. 9276683) Examination for Defects	10	-	3.2	4.4.2.10
	Plate (Dwg. 9276684) Examination for Defects	10	-	3.2	4.4.2.11
	Support, Grain (Dwg. 9280059) Examination for Defects	20	-	3.2	4.4.2.3
	Grain Support Bonding Assembly (Dwg. 9280060) Examination for Defects	10	-	3.2	4.4.2.4

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection

4.4.1 Inspection lot formation.-Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination - See MIL-A-48078.

a. Sampling plans. Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans and procedures for Major and Minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-50574B (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.1	Trap, Prior to Phosphate Coating				9235989
					NEXT HIGHER ASSEMBLY
					9280060
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Outside diameter (min.)		0.40%	3.2	Gage
102	Thickness		0.40%	3.2	Gage
103	Physical properties		Note a	3.2	Note a
Minor					
201	Inside diameter		0.65%	3.2	Gage
202	Radii missing or incorrect		0.65%	3.2	Visual
203	Evidence of poor workmanship		1.0%	3.7	Visual
204	Surface to be free of rust and contamination		0.65%	3.2	Visual

NOTES:

a. See Paragraph 4.5.2.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-50574B (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.2	Trap, After Phosphate Coating		9235989
			NEXT HIGHER ASSEMBLY 9280060

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Outside diameter (max.)		0.40%	3.2	Gage
Minor					
201	Protective finish missing, incomplete or inadequate		0.65%	3.2	Visual
202	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-50574B (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.3	Support, Grain		9280059
			NEXT HIGHER ASSEMBLY 9280060

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Inside diameter	Note a	0.40%	3.2	Gage
102	Outside diameter	Note a	0.40%	3.2	Gage
103	Thickness	Note a	0.40%	3.2	Gage
104	True position of inside diameter to outside diameter	Note a	0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship	Note a	1.0%	3.7	Visual
202	Stamping defects	Note a	0.65%	3.4	Visual

NOTES: a. See paragraph 4.4.3.1.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.4	Grain Support Bonding Assembly	1 OF 1	9280060
			NEXT HIGHER ASSEMBLY 9235999

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Center hole of grain support not aligned with hole in trap		0.40%	3.2	Visual
102	Grain support not bonded sufficiently to assure no movement can occur to obscure trap hole or cause material to fold		0.40%	3.2	Manual
Minor					
201	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.5	Spacer, Grain		9235990
			NEXT HIGHER ASSEMBLY 9235999

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Total length	Note a	0.40%	3.2	Gage
102	Total width	Note a	0.40%	3.2	Gage
103	Total height	Note a	0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship	Note a	1.0%	3.7	Visual
202	Stamping defects	Note a	0.65%	3.4	Visual

NOTES: a. See Paragraph 4.4.3.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.6	Cushion, Grain Forward	1 OF 1	9235991
			NEXT HIGHER ASSEMBLY 9235999

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Inside diameter	Note a	0.40%	3.2	Gage
102	Outside diameter	Note a	0.40%	3.2	Gage
103	Width	Note a	0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship	Note a	1.0%	3.7	Visual
202	Stamping defects	Note a	0.65%	3.4	Visual

NOTES: a. See paragraph 4.4.3.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS MIL-P-50574B (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.7	Cushion, Grain Aft				9235992
					NEXT HIGHER ASSEMBLY 9235999
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Inside diameter	Note a	0.40%	3.2	Gage
102	Outside diameter	Note a	0.40%	3.2	Gage
103	Thickness	Note a	0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship	Note a	1.0%	3.7	Visual
202	Stamping defects	Note a	0.65%	3.4	Visual

NOTES: a. See paragraph 4.4.3.1.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assistandardi... - Downloaded: 2026-Nov-22 12:07:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-50574B (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.8	Ring, Seal	1 OF 1	9235993
			NEXT HIGHER ASSEMBLY: 9235999

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Length of large inside diameter section		0.40%	3.2	Gage
102	Large inside diameter		0.40%	3.2	Gage
103	Runout of large inside diameter to outside diameter		0.40%	3.2	Gage
104	Outside diameter		0.40%	3.2	Gage
Minor					
201	Total length		0.65%	3.2	Gage
202	Small inside diameter		0.65%	3.2	Gage
203	Runout of small inside diameter to outside diameter		0.65%	3.2	Gage
204	Angle between small inside diameter and outside diameter missing or improper		0.65%	3.2	Visual
205	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-50574B (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.9	Obturator		9235994
			NEXT HIGHER ASSEMBLY 9235999

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Large inside diameter	Note a	0.40%	3.2	Gage
102	Thickness at large inside diameter	Note a	0.40%	3.2	Gage
103	Thickness at small inside diameter	Note a	0.40%	3.2	Gage
104	Distance from large inside diameter to small inside diameter	Note a	0.40%	3.2	Gage
105	Mechanical properties	Note b	0.40%	3.5	4.5.3
Minor					
201	Evidence of poor workmanship	Note a	1.0%	3.7	Visual
202	Molding defect	Note a	0.65%	3.3	Visual

NOTES: a. See paragraph 4.4.3.1.
b. See paragraph 4.4.3.2.

Source: https://assist.daps.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
4.4.2.10	Cap				9276683
					NEXT HIGHER ASSEMBLY
					9276682
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pitch diameter of threads		0.40%	3.2	Gage
102	True position of thread to Datum A		0.40%	3.2	Gage
103	Diameter of O-ring groove		0.40%	3.2	Gage
104	True position of O-ring groove		0.40%	3.2	Gage
105	Diameter over knurls		0.40%	3.2	Gage
106	Largest outside diameter (over lip)		0.40%	3.2	Gage
107	Length of full knurl, including relief, min		0.40%	3.2	Gage
108	Width of knurl relief, max.		0.40%	3.2	Gage
Minor					
201	Diameter of thread undercut		0.65%	3.2	Gage
202	Distance from threaded end surface to O-ring groove		0.65%	3.2	Gage
203	Overall length		0.65%	3.2	Gage
204	Thickness at threaded end		0.65%	3.2	Gage
205	Height of boss on threaded end		0.65%	3.2	Gage
206	Diameter of boss on threaded end surface		0.65%	3.2	Gage
207	Width of O-ring groove		0.65%	3.2	Gage
208	Width of undercut		0.65%	3.2	Gage
209	Distance from threaded end surface to end of undercut		0.65%	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-50574B (AR)

PARAGRAPH	TITLE	SHEET 2 OF 2	DRAWING NUMBER
4.4.2.10	CONTINUATION SHEET		9276683
			NEXT HIGHER ASSEMBLY
			9276682

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
210	Diameter of section between undercut and O-ring groove		0.65%	3.2	Gage
211	Any radius or chamfer missing or improper		0.65%	3.2	Visual
212	Distance from boss on threaded end to lip		0.65%	3.2	Visual
213	True position of boss on threaded end		0.65%	3.2	Visual
214	Flat or taper missing or improper on boss		0.65%	3.2	Visual
215	Surface finish improper on boss and O-ring groove		0.65%	3.2	Visual
216	Marking missing, misleading or improper		0.65%	3.2	Visual
217	Evidence of poor workmanship		1.0%	3.2	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.11	Plate	1 OF 1	9276684
			NEXT HIGHER ASSEMBLY 9276682

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Inside diameter		0.40%	3.2	Gage
102	Thickness		0.40%	3.2	Gage
Minor					
201	Size or location of tabs obviously improper		0.65%	3.2	Visual
202	Outside diameter of center section		0.65%	3.2	Gage
203	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-50574B (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.12	Rocket Off Cap Assembly		9276682
			NEXT HIGHER ASSEMBLY 9235999

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Gap between plate and lip exceeds max.		0.40%	3.2	Gage
102	Plate loose		0.40%	3.2	Manual
Minor					
201	Protective finish missing or improper		0.65%	3.2	Visual
202	Marking missing, misleading or improper		0.65%	3.2	Visual
203	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil - Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

4.4.3 Testing.-Testing is described in the First Article and Quality Conformance Inspection tables.

4.4.3.1 Quality conformance testing of molded and stamped components.-In lieu of MIL-STD-105, the following sampling plan may be used for the Quality Conformance Inspections described in the preceeding tables for the molded and stamped components:

a. The first twenty (20) consecutive pieces from each set of dies or mold cavity.
b. Five (5) pieces from each set of dies or mold cavity at intervals of 1,000 pieces from each set of dies or mold cavity.
c. The last five (5) pieces from each set of dies or mold cavity (due to die or mold replacement or end of the contract).

The occurrence of any defect on any sample piece shall be cause for taking corrective action and for rejecting all pieces produced since the last acceptable sample.

4.4.3.2 Obturator breaking load.-A sample of twenty (20) obturators shall be randomly selected from each lot of obturators. If any of the samples fail to meet the requirements of 3.5, the lot shall be rejected.

4.4.4 Inspection equipment.-The inspection equipment to perform the examination and tests prescribed herein is described in the 'Paragraph Reference/Inspection Method' column in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.2 herein.

4.5 Methods of inspection

4.5.1 Materials, components and processes.-Compliance with all requirements of Section 3 of this specification shall be ascertained by current and continuing examination of inspection and test data to determine that all components (parts, assemblies, and materials) have been inspected and tested and found to comply with their respective drawing and specification requirements, and that all specified manufacturing processes have been followed.

4.5.1.1 Visual and mechanical inspections.-The visual, manual and mechanical inspections and tests shall verify compliance with the requirements of Sections 3 and 5 of this specification in accordance with 4.4.2 herein and Table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

4.5.2 Trap physical properties

4.5.2.1 Hardness.-Each trap shall be subjected to a hardness test on the surface indicated on the drawing and the results recorded. The test shall be conducted in accordance with American Society for Testing and Materials, Method E18. The hardness readings thus obtained shall be used as the basis for selecting the tension test samples of 4.5.2.2.

4.5.2.2 Yield strength and elongation.-Two traps from every heat treat batch shall be selected for this test (one trap from the highest hardness reading and one trap from the lowest hardness reading). One tensile specimen shall be taken from each of these traps and tested in accordance with American Society for Testing and Materials, Method E8, with the largest small-size, proportional round specimen possible. If any specimen fails to meet the requirements of the dwg. 9235989, the batch shall be rejected subject to retest as specified in 4.5.2.3.

4.5.2.3 Retest.-When a tensile specimen selected from the highest hardness reading, fails to comply with the yield strength or elongation requirements of the drawing, the trap with the next highest hardness shall be selected for test. Likewise, if a tensile specimen selected from the lowest hardness reading fails to comply with the requirements, the next lowest hardness reading shall be selected. Selection of samples shall continue until an acceptable hardness range is established. An acceptable hardness range is a range which provides acceptable yield strength and elongation results. Any trap which falls outside this range shall be rejected.

4.5.3 Obturator breaking load.-The obturator shall be tested for breaking load using an approved test fixture. The test fixture shall consist of two 1 inch diameter opposed spindles machined to the internal profile of the obturator. The obturator shall be assembled and tested, using test speed of 2.00 inches per minute.

5. Packaging

5.1 Packaging, packing and marking of accessories other than ring seal.-With the exception of the ring seal, obturator, and rocket-off cap, packaging, packing and marking for components and assemblies shall be as specified in MIL-STD-1169.

5.2 Obturator.-Obturators shall be packaged in accordance with Dwg. 9235994.

5.3 Ring seal.-Packaging, packing and marking of the ring seal shall be in accordance with Dwg. 9280897.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

5.4 Rocket off cap.-The rocket off cap shall be packaged and marked to comply with the requirements for unit packaging of Level C of MIL-STD-1169.

6. NOTES

6.1 Intended use.-The components covered by this specification are intended for use on the M549, 155MM, HE, Rocket Assisted Projectile.

6.2 Ordering data.-See MIL-A-48078.

6.3 Inspection equipment designs - See MIL-A-48078.-Submit designs as required to Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAR-I, Dover, NJ 07801.

6.4 Visual examination qualification.-When compliance with the applicable requirement is in doubt as a result of visual examination the characteristic may be measured or gaged to determine acceptability.

6.5 Drawings.-Drawings listed in Section 2 of this specification under the heading US Army Armament Research and Development Command (ARRADCOM) may also include drawings prepared by, and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARRADCOM.

6.6 Changes from previous issue.-Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Custodian:
Army - AR

Preparing activity:
Army - AR

Project No. 1320-A427

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.