MIL-S-52420A(ME)
10 January 1973
SUPERSEDING
MIL-S-52420(MO)
12 April 1965

MILITARY SPECIFICATION

SHEATH, PLUMB BOB WITH ARROWS HOLDER

1. SCOPE

1.1 This specification covers a plumb bob sheath with arrows holding clip.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

Federal

PPP-B-601	- Boxes, Wood, Cleated-Plywood.
PPP-B-636	- Boxes, Shipping, Fiberboard.

Military

MIL-P-116	- Preservation, Methods of.

STANDARDS

Military

MIL-STD-129	- Marking for Shipment and Storage.

DRAWINGS

ME

TA1321/E7560	- Sheath, Plumb Bob with Arrows Holder.

FSC 5210

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:17Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, and drawings required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classificati Committee, ATTN: Tariff Publishing Officer, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., ATTN: Tariff Order Section, 1616 P Street, NW, Washington, DC 20036.)

3. REQUIREMENTS

3.1 Description. The plumb-bob sheath with arrows-holding clip shall be in accordance with Top Assembly T21321TE7560 and as specified herein.

3.1.1 Drawings. The drawings forming a part of this specification are end product drawings. No deviation from the prescribed dimensions or tolerances is permissible without prior approval of the contracting officer. Any data (e.g. shop drawings, layouts, flow sheets, processing procedures, etc.) prepared by the supplier or obtained from a vendor to support fabrication and manufacture of the production item shall be made available, upon request, for inspection by the contracting officer or his designated representative.

3.2 Material. Material shall be as specified herein and as shown on the applicable drawings. Materials not specified shall be selected by the supplier and shall be subject to all provisions of this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:17Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Acceptability criteria. Sheaths which conform to all requirements in sections 3 and 5 of this specification and pass all applicable examinations and tests in section 4 of this specification will be considered acceptable by the Government.

4.1.2 Component and material inspection. The supplier is responsible for insuring that components and materials used are manufactured, examined, and tested in accordance with referenced specifications and standards.

4.2 Classification of inspection. Inspection shall be classified as follows:

(a) Quality conformance inspection (see 4.3).
(b) Inspection of preparation for delivery (see 4.5).

4.3 Quality conformance inspection.

4.3.1 Examination. Each sheath shall be examined as specified in 4.4.1. Presence of one or more defects shall be cause for rejection.

4.4 Inspection procedure.

4.4.1 Examination. The sheath shall be examined for the following defects:

101. Material not as specified.
102. Dimensions not as specified.
103. Stitching and riveting not as specified.
104. Assembly not complete or not correct.
105. Identification marking not as specified.
106. Workmanship not as specified.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:17Z
Check the source to verify that this is the current version before use.

4.5 Inspection of preparation for delivery.

4.5.1 Quality conformance inspection of pack.

4.5.1.1 Unit of product. For the purpose of inspection, a completed pac prepared for shipment shall be considered a unit of product.

4.5.1.2 Examination. Each sheath shall be examined for the following defects. Presence of one or more defects shall be cause for rejection.

107.	Materials, methods, and containers not as specified for level A or B. Each incorrect material, method, or container shall be considered one defect.
108.	Gross weight exceeds 200 pounds for level A.
109.	Strapping not zinc coated for level A.
110.	Size or weight exceeds the limitations of the box specification for level B.
111.	Box not closed and sealed as specified for level B.
112.	Marking missing, illegible, incorrect, or incomplete.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A, B, or C as specified (see 6.2).

5.1.1 Level A. Each sheath shall be preserved in accordance with MIL-P-116, method IC-1.

5.1.2 Level B. Each sheath shall be preserved in accordance with MIL-P-116, method III, using a plastic bag.

5.1.3 Level C. The sheaths shall be packaged in the suppliers cartons or bags in a manner to afford protection against deterioration and damage from the supplier to the initial destination.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A. The sheaths shall be packed together in a close-fitting box conforming to PPP-B-601, overseas type, style I, grade B. The gross weight of each box shall not exceed 200 pounds. Box closure and strapping shall be in accordance with the appendix to the box specification. Strappin shall be zinc coated on all international logistics shipments.

Source: https://assist.dla.mil -- Downloaded: 2026-0-22121:17Z
Check the source to verify that this is the current version before use.

5.2.2 Level B. The sheaths shall be packed together in a close-fitting box conforming to PPP-B-636, V3c. The box shall not exceed the size or weight limitations of the box specification. The box shall have all seams, corners, and manufacturer's joints sealed with tape and shall be closed and secured in accordance with the appendix to the box specification.

5.2.3 Level C. The sheaths shall be packed to assure carrier acceptance and safe delivery to destination at lowest ratings in fiberboard containers complying with Uniform Freight Classification rules or National Motor Freight Classification rules.

5.3 Marking. Packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The plumb-bob sheath with arrows-holding clip is intended for tapeman's use in survey work.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Level of preservation and packaging and level of packing required (see 5.1 and 5.2). Level B preservation, packaging, and packing is intended to provide economical but limited protection and should be specified only when it is determined the sheaths will be held in covered storage.

Custodian:

Army - ME

Preparing activity:

Army - ME

Project No. 5210-A210

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:17Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS. This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION MIL-S-5249C(ME) Sheath, Plumb Bol[illegible]th Arrows Holder

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO (If "yes", in what way?)

4. REMARKS (Attach any pertinent data which may be of use in improving this specification. If there are additional papers attach to form and place both in an envelope addressed to preparing activity.)

SUBMITTED BY (Printed or typed name and activity - Optional)

DATE

DD FORM 1426
11 Oct 72 (Rev)

REPLACES [illegible] OF 1 OCT 64 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:17Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
U. S. ARMY MOBILITY EQUIPMENT
RESEARCH, DEVELOPMENT
CENTER
FORT BELVOIR, VIRGINIA 22060

OFFICIAL BUSINESS
AMSME-RZD-S

POSTAGE AND FEES PAID
DOD-314

COMMANDER
U. S. ARMY MOBILITY EQUIPMENT
RESEARCH, DEVELOPMENT CENTER
ATTN: AMSME-RZD-S
FORT BELVOIR, VIRGINIA 22060

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:17Z
Check the source to verify that this is the current version before use.