MILITARY SPECIFICATION

ANTENNA, FIXED, HIGH FREQUENCY, HORIZONTAL
OMNIDIRECTIONAL BROADBAND

This amendment forms a part of Military Specification MIL-A-28768/4(EC), dated 15 January 1985, and is approved for use within the Space and Naval Warfare Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* 2.1.1, after "SPECIFICATION" "MILITARY", add:

"MIL-T-28732 Transformer, Impedance Matching, Balanced To Unbalanced (Balun)"

PAGE 3

* TABLE II: Delete and substitute:

"

TABLE II. Pattern and gain.

Frequency (MHz)	Main beam (minimum) (degrees)	Main beam (maximum) (degrees)	UHPP 1/ (minimum) (degrees)	LHPP 2/ (maximum) (degrees)	Gain (minimum) (dBi) 3/
4	29	40	50	20	6.0
8	19	23	30	10	7.5
12	16	19	25	8	7.5
16	13	16	22	7	8.0
30	8	10	15	5	10.0

1/ Upper half power point (see 6.3)
2/ Lower half power point (see 6.3)
3/ Decibels isotropic

"

* 3.5.6: Delete and substitute:

"3.5.6 Input impedance and frequency. The nominal input impedance shall be 50 ohms. If an impedance matching balanced to unbalanced transformer is used, the transformer shall conform to the requirements of MIL-T-28732, except that the Maintainability paragraph is not applicable. The frequency range of the balun shall be the same as that specified for the type of antenna (see 1.2) with which the balun is to be used."

* 4.1 and 4.2: Delete and substitute:

"4.1 Quality assurance provisions. Quality assurance provisions shall be in accordance with MIL-A-28768 and as specified in 4.2 through 4.4.

"4.2 Classification of inspections. The inspections specified herein are classified as specified in a and b:

a. First article inspection (see 4.3)
b. Quality conformance inspection (see 4.4)

"4.3 First article inspection. First article inspection shall be conducted on the antenna curtain(s) and the balun connected together as one unit. In addition to the first article inspection specified in MIL-A-28768, the inspections specified in a through l shall be conducted:

a. Verify conformance to frequency range requirements of 3.5.1
b. Verify conformance to size requirements of 3.2

AMSC N/A FSC 5985

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:03Z
Check the source to verify that this is the current version before use.

c. Verify conformance to rotational requirements of 3.4.1
d. Verify conformance to installation design requirements of 3.4.3
e. Verify conformance to power requirements of 3.5.2
f. Verify conformance to VSWR requirements of 3.5.6.1
g. Verify conformance to efficiency requirements of 3.5.7
h. Verify conformance to the Lightning protection paragraph of MIL-A-28768
i. Verify conformance to the Spurious frequencies paragraph of MIL-T-28732
j. Verify conformance to the Unbalanced paragraph of MIL-T-28732
k. Verify conformance to the Enclosure paragraph of MIL-T-28732
l. Verify conformance to the gain requirements of 3.5.3 and the pattern requirements of 3.5.5 by means of tests or analysis.

"4.4 Quality conformance inspection. Quality conformance inspection shall consist of the applicable production inspection shown in Group A of the Examinations and tests TABLE of MIL-A-28768, except that the performance tests shall not be required. Conformance to the size of the various components and completeness of the antenna shall be verified."

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Preparing activity:
NAVY - EC

(Project No. 5985-N549(EC))

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:03Z
Check the source to verify that this is the current version before use.