INCH-POUND
MIL-DTL-28754/101A
W/AMENDMENT 3
12 August 2026
SUPERSEDING
MIL-DTL-28754/101A
W/AMENDMENT 2
25 April 2024

MILITARY SPECIFICATION SHEET

CONNECTORS, ELECTRICAL, MODULAR, TYPE IV, CONNECTOR, 0.6 PITCH, 250 CONTACT, CENTER

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-28754.

AMSC N/A
FSC 5935
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:57Z
Check the source to verify that this is the current version before use.





FIGURE 1. Dimensions and configurations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:57Z
Check the source to verify that this is the current version before use.



VIEW A - A






FIGURE 1. Dimensions and configurations – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:57Z
Check the source to verify that this is the current version before use.




SECTION C - C




DETAIL D

FIGURE 1. Dimensions and configurations – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:57Z
Check the source to verify that this is the current version before use.



DETAIL E
SHELL SHOWN BODY
OMITTED FOR CLARITY



DETAIL F

FIGURE 1. Dimensions and configurations – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:57Z
Check the source to verify that this is the current version before use.

NOTES:

1. Dimensions are in inches.
2. Unless otherwise specified, tolerances are plus or minus 0.005 inch for three place decimals, plus or minus 0.01 inch for two place decimals and plus or minus 5° for angles.
3. The carrier strip shall remain attached to the contact tails to facilitate shipping. The conductors shall be scored or thinned at the point indicated to facilitate removal at final assembly, and shall break off in 5 plus or minus 2 flexure cycles of plus or minus 45° from nominal. The carrier strip is not required to be continuous.
4. Plating defects on the carrier strip above the score line are acceptable, provided that inspection testing of the connector is not affected.
5. Dimensional limits apply after plating.
6. Flash around blade contacts not to exceed 0.010 inch from the surface of the insulator and shall be firmly attached.
7. The connector body shall be made of 5 identical sections, each containing 50 contacts.
8. Contact numbers 1, 50, 201 and 250 shall be marked in contrasting color on the contact shield in 0.06 high characters using epoxy ink in accordance with A-A-56032. Mark part number, manufacturer's CAGE number and date code in this area with 0.06 inch high characters using contrasting color ink in accordance with A-A-56032. All markings shall be permanently and legibly marked in accordance with MIL-STD-1285.

FIGURE 1. Dimensions and configurations – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:57Z
Check the source to verify that this is the current version before use.




FIGURE 2. Contact pattern numbering.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:57Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configurations: See figures 1 and 2. See table I.

Materials and finishes:

Contacts: The contacts shall be brass, alloy UNS No. C26000 in accordance with ASTM B36/B36M, temper 1/2 hard. The contacts shall be finished as follows:

Above the connector body, the contacts shall be finished by the following steps:

Steps 1, 2, 4, 5, and 7 – SAE-AMS-P-81728 cleanliness.

Step 3 – Nickel Sulfamate underplate in accordance with SAE-AMS-QQ-N-290, Class 1, to 50 microinches min.

Step 6 – Tin-lead plate (90% Sn – 10% Pb), SAE-AMS-P-81728, 0.0003 – 0.0005 inch thickness.

Step 8 – Form the contacts.

Step 9 – Reflow in hot (235°C) peanut oil, 30 seconds. Quality assurance of SAE-AMS-P-81728 shall apply. No indication of dewetting or poor solderability shall be allowed.

Step 10 – Rinse in mineral spirits, MIL-PRF-680.

Step 11 – Selectively coat the area indicated on the drawing with solder, in accordance with J-STD-006, SN60 or SN63, to a thickness of 0.0005 – 0.003 inch. Use flux, in accordance with J-STD-004, type RMA, as required.

The connector body shall be molded, plastic, diallylphthalate in accordance with ASTM D5948, type GDI-30F or type SDG-F.

The connector shell shall be aluminum alloy 6061,temper T6 in accordance with SAE AMS4150 or temper T6510 or T6511 in accordance with SAE AMS4173 or ASTM B241/241M.

Aluminum alloy shall be anodic coating, MIL-PRF-8625, type III, class 2, dyed black. The inside surface of the 0.098 diameter hole shall be 90% free of anodize. The anodic coating shall be 0.0020 plus or minus 0.0005 thick on all flat surfaces. Corners shall have a slight radius to facilitate coverage.

Solderability: In accordance with MIL-DTL-28754.

ELECTRICAL REQUIREMENTS:

Dielectric withstanding voltage: The connector shall meet the requirements of test procedure EIA-364-20, method B, test condition I for 350 VAC (RMS) 60 Hz, or 500 VDC.

Low level signal contact resistance: Voltage drop shall not exceed 1.2 millivolts. Wire size is not applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:57Z
Check the source to verify that this is the current version before use.

Contact resistance: Voltage drop shall not exceed 30 millivolts at 3 Amps current.

Voltage rating: 300 Volts, AC (RMS), at sea level.

Durability: In accordance with MIL-DTL-28754, voltage drop shall not exceed 35 mV after testing.

Part or Identifying Number (PIN): M28754/101- (Dash number from table I).

TABLE I. Dash numbers.

Dash number	X Dimension
-1	0.103 plus or minus 0.008
-2	0.127 plus or minus 0.008

First article testing: The connector shall meet the tests of MIL-DTL-28754, table IV, type IV, except for Subgroup IV, Fin/Header torque, Fin cantilever load, and Guide rib strength test.

Number of units to be inspected: Twelve (12) units of each dash number shall be inspected.

Backplane contacts: Low Insertion Force (LIF) contacts in accordance with MIL-C-28859 or MIL-DTL-28754 are strongly recommended for use with this connector.

Compatibility: These connectors may be used with the frames described in MIL-DTL-28754/92.

Amendment notations. The margins of this specification are marked with vertical lines to indicate where modifications from this amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Referenced documents. In addition to MIL-DTL-28754, this document references the following:

A-A-56032
MIL-PRF-8625
MIL-C-28859
MIL-DTL-28754/92
MIL-PRF-680
MIL-STD-1285
ASTM B36/B36M
ASTM B241/B241M
ASTM D5948
EIA-364-20
SAE AMS4150
SAE AMS4173
SAE-AMS-P-81728
SAE-AMS-QQ-N-290
J-STD-004
J-STD-006

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:57Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodian:
Army – CR
Navy – AS
DLA - CC

Preparing activity:
DLA – CC

(Project 5935-2026-038)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:57Z
Check the source to verify that this is the current version before use.