INCH-POUND

MIL-PRF-28776D
SUPPLEMENT 1
1 November 2002

PERFORMANCE SPECIFICATION

RELAYS, HYBRID, ESTABLISHED RELIABILITY,
GENERAL SPECIFICATION FOR

This supplement forms a part of MIL-PRF-28776D, dated 1 November 2002.

SPECIFICATION SHEETS

MIL-PRF-28776/1	-	Relays, Hybrid, Established Reliability, DPDT, Low Level to 1.0 Ampere (Transistor Driven) (Electromechanical Output).
MIL-PRF-28776/3	-	Relays, Hybrid, Established Reliability, DPDT, Low Level to 1.0 Ampere (Sensitive Coil Operate Power at 25°C) (Transistor Driven) (Electromechanical Output) With Diode Coil Suppression.
MIL-PRF-28776/4	-	Relays, Hybrid, Established Reliability, SPDT, Low Level to 1.0 Ampere (Sensitive, Coil Operate Power at 25°C) (Transistor Driven) (Electromechanical Output) With Diode Coil Suppression.
MIL-PRF-28776/5	-	Relays, Hybrid, Established Reliability, SPDT, Low Level to 1.0 Ampere (Transistor Driven) (Electromechanical Output) With Diode Coil Suppression.
MIL-PRF-28776/6	-	Relays, Hybrid, Established Reliability, DPDT, Low Level to 1.0 Ampere, Internal MOSFET Drive With Zener Diode Gate Protection, (Electromechanical Output), Diode Coil Suppression and Terminals With 0.100 Grid Lead Spacing.
MIL-PRF-28776/7	-	Relays, Hybrid, Established Reliability, DPDT, Low Level to 1.0 Ampere (Sensitive Coil Operate at 25°C), Internal MOSFET Driver With Zener Diode Gate Protection (Electromechanical Output), Diode Coil Suppression and Terminals With 0.100 Grid Lead Spacing.

Preparing activity:
DLA-CC

(Project 5945-1201)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:08Z
Check the source to verify that this is the current version before use.