INCH-POUND

MIL-PRF-28776H
SUPPLEMENT 1
20 September 2017

PERFORMANCE SPECIFICATION

RELAYS, HYBRID, ESTABLISHED RELIABILITY,
GENERAL SPECIFICATION FOR

This supplement forms a part of MIL-PRF-28776H, dated 20 September 2017.

SPECIFICATION SHEETS

MIL-PRF-28776/1	-	Relays, Hybrid, Established Reliability, DPDT, Low Level to 1.0 Ampere (Transistor Driven) (Electromechanical Output)
MIL-PRF-28776/3	-	Relays, Hybrid, Established Reliability, DPDT, Low-Level to 1.0 Ampere (Sensitive Coil Operate Power at 25 Degrees C) (Transistor Driven) (Electromechanical Output) with Diode Coil Suppression
MIL-PRF-28776/4	-	Relays, Hybrid, Established Reliability, SPDT, Low Level to 1.0 Ampere (Sensitive Coil Operate Power at 25º C) (Transistor Driven) (Electromechanical Output) With Diode Coil Suppression
MIL-PRF-28776/5	-	Relays, Hybrid, Established Reliability, SPDT, Low-Level to 1.0 Ampere (Transistor Driven) (Electromechanical Output) With Diode Coil Suppression
MIL-PRF-28776/6	-	Relays, Hybrid, Established Reliability, DPDT, Low Level to 1.0 Ampere Internal MOSFET Drive With Zener Diode Gate Protection (Electromechanical Output) Diode Coil Suppression and Terminals With 0.100 Grid Lead Spacing
MIL-PRF-28776/7	-	Relays, Hybrid, Established Reliability, DPDT, Low Level to 1.0 Ampere (Sensitive Coil Operate Power at 25ºC), Terminal MOSFET Driver With Zener Diode Gate Protection (Electromechanical Output), Diode Coil Suppression and Terminals With 0.100 Grid Lead Spacing

Custodians:
Army - CR
Navy - EC
Air Force – 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5945-2017-043)

Review activities:
Army - CR4, MI
Navy - AS, MC, OS
Air Force – 19

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/.

AMSC N/A

FSC 5945

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:07Z
Check the source to verify that this is the current version before use.