MILITARY SPECIFICATION

POLES, STRUCTURAL WOODEN, FOR HIGH FREQUENCY (HF) ANTENNAS

This amendment forms a part of Military Specification MIL-P-28766(EC), 26 February 1971.

Page 2

2.2: Delete ASTM specification "A36 - Specification for Structural Steel".

3.2.2.1, line 2: Delete "pitch" and substitute "pith".

Page 3

3.3.1: Delete first sentence and substitute "Only when specifically allowed by the detailed antenna specification or the procurement document, may poles be spliced (see 6.2)."

3.4: Delete first sentence and substitute "When the detailed antenna specification allows non-embedded pole bases, pole anchorage design shall avoid the use of through bolts (see 6.2)."

Page 5

4.3.1.4: Delete "(ASTM A36)."

5.1.1: Delete "Not applicable" and substitute "Each pole shall be banded at each end with at least three 12 gage steel sheet metal strips 1-inch wide. The strips shall be spaced at 6-inch intervals, starting at the ends of the pole, and shall be tightly banded to the pole and securely nailed in position.

Page 6

6.2: Add "(g) Permission to splice poles, if desired (see 3.3.1)" and "(h) Permission for non-embedment of pole bases, if desired (see 3.4)."

6.4.1: Delete "6.1" and substitute "6.4.1."

Preparing activity
Navy - EC
(Project 5510-N139)

FSC 5510

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:01Z
Check the source to verify that this is the current version before use.