[INCH-POUND]
A-A-3032
October 3, 1996
SUPERSEDING
GGG-P-00151B (GSA-FSS)
February 1, 1971 and
GGG-P-151A
October 13, 1953

COMMERCIAL ITEM DESCRIPTION

PEAVY

The General Services Administration has authorized the use of this Commercial Item Description for procurement of Type I, peavy specified in GGG-P-00151 for all federal agencies.

1. SCOPE.

1.1 Scope. This commercial item description covers a peavy.

1.1.1 Intended use. This peavy is used for rolling, by clasping the hook around the log and for pushing and guiding the logs.

2. CLASSIFICATION.

2.1 Classification. Not applicable.

3. SALIENT CHARACTERISTICS.

3.1 Design. The peavy shall consist of a socket, hook, hook bolt, pike, and handle. The construction and dimensions shall be similar to Figure 1. All parts shall be easily accessible for replacement.

3.1.1 Illustration. Except for the technical requirements (e.g., design, dimensions), the illustration herein is descriptive and is not intended to preclude the purchase of items otherwise conforming to the requirements of this document.




Figure 1. Peavy.

Beneficial comments, recommendations, additions, deletions, clarifications, etc., and any other data which may improve this document should be sent to: General Services Administration, Federal Supply Service, Tools and Appliances Commodity Center, Kansas City, MO 64131.

Distribution Statement A. Approved for public release; distribution is unlimited. FSC 5120

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.

3.1.2 Socket. The peavy socket shall be made of steel or a malleable iron casting at the manufacturer's option.

3.1.3 Hook. The hook shall be forged from steel bar. The hook size shall be 1 by 1/2 inch with a minimum of 10 inches, maximum of 11 inches hook opening. Tolerance on hook width and thickness shall be ± 1/16 inch. The measurement for the hook opening shall be taken from the center of the swivel bolt to the tip of the hook.

3.1.4 Hook bolt. The hook bolt shall be of the steel-carriage type, size thread 7/16-14UNC, with a minimum length of 1-1/2 inches, complete with nylon insert lock nut. At assembly, the hook shall be securely attached to the socket by the bolt in such a manner that the hook will swing freely.

3.1.5 Pike. The pike shall be forged from steel bar, SAE 1070 minimum. The pike shaft shall be firmly imbedded in the handle before the handle is shaped to fit the socket. The point shall have a radius of approximately 1/2 inch.

3.1.6 Handle. The handle shall be made from hard maple or hickory with an overall length of 54 inches ± 1 inch measured from the toe ring. The handle diameter shall be 2-1/2 inches ± 1/8 inch at the clasp tapering towards the extension toe ring. The handle shall be totally dipped in clear laquer or wood preserative before assembly. The toe ring end and the toe ring of the handle, including the length of the clasp, shall be treated with a good grade of paint.

3.2 Finish. All metal parts shall have a protective coating of black oxide, or painted at the manufacturer's option.

3.3 Identification marking. The peavy shall be marked with the manufacturer's name or identifying symbol and the state or country of manufacture, unless otherwise specified. All identification markings shall be engraved, etched, molded, or indented directly on the item's surface in such a manner that it remains clearly legible throughout the life of the item.

3.4 Workmanship. Details of workmanship shall be in accordance with the best commercial practice. Paints, coatings, and finishes shall be smooth, adherent, continuous, and not stained or discolored. External surfaces shall be free of tool and gouge marks, nicks, or other surface imperfections. The item shall be free from manufacturing workmanship defects (e.g., sharp or rough external edges, corners, or surfaces) and material workmanship defects (e.g., pits, rips, fins, burrs, tears, nodules, cracks, blisters) which may adversely impact the item's serviceability, durability, safety, or appearance.

4. REGULATORY REQUIREMENTS.

4.1 Recovered materials. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

4.2 Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within the tolerances specified (using conversion tables contained in the latest revision of Federal Standard 376) and all other requirements of this document are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the contracting officer to determine if the product is acceptable.

5. QUALITY ASSURANCE PROVISIONS.

5.1 Product conformance. The product provided to the Government shall conform to the contractually specified requirements. For product characteristics and requirements which are not contractually specified, the provided product shall conform to the producer's own drawings, standards, specifications, and quality assurance practices for the highest quality product commercially offered by the producer. If the product is not commercially offered by the producer, the best commercial practices shall apply. The Government reserves the right to require proof of such conformances prior to first delivery and thereafter as provided for under the provisions of the contract.

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:28Z
Check the source to verify that this is the currentversion before use.

5.2 Responsibility for inspection. Unless otherwise specified, the contractor is responsible for the performance of all inspection requirements and may use any commercial facilities (including the contractor's own facilities) suitable for performance of the inspection requirements, unless disapproved by the Government. The Government reserves the right to perform any inspections deemed necessary to assure the item conforms to the specified requirements.

5.3 Bid sample(s). When a bid sample requirement is specified in the solicitation, the bid sample(s) shall be inspected for all salient characteristics by the Government. A failure of any bid sample to meet the salient characteristics shall be cause for rejection.

5.4 First article sample(s). When a first article requirement is specified in the contract, the first article sample(s) shall be inspected for all salient characteristics. A failure of any first article sample to meet the salient characteristics shall be cause for rejection.

6. PACKAGING.

6.1 Packaging. Requirements of preservation, packing, packaging, and marking of packages shall be as specified in the contract or order.

7. NOTES.

(This section contains information of a general or explanatory nature that is not mandatory.)

7.1 Addresses for obtaining copies of referenced documents:

Federal Specifications and Standards: Federal Supply Service Bureau, Specification Section, Suite 8100, 470 L'Enfant Plaza, SW, Washington, DC 20407.

Federal Acquisition Regulations (FAR): Government Printing Office, Superintendent of Documents, Washington, DC 20402-9371.

ANSI/ASQC Z1.4: American Society for Quality Control, P.O. Box 3005, 611 East Wisconsin Avenue, Milwaukee, WI 43201-4606.

7.2 Ordering data. Purchasers should select the preferred options permitted herein and should include the following information in procurement documents:

(a) Title, number, and date of this Commercial Item Description.
(b) When applicable, the appropriate NSN(s).
(c) If bid samples are required, the number of samples required, and the subjective inspection requirements.
(d) If first article samples are required and the number of samples required.
(e) If lot sampling inspection is required and the applicable lot sampling requirements. For example:

Sampling for inspection. Sampling for inspection (both examinations and testing) shall be in accordance with ANSI/ASQC Z1.4.

Inspection. Each sample tool shall be examined and tested for all salient characteristics. The Inspection Level shall be S-2 with an Acceptable Quality Level of 4.0, expressed in terms of defects per hundred units.

(f) What preservation, packing, packaging, and marking of packages are required.

7.3 National Stock Numbers (NSNs). The following list of NSNs corresponds to the peavy specified in this CID. This list may not be indicative of all possible NSNs associated with this CID.

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:28Z
Check the source to verify that this is the currentversion before use.

NSN	SIZE
5120-00-223-8996	10-1/2 inch opening

MILITARY INTERESTS:

NONE: DoD has no registered interest in revisions or notices to this Commercial Item Description until further notice.

PREPARING ACTIVITY:

GSA - FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.