INCH-POUND

MIL-PRF-87217/1A
25 May 1999
SUPERSEDING
MIL-C-87217/1
11 March 1985

PERFORMANCE SPECIFICATION SHEET

CAPACITORS, FIXED, SUPERMETALLIZED PLASTIC FILM DIELECTRIC, DIRECT CURRENT FOR LOW ENERGY, HIGH IMPEDANCE APPLICATIONS, HERMETICALLY SEALED IN METAL CASES, HIGH RELIABILITY, STYLES CHS01, CHS02, AND CHS03

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the capacitors described herein shall consist of this specification and the latest issue of MIL-PRF-87217.



NOTES:
1. Dimensions are in inches.
2. Metric equivalents are in parentheses.
3. Number 22 AWG wire (.025 (0.64 mm) inches ±.002 (0.05 mm)) for case diameters of .312 (7.92 mm) and less.
   Number 20 AWG wire (.032 (0.81 mm) inches ±.002 (0.05 mm)) for case diameters of .400 (10.16 mm) and .500 (12.70 mm).
   Number 18 AWG wire (.040 (1.02 mm) inches ±.002 (0.05 mm)) for case diameters of .562 (14.27 mm) and over.
4. See table I for additional dimensions.
5. Insulating sleeve shall extend beyond the capacitor body. Insulating sleeve thickness shall not exceed .005 (0.13 mm).
6. Plastic insulating sleeve shall be transparent; marking shall be applied to the capacitor case.
7. Lead length may be a minimum of one inch for use in tape and reel packaging, when specified in the ordering data.

FIGURE 1. Capacitor configuration.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:20Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical characteristics, dimensions, and dash numbers.

CHS01 - 30 volts (dc rating)									
Capacitance value (nom) (in μF)	Dimensions 1/ (in inches with mm in parentheses)			Dash number 2/					
	L ±.030(.76)	D +.020(.51) -.010(.25)	G (max)	Capacitance tolerance value (in %)					
				±0.25	±0.5	±1.0	±2.0	±5.0	±10.0
0.001	0.500 (12.70)	0.170 (4.32)	0.700 (17.78)	1001-	1002-	1003-	1004-	1005-	1006-
0.0012	0.500 (12.70)	0.170 (4.32)	0.700 (17.78)	1007-	1008-	1009-	1010-	1011-	1012-
0.0015	0.500 (12.70)	0.170 (4.32)	0.700 (17.78)	1013-	1014-	1015-	1016-	1017-	1018-
0.0018	0.500 (12.70)	0.170 (4.32)	0.700 (17.78)	1019-	1020-	1021-	1022-	1023-	1024-
0.002	0.500 (12.70)	0.170 (4.32)	0.700 (17.78)	1025-	1026-	1027-	1028-	1029-	1030-
0.0022	0.500 (12.70)	0.170 (4.32)	0.700 (17.78)	1031-	1032-	1033-	1034-	1035-	1036-
0.0027	0.500 (12.70)	0.170 (4.32)	0.700 (17.78)	1037-	1038-	1039-	1040-	1041-	1042-
0.0033	0.500 (12.70)	0.170 (4.32)	0.700 (17.78)	1043-	1044-	1045-	1046-	1047-	1048-
0.0039	0.500 (12.70)	0.170 (4.32)	0.700 (17.78)	1049-	1050-	1051-	1052-	1053-	1054-
0.0047	0.500 (12.70)	0.170 (4.32)	0.700 (17.78)	1055-	1056-	1057-	1058-	1059-	1060-
0.005	0.500 (12.70)	0.170 (4.32)	0.700 (17.78)	1061-	1062-	1063-	1064-	1065-	1066-
0.0056	0.500 (12.70)	0.170 (4.32)	0.700 (17.78)	1067-	1068-	1069-	1070-	1071-	1072-
0.0068	0.500 (12.70)	0.170 (4.32)	0.700 (17.78)	1073-	1074-	1075-	1076-	1077-	1078-
0.0082	0.500 (12.70)	0.170 (4.32)	0.700 (17.78)	1079-	1080-	1081-	1082-	1083-	1084-
0.01	0.500 (12.70)	0.170 (4.32)	0.700 (17.78)	1085-	1086-	1087-	1088-	1089-	1090-
0.012	0.500 (12.70)	0.170 (4.32)	0.700 (17.78)	1091-	1092-	1093-	1094-	1095-	1096-
0.015	0.500 (12.70)	0.170 (4.32)	0.700 (17.78)	1097-	1098-	1099-	1100-	1101-	1102-
0.018	0.500 (12.70)	0.170 (4.32)	0.700 (17.78)	1103-	1104-	1105-	1106-	1107-	1108-
0.02	0.500 (12.70)	0.170 (4.32)	0.700 (17.78)	1109-	1110-	1111-	1112-	1113-	1114-
0.022	0.500 (12.70)	0.170 (4.32)	0.700 (17.78)	1115-	1116-	1117-	1118-	1119-	1120-
0.027	0.562 (14.27)	0.170 (4.32)	0.762 (19.35)	1121-	1122-	1123-	1124-	1125-	1126-
0.033	0.562 (14.27)	0.170 (4.32)	0.762 (19.35)	1127-	1128-	1129-	1130-	1131-	1132-
0.039	0.562 (14.27)	0.170 (4.32)	0.762 (19.35)	1133-	1134-	1135-	1136-	1137-	1138-
0.047	0.562 (14.27)	0.170 (4.32)	0.762 (19.35)	1139-	1140-	1141-	1142-	1143-	1144-
0.05	0.562 (14.27)	0.170 (4.32)	0.762 (19.35)	1145-	1146-	1147-	1148-	1149-	1150-
0.056	0.562 (14.27)	0.170 (4.32)	0.762 (19.35)	1151-	1152-	1153-	1154-	1155-	1156-
0.068	0.687 (17.45)	0.170 (4.32)	0.887 (22.53)	1157-	1158-	1159-	1160-	1161-	1160-
0.082	0.687 (17.45)	0.170 (4.32)	0.887 (22.53)	1163-	1164-	1165-	1166-	1167-	1168-
0.1	0.687 (17.45)	0.193 (4.90)	0.887 (22.53)	1169-	1170-	1171-	1172-	1173-	1174-
0.12	0.687 (17.45)	0.193 (4.90)	0.887 (22.53)	1175-	1176-	1177-	1178-	1179-	1180-
0.15	0.562 (14.27)	0.235 (5.97)	0.762 (19.35)	1181-	1182-	1183-	1184-	1185-	1186-
0.18	0.687 (17.45)	0.235 (5.97)	0.887 (22.53)	1373-	1374-	1375-	1376-	1377-	1378-
0.20	0.687 (17.45)	0.235 (5.97)	0.887 (22.53)	1187-	1188-	1189-	1190-	1191-	1192-
0.22	0.687 (17.45)	0.235 (5.97)	0.887 (22.53)	1193-	1194-	1195-	1196-	1197-	1198-
0.27	0.687 (17.45)	0.235 (5.97)	0.887 (22.53)	1199-	1200-	1201-	1202-	1203-	1204-
0.33	0.687 (17.45)	0.235 (5.97)	0.887 (22.53)	1205-	1206-	1207-	1208-	1209-	1210-
0.39	0.687 (17.45)	0.235 (5.97)	0.887 (22.53)	1211-	1212-	1213-	1214-	1215-	1216-
0.47	0.687 (17.45)	0.312 (7.92)	0.887 (22.53)	1217-	1218-	1219-	1220-	1221-	1222-
0.50	0.687 (17.45)	0.312 (7.92)	0.887 (22.53)	1223-	1224-	1225-	1226-	1227-	1228-
0.56	0.687 (17.45)	0.312 (7.92)	0.887 (22.53)	1229-	1230-	1231-	1232-	1233-	1234-
0.68	0.687 (17.45)	0.312 (7.92)	0.887 (22.53)	1235-	1236-	1237-	1238-	1239-	1240-
0.82	0.813 (20.65)	0.312 (7.92)	1.013 (25.73)	1241-	1242-	1243-	1244-	1245-	1246-
1.0	0.813 (20.65)	0.312 (7.92)	1.013 (25.73)	1247-	1248-	1249-	1250-	1251-	1252-
1.2	0.813 (20.65)	0.312 (7.92)	1.013 (25.73)	1253-	1254-	1255-	1256-	1257-	1258-
1.5	0.813 (20.65)	0.400 (10.16)	1.013 (25.73)	1259-	1260-	1261-	1262-	1263-	1264-
1.8	0.813 (20.65)	0.400 (10.16)	1.013 (25.73)	1265-	1266-	1267-	1268-	1269-	1270-
2.0	0.813 (20.65)	0.400 (10.16)	1.013 (25.73)	1271-	1272-	1273-	1274-	1275-	1276-
2.2	0.813 (20.65)	0.400 (10.16)	1.013 (25.73)	1277-	1278-	1279-	1280-	1281-	1282-
2.7	1.063 (27.00)	0.400 (10.16)	1.263 (32.08)	1385-	1386-	1387-	1388-	1389-	1390-
3.0	1.063 (27.00)	0.400 (10.16)	1.263 (32.08)	1289-	1290-	1291-	1292-	1293-	1294-
3.3	1.063 (27.00)	0.400 (10.16)	1.263 (32.08)	1295-	1296-	1297-	1298-	1299-	1300-

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:20Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical characteristics, dimensions, and dash numbers - Continued.

Capacitance value (nom) (in μF)	Dimensions 1/ (in inches with mm in parentheses) L ±.030(.76)	D +.020(.51) -.010(.25)	G (max)	Dash number 2/ Capacitance tolerance value (in %) ±0.25	±0.5	±1.0	±2.0	±5.0	±10.0
CHS01 - 30 volts (dc rating)									
3.9	1.375 (34.93)	0.400 (10.16)	1.575 (40.01)	1301-	1302-	1303-	1304-	1305-	1306-
4.7	1.375 (34.93)	0.500 (12.70)	1.575 (40.01)	1313-	1314-	1315-	1316-	1317-	1318-
5.0	1.375 (34.93)	0.500 (12.70)	1.575 (40.01)	1319-	1320-	1321-	1322-	1323-	1324-
5.6	1.375 (34.93)	0.500 (12.70)	1.575 (40.01)	1325-	1326-	1327-	1328-	1329-	1330-
6.8	1.375 (34.93)	0.562 (14.27)	1.575 (40.01)	1331-	1332-	1333-	1334-	1335-	1336-
8.0	1.375 (34.93)	0.562 (14.27)	1.575 (40.01)	1337-	1338-	1339-	1340-	1341-	1342-
8.2	1.375 (34.93)	0.562 (14.27)	1.575 (40.01)	1343-	1344-	1345-	1346-	1347-	1348-
10.0	1.375 (34.93)	0.562 (14.27)	1.575 (40.01)	1349-	1350-	1351-	1352-	1353-	1354-
CHS02 - 50 volts (dc rating)									
0.001	0.500 (12.70)	0.170 (4.32)	0.700 (17.78)	2001-	2002-	2003-	2004-	2005-	2006-
0.0012	0.500 (12.70)	0.170 (4.32)	0.700 (17.78)	2007-	2008-	2009-	2010-	2011-	2012-
0.0015	0.500 (12.70)	0.170 (4.32)	0.700 (17.78)	2013-	2014-	2015-	2016-	2017-	2018-
0.0018	0.500 (12.70)	0.170 (4.32)	0.700 (17.78)	2019-	2020-	2021-	2022-	2023-	2024-
0.002	0.500 (12.70)	0.170 (4.32)	0.700 (17.78)	2025-	2026-	2027-	2028-	2029-	2030-
0.0022	0.500 (12.70)	0.170 (4.32)	0.700 (17.78)	2031-	2032-	2033-	2034-	2035-	2036-
0.0027	0.500 (12.70)	0.170 (4.32)	0.700 (17.78)	2037-	2038-	2039-	2040-	2041-	2042-
0.0033	0.500 (12.70)	0.170 (4.32)	0.700 (17.78)	2043-	2044-	2045-	2046-	2047-	2048-
0.0039	0.500 (12.70)	0.170 (4.32)	0.700 (17.78)	2049-	2050-	2051-	2052-	2053-	2054-
0.0047	0.500 (12.70)	0.170 (4.32)	0.700 (17.78)	2055-	2056-	2057-	2058-	2059-	2060-
0.005	0.500 (12.70)	0.170 (4.32)	0.700 (17.78)	2061-	2062-	2063-	2064-	2065-	2066-
0.0056	0.500 (12.70)	0.170 (4.32)	0.700 (17.78)	2067-	2068-	2069-	2070-	2071-	2072-
0.0068	0.500 (12.70)	0.170 (4.32)	0.700 (17.78)	2073-	2074-	2075-	2076-	2077-	2078-
0.0082	0.562 (14.27)	0.170 (4.32)	0.762 (19.35)	2079-	2080-	2081-	2082-	2083-	2084-
0.01	0.562 (14.27)	0.170 (4.32)	0.762 (19.35)	2085-	2086-	2087-	2088-	2089-	2090-
0.012	0.562 (14.27)	0.170 (4.32)	0.762 (19.35)	2091-	2092-	2093-	2094-	2095-	2096-
0.015	0.562 (14.27)	0.170 (4.32)	0.762 (19.35)	2097-	2098-	2099-	2100-	2101-	2102-
0.018	0.562 (14.27)	0.193 (4.90)	0.762 (19.35)	2103-	2104-	2105-	2106-	2107-	2108-
0.02	0.562 (14.27)	0.193 (4.90)	0.762 (19.35)	2109-	2110-	2111-	2112-	2113-	2114-
0.022	0.562 (14.27)	0.193 (4.90)	0.762 (19.35)	2115-	2116-	2117-	2118-	2119-	2120-
0.027	0.562 (14.27)	0.193 (4.90)	0.762 (19.35)	2121-	2122-	2123-	2124-	2125-	2126-
0.033	0.562 (14.27)	0.193 (4.90)	0.762 (19.35)	2127-	2128-	2129-	2130-	2131-	2132-
0.039	0.687 (17.45)	0.170 (4.32)	0.887 (22.53)	2133-	2134-	2135-	2136-	2137-	2138-
0.047	0.687 (17.45)	0.170 (4.32)	0.887 (22.53)	2139-	2140-	2141-	2142-	2143-	2144-
0.05	0.687 (17.45)	0.170 (4.32)	0.887 (22.53)	2145-	2146-	2147-	2148-	2149-	2150-
0.056	0.687 (17.45)	0.193 (4.90)	0.887 (22.53)	2151-	2152-	2153-	2154-	2155-	2156-
0.068	0.687 (17.45)	0.193 (4.90)	0.887 (22.53)	2157-	2158-	2159-	2160-	2161-	2160-
0.082	0.813 (20.65)	0.193 (4.90)	1.013 (25.73)	2163-	2164-	2165-	2166-	2167-	2168-
0.1	0.813 (20.65)	0.193 (4.90)	1.013 (25.73)	2169-	2170-	2171-	2172-	2173-	2174-
0.12	0.687 (17.45)	0.235 (5.97)	0.887 (22.53)	2175-	2176-	2177-	2178-	2179-	2180-
0.15	0.687 (17.45)	0.235 (5.97)	0.887 (22.53)	2181-	2182-	2183-	2184-	2185-	2186-
0.18	0.813 (20.65)	0.235 (5.97)	1.013 (25.73)	2187-	2188-	2189-	2190-	2191-	2192-
0.20	0.813 (20.65)	0.235 (5.97)	1.013 (25.73)	2193-	2194-	2195-	2196-	2197-	2198-
0.22	0.813 (20.65)	0.235 (5.97)	1.013 (25.73)	2199-	2200-	2201-	2202-	2203-	2204-
0.27	0.687 (17.45)	0.312 (7.92)	0.887 (22.53)	2205-	2206-	2207-	2208-	2209-	2210-
0.33	0.687 (17.45)	0.312 (7.92)	0.887 (22.53)	2211-	2212-	2213-	2214-	2215-	2216-
0.39	0.813 (20.65)	0.312 (7.92)	1.013 (25.73)	2217-	2218-	2219-	2220-	2221-	2222-
0.47	0.813 (20.65)	0.312 (7.92)	1.013 (25.73)	2223-	2224-	2225-	2226-	2227-	2228-
0.50	0.813 (20.65)	0.312 (7.92)	1.013 (25.73)	2229-	2230-	2231-	2232-	2233-	2234-
0.56	0.813 (20.65)	0.400 (10.16)	1.013 (25.73)	2235-	2236-	2237-	2238-	2239-	2240-
0.68	0.813 (20.65)	0.400 (10.16)	1.013 (25.73)	2241-	2242-	2243-	2244-	2245-	2246-
0.82	1.063 (27.00)	0.400 (10.16)	1.263 (32.08)	2247-	2248-	2249-	2250-	2251-	2252-

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:20Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical characteristics, dimensions, and dash numbers - Continued.

Capacitance value (nom) (in μF)	Dimensions 1/ (in inches with mm in parentheses)			Dash number 2/					
		D	G	Capacitance tolerance value (in %)					
	L ±.030(.76)	+.020(.51) -.010(.25)	(max)	±0.25	±0.5	±1.0	±2.0	±5.0	±10.0
1.0	1.063 (27.00)	0.400 (10.16)	1.263 (32.08)	2253-	2254-	2255-	2256-	2257-	2258-
1.2	1.063 (27.00)	0.400 (10.16)	1.263 (32.08)	2259-	2260-	2261-	2262-	2263-	2264-
1.5	1.063 (27.00)	0.400 (10.16)	1.263 (32.08)	2265-	2266-	2267-	2268-	2269-	2270-
1.8	1.063 (27.00)	0.400 (10.16)	1.263 (32.08)	2271-	2272-	2273-	2274-	2275-	2276-
2.0	1.125 (28.58)	0.500 (12.70)	1.325 (33.66)	2277-	2278-	2279-	2280-	2281-	2282-
2.2	1.125 (28.58)	0.500 (12.70)	1.325 (33.66)	2283-	2284-	2285-	2286-	2287-	2288-
2.7	1.375 (34.93)	0.500 (12.70)	1.575 (40.01)	2289-	2290-	2291-	2292-	2293-	2294-
3.0	1.375 (34.93)	0.500 (12.70)	1.575 (40.01)	2295-	2296-	2297-	2298-	2299-	2300-
3.3	1.375 (34.93)	0.500 (12.70)	1.575 (40.01)	2301-	2302-	2303-	2304-	2305-	2306-
3.9	1.375 (34.93)	0.562 (14.27)	1.575 (40.01)	2307-	2308-	2309-	2310-	2311-	2312-
4.7	1.375 (34.93)	0.670 (17.02)	1.575 (40.01)	2319-	2320-	2321-	2322-	2323-	2324-
5.0	1.375 (34.93)	0.670 (17.02)	1.575 (40.01)	2325-	2326-	2327-	2328-	2329-	2330-
5.6	1.375 (34.93)	0.670 (17.02)	1.575 (40.01)	2331-	2332-	2333-	2334-	2335-	2336-
6.8	1.875 (47.63)	0.670 (17.02)	2.075 (52.71)	2337-	2338-	2339-	2340-	2341-	2342-
8.0	1.875 (47.63)	0.670 (17.02)	2.075 (52.71)	2343-	2344-	2345-	2346-	2347-	2348-
8.2	1.875 (47.63)	0.670 (17.02)	2.075 (52.71)	2349-	2350-	2351-	2352-	2353-	2354-
10.0	1.875 (47.63)	0.670 (17.02)	2.075 (52.71)	2355-	2356-	2357-	2358-	2359-	2360-
CHS03 - 100 volts (dc rating)									
0.001	0.500 (12.70)	0.170 (4.32)	0.700 (17.78)	3001-	3002-	3003-	3004-	3005-	3006-
0.0012	0.500 (12.70)	0.170 (4.32)	0.700 (17.78)	3007-	3008-	3009-	3010-	3011-	3012-
0.0015	0.500 (12.70)	0.170 (4.32)	0.700 (17.78)	3013-	3014-	3015-	3016-	3017-	3018-
0.0018	0.500 (12.70)	0.170 (4.32)	0.700 (17.78)	3019-	3020-	3021-	3022-	3023-	3024-
0.002	0.500 (12.70)	0.170 (4.32)	0.700 (17.78)	3025-	3026-	3027-	3028-	3029-	3030-
0.0022	0.500 (12.70)	0.170 (4.32)	0.700 (17.78)	3031-	3032-	3033-	3034-	3035-	3036-
0.0027	0.500 (12.70)	0.170 (4.32)	0.700 (17.78)	3037-	3038-	3039-	3040-	3041-	3042-
0.0033	0.500 (12.70)	0.170 (4.32)	0.700 (17.78)	3043-	3044-	3045-	3046-	3047-	3048-
0.0039	0.500 (12.70)	0.170 (4.32)	0.700 (17.78)	3049-	3050-	3051-	3052-	3053-	3054-
0.0047	0.500 (12.70)	0.170 (4.32)	0.700 (17.78)	3055-	3056-	3057-	3058-	3059-	3060-
0.005	0.500 (12.70)	0.170 (4.32)	0.700 (17.78)	3061-	3062-	3063-	3064-	3065-	3066-
0.0056	0.500 (12.70)	0.170 (4.32)	0.700 (17.78)	3067-	3068-	3069-	3070-	3071-	3072-
0.0068	0.562 (14.27)	0.170 (4.32)	0.762 (19.35)	3073-	3074-	3075-	3076-	3077-	3078-
0.0082	0.562 (14.27)	0.170 (4.32)	0.762 (19.35)	2079-	3080-	3081-	3082-	3083-	3084-
0.01	0.687 (17.45)	0.170 (4.32)	0.887 (22.53)	3085-	3086-	3087-	3088-	3089-	3090-
0.012	0.687 (17.45)	0.170 (4.32)	0.887 (22.53)	3091-	3092-	3093-	3094-	3095-	3096-
0.015	0.687 (17.45)	0.170 (4.32)	0.887 (22.53)	3097-	3098-	3099-	3100-	3101-	3102-
0.018	0.687 (17.45)	0.193 (4.90)	0.887 (22.53)	3103-	3104-	3105-	3106-	3107-	3108-
0.02	0.687 (17.45)	0.193 (4.90)	0.887 (22.53)	3109-	3110-	3111-	3112-	3113-	3114-
0.022	0.687 (17.45)	0.193 (4.90)	0.887 (22.53)	3115-	3116-	3117-	3118-	3119-	3120-
0.027	0.687 (17.45)	0.193 (4.90)	0.887 (22.53)	3121-	3122-	3123-	3124-	3125-	3126-
0.033	0.687 (17.45)	0.193 (4.90)	0.887 (22.53)	3127-	3128-	3129-	3130-	3131-	3132-
0.039	0.687 (17.45)	0.235 (5.97)	0.887 (22.53)	3133-	3134-	3135-	3136-	3137-	3138-
0.047	0.687 (17.45)	0.235 (5.97)	0.887 (22.53)	3139-	3140-	3141-	3142-	3143-	3144-
0.05	0.687 (17.45)	0.235 (5.97)	0.887 (22.53)	3145-	3146-	3147-	3148-	3149-	3150-
0.056	0.687 (17.45)	0.235 (5.97)	0.887 (22.53)	3151-	3152-	3153-	3154-	3155-	3156-
0.068	0.813 (20.65)	0.235 (5.97)	1.013 (25.73)	3157-	3158-	3159-	3160-	3161-	3160-
0.082	0.687 (17.45)	0.312 (7.92)	0.887 (22.53)	3163-	3164-	3165-	3166-	3167-	3168-
0.1	0.687 (17.45)	0.312 (7.92)	0.887 (22.53)	3169-	3170-	3171-	3172-	3173-	3174-
0.12	0.687 (17.45)	0.312 (7.92)	0.887 (22.53)	3175-	3176-	3177-	3178-	3179-	3180-
0.15	0.813 (20.65)	0.312 (7.92)	1.013 (25.73)	3181-	3182-	3183-	3184-	3185-	3186-

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:20Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical characteristics, dimensions, and dash numbers - Continued.

CHS03 - 100 volts (dc rating)										
Capacitance value (nom) (in μF)	Dimensions 1/ (in inches with mm in parentheses)			Dash number 2/					
		D	G	Capacitance tolerance value (in %)					
	L ±.030(.76)	+.020(.51) -.010(.25)	(max)	±0.25	±0.5	±1.0	±2.0	±5.0	±10.0
0.18	0.813 (20.65)	0.312 (7.92)	1.013 (25.73)	3187-	3188-	3189-	3190-	3191-	3192-
0.20	0.813 (20.65)	0.312 (7.92)	1.013 (25.73)	3193-	3194-	3195-	3196-	3197-	3198-
0.22	0.813 (20.65)	0.312 (7.92)	1.013 (25.73)	3199-	3200-	3201-	3202-	3203-	3204-
0.27	1.063 (27.00)	0.312 (7.92)	1.263 (32.08)	3205-	3206-	3207-	3208-	3209-	3210-
0.33	1.063 (27.00)	0.312 (7.92)	1.263 (32.08)	3211-	3212-	3213-	3214-	3215-	3216-
0.39	1.063 (27.00)	0.400 (10.16)	1.263 (32.08)	3217-	3218-	3219-	3220-	3221-	3222-
0.47	1.063 (27.00)	0.400 (10.16)	1.263 (32.08)	3223-	3224-	3225-	3226-	3227-	3228-
0.50	1.063 (27.00)	0.400 (10.16)	1.263 (32.08)	3229-	3230-	3231-	3232-	3233-	3234-
0.56	1.063 (27.00)	0.400 (10.16)	1.263 (32.08)	3235-	3236-	3237-	3238-	3239-	3240-
0.68	1.125 (28.58)	0.500 (12.70)	1.325 (33.66)	3241-	3242-	3243-	3244-	3245-	3246-
0.82	1.125 (28.58)	0.500 (12.70)	1.325 (33.66)	3247-	3248-	3249-	3250-	3251-	3252-
1.0	1.125 (28.58)	0.562 (14.27)	1.325 (33.66)	3253-	3254-	3255-	3256-	3257-	3258-
1.2	1.125 (28.58)	0.562 (14.27)	1.325 (33.66)	3259-	3260-	3261-	3262-	3263-	3264-
1.5	1.375 (34.93)	0.562 (14.27)	1.575 (40.01)	3265-	3266-	3267-	3268-	3269-	3270-
2.0	1.375 (34.93)	0.670 (17.02)	1.575 (40.01)	3271-	3272-	3273-	3274-	3275-	3276-
2.2	1.375 (34.93)	0.670 (17.02)	1.575 (40.01)	3277-	3278-	3279-	3280-	3281-	3282-
2.7	1.875 (47.63)	0.670 (17.02)	2.075 (52.71)	3283-	3284-	3285-	3286-	3287-	3288-
3.0	1.875 (47.63)	0.670 (17.02)	2.075 (52.71)	3289-	3290-	3291-	3292-	3293-	3294-
3.3	1.875 (47.63)	0.670 (17.02)	2.075 (52.71)	3295-	3296-	3297-	3298-	3299-	3300-
3.9	1.875 (47.63)	0.750 (19.05)	2.075 (52.71)	3301-	3302-	3303-	3304-	3305-	3306-
4.7	1.875 (47.63)	0.750 (19.05)	2.075 (52.71)	3313-	3314-	3315-	3316-	3317-	3318-
5.0	1.875 (47.63)	0.750 (19.05)	2.075 (52.71)	3319-	3320-	3321-	3322-	3323-	3324-
5.6	1.875 (47.63)	0.750 (19.05)	2.075 (52.71)	3325-	3326-	3327-	3328-	3329-	3330-
6.8	2.375 (60.53)	1.000 (25.40)	2.575 (65.41)	3331-	3332-	3333-	3334-	3335-	3336-
8.0	2.375 (60.53)	1.000 (25.40)	2.575 (65.41)	3337-	3338-	3339-	3340-	3341-	3342-
8.2	2.375 (60.53)	1.000 (25.40)	2.575 (65.41)	3343-	3344-	3345-	3346-	3347-	3348-
10.0	2.375 (60.53)	1.000 (25.40)	2.575 (65.41)	3349-	3350-	3351-	3352-	3353-	3354-

1/ L and D are bare case dimensions (see figure 1).
2/ Single letter A = sleeved or B = unsleeved.

REQUIREMENTS:

Parts supplied to this specification shall be qualified to “S” failure rate level and shall have passed subgroup 1, subgroup 2, and subgroup 4 in group A inspection of MIL-PRF-83421. All parts shall be permanently serialized on the case prior to group A inspection of MIL-PRF-87217.

Design and construction:

Dimensions and configuration: See figure 1 and table I.

Case material: Nonmagnetic.

Capacitance (Cap.) value: See table I.

Cap. Tolerance: See table I.

Rated voltage: See tables I and II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:20Z
Check the source to verify that this is the current version before use.

TABLE II. DC ratings.

Styles	Volts, dc
CHS01	30
CHS02	50
CHS03	100

Operating temperature range: -55°C to +100°C.

Thermal shock: In accordance with MIL-PRF-87217 with the following exception:

20 cycles, -55°C to +100°C, nonenergized with a 5-minute maximum wait between chambers.

DC burn-in: In accordance with MIL-PRF-87217 with the following exception:

160 hours minimum at +100°C with 1.5 ±0.5 V dc and 1.0 through 10.0 megohms resistor in series with each capacitor.

Insulation resistance (IR): Method 302 of MIL-STD-202. The following details shall apply:

a. Test potential: Rated voltage

b. Points of measurement:

Terminal to terminal: Between terminals at the applicable specified temperatures, and at 25°C ±3°C.

c. Charge time 5 minutes maximum; however, for capacitance values greater than 1.0 µF, an additional 1 minute per µF is permitted.

d. See figure 2 for limits.

Capacitance: Method 305 of MIL-STD-202. The following details shall apply:

a. Test frequency: 1,000 ±100 hertz (Hz).

b. Limit of accuracy: ±0.05 percent.

Seal: Method 112 of MIL-STD-202, test condition C, procedure IIIa, followed by test condition A with the exception of the following:

1bf/in^2	Exposure time hours	Maximum dwell hours	R_1 Reject limit (atm cm^3/s)
45 ± 5	1 +1, -0	1	1 X10^{-6}

High impedance dc life: The capacitors shall be tested 250 hours at 100°C with 1.5 ±0.5 volts dc and 1 through 10 megohms resistor in series with each capacitor so that the energy from source or across the capacitor is 500 microjoules, maximum. The following details shall apply.

a. Insulation resistance - terminal to terminal: Shall meet the initial requirements.

b. Capacitance: Shall meet the initial requirements.

c. Dissipation factor: Shall meet the initial requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:20Z
Check the source to verify that this is the current version before use.



FIGURE 2. Insulation resistance vs. capacitance value.

PIN: Consists of the basic number of this specification sheet with a dash number coded as shown in the following:

M87217/01-
1 123 A

Single digit designating style (i.e., 1 - CHS01; 2 = CHS02; and 3 = CHS03).

Nonsignificant dash number from table I.

Single letter A = sleeved or B = unsleeved.

Packaging: Capacitors will be furnished in tape and reel packaging when so specified in the ordering data.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:20Z
Check the source to verify that this is the current version before use.

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Review activities:
Army - AR, MI
Navy - AS, CG, MC, OS, SH
Air Force - 19
NASA - NA

Preparing activity:
DLA - CC

(Project 5910-2015-01)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:20Z
Check the source to verify that this is the current version before use.