FED SUP CLASS

REVIEW ACTIVITY : DCSC, 69
USER ACTIVITY : YD, ATAC



THIS CORNER MUST BE SMOOTH AND SHARP. REMOVE FEATHER EDGE.

.125 DRILL - R
SPACED AS
£ #

Ⓓ CANCELED AFTER 21 APRIL 1982
NO SUPERSEDING STANDARD.



WT. OF FIN. PISTON:
504 ± 3 GRAMS.

Ⓒ ENTIRE STANDARD REVISED

P.A. ARMY MO(ERDL) Other Cust A.F. - 69 NAVY - YD	TITLE PISTON, INTERNAL COMBUSTION ENGINE: 3-7/16" X 3-1/2"	PART NO. MS 13957-1 MILITARY STANDARD MS 13957
PROCUREMENT SPECIFICATION MIL-E-11275	SUPERSEDES	SHEET 1 OF 6

DD FORM 672-1 (Continuation)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

This Military Standard has been approved by the Department of Defense and is mandatory for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

APPROVED 19 JUNE 1952 REVISED Ⓐ 27 NOVEMBER 1953 Ⓑ 24 OCTOBER 1955 Ⓒ 7 MAR 1966 Ⓓ 21 APRIL 1982

Source: https://assist.dla.mil -- Downloaded: 202610-23T13:31Z
Check the source to verify that this is the current version before use.