FED. SUP CLASS
6640

USER ACTIVITIES: ARMY - MD, DM
NAVY - MS

REVIEWER ACTIVITIES: ARMY - ME
NAVY - OS
AIR FORCE - 82



PART NUMBER	SIZE	DIMENSIONS (mm) LENGTH	MUFF CENTER TO DOVETAIL	WIDTH
MS36418-1	Long	88.9	50.8	25.4
MS36418-2	Short	63.5	25.4	25.4
MS36418-3	Dovetail Socket	25.4	----	Tapered

MATERIAL: Supports shall be cast iron with gray enamel finish, and thumb screw shall be nickel-plated brass. The socket shall be sheet steel, nickel plated.

DESIGN: The muff opening shall be large enough for rod up to 20.6 mm (13/16"). The dovetail shall fit snugly into the socket for vertical rod support.

NOTE: Items differing from this Military Standard by minor variations in design or dimensions are considered standard under this document, provided such variations do not affect performance and are not in conflict with the material requirements specified herein.

APPROVED 30 JUN 1983 REVISED

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

P.A. EA	INTERNATIONAL INTEREST	TITLE	MILITARY STANDARD
Other Cust MS 99		CLAMP, MUFF, DOVETAIL	MS36418
Procurement Specifications NONE	SUPERSEDES:		SHEET 1 OF 1

DD FORM 1 MAY 73 672 (COORDINATED) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE PROJECT NUMBER 6640-1181

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:40Z
Check the source to verify that this is the current version before use.