[INCH-POUND]
A-A-1384A
March 4, 1993
TO SUPERSEDE
A-A-1384
September 10, 1980

COMMERCIAL ITEM DESCRIPTION

HOLDER, DOOR

The General Services Administration has authorized the use of this commercial item description.

1. SCOPE

1.1 Scope. This commercial item description covers non-automatic type door holders.

1.2 Classification. The door holders shall be furnished in the following types and sizes:

Type I - Lever

Size 1 - 2 inch	(50.8 mm)
Size 2 - 3 inch	(76.2 mm)

Type II - Plunger

Size 1 - 7/8 inch	(22.2 mm)
Size 2 - 1-1/8 inch	(28.6 mm)

2. APPLICABLE DOCUMENTS

2.1 The documents referenced in this commercial item description shall be the issues in effect on the date of the invitation for bids or request for proposal unless otherwise specified. These documents form a part of this commercial item description to the extent specified. In the event of a conflict between this commercial item description and a document referenced herein, this commercial item description shall take precedence.

Beneficial comments, recommendations, additions, deletions, clarifications, etc., and any other data which may improve this document should be sent to: General Services Administration, Engineering Group (7FXEE), 819 Taylor Street, Fort Worth, TX 76102.

DISTRIBUTION STATEMENT A: Approved for public release. Distribution is unlimited

FSC 5340

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:13Z
Check the source to verify that this is the current version before use.

Federal Standard:

FED-STD-376 - Preferred Metric Units for General use by the Federal Government.

Copies of Federal specifications and standards are available from the General Services Administration Business Service Centers in Boston, MA; New York, NY; Philadelphia, PA; Washington, DC; Atlanta, GA; Chicago, IL; Kansas City, MO; Fort Worth, TX; Denver, CO; San Francisco, CA; Los Angeles, CA; and Seattle, WA.

Military Standard:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.

Copies of military standards may be obtained from the Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.

ASTM Standard:

E29 - Standard Practice For Using Significant Digits In Test Data To Determine Conformance With Specifications.

Application for copies of ASTM standards should be addressed to ASTM, 1916 Race Street, Philadelphia, PA 19103.

ANSI/BHMA Standards:

A156.16 - American National Standard for Auxiliary Hardware.
A156.18 - American National Standard for Materials and Finishes.

Application for copies of ANSI/BHMA standards should be addressed to the Building Hardware Manufacturers Association, Inc., 60 East 42nd Street, New York, NY 10065.

3. SALIENT CHARACTERISTICS

3.1 Design. Door holders shall be in accordance with ANSI/BHMA A156.16.

3.1.1 Type I. Shall be lever type with a securely held replaceable rubber tip which will no fold under or dislodge from lateral pressure. The holder shall be designed for attachment by surface screws and the lever shall be hinged to so that it swings up and remains in the vertical position when not in service.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:13Z
Check the source to verify that this is the current version before use.

3.1.2 Type II. Shall be plunger type with a securely held replacement rubber tip which will not fold under or dislodge from lateral pressure. The holder shall be designed for attachment by surface screws. The plunger type holder shall be designed so that the plunger is held firm when pushed down by foot and released by tripping a spring action trigger.

3.2 Sizes.

3.2.1 Type I. Size for type I holders designates the floor to door clearance. Size 1 shall be designed for 2-1/2 inch (63.5 mm) or less clearance. Size 2 shall be designed for 3-1/2 (88.9 mm) inch or less clearance.

3.2.2 Type II. Size for type II holders designates the floor to door clearance. Size 1 shall have a 7/8 inch (22.2 mm) throw. Size 2 shall have a 1-1/8 inch (28.6 mm) throw.

3.3 Material. The door holders shall be made of brass, bronze, cast iron, or aluminum, as specified (see 6.1).

3.4 Finish. Unless otherwise specified, significant surfaces of the hinge shall be finished in accordance with ANSI/BHMA A156.16 and A156.18, finish code as specified (see 6.1).

3.5 Grade. Door holders supplied under this commercial item description shall be grade 1, 2, or 3, as specified (see 6.1). Grade designates durability with grade 1 being the most durable (see ANSI/BHMA A156.16).

3.6 Product identification code. Door holders supplied under this commercial item description shall be identified by an identifying number in accordance with section 7 of ANSI/BHMA A156.16.

3.7 Workmanship. Door holders shall be free from sharp edges and shall be free of defects which may impair appearance or serviceability.

3.8 Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practicable.

3.9 Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within the tolerances specified using conversion tables contained in the latest revision of FED-STD-376, and all other requirements of this commercial item description are met.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:13Z
Check the source to verify that this is the current version before use.

3.10 Commercial item. The use of the term "commercial item description" in this document does not imply that any item or items offered are not required to conform with all requirements specified herein.

3.11 Measurement system. The values stated in inch-pound units are to be regarded as the standard. The metric values stated in parentheses are for information purposes only.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the use of the contractor's own or any other facilities suitable for the performance of the inspection requirements specified herein shall be permitted, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Sampling. The levels of inspection and acceptable quality levels (AQL's) shall be in accordance with MIL-STD-105.

4.3 Lot formation. All door holders of the same type, size, and grade from the same manufacturer offered for delivery at one time shall be considered a lot for purposes of inspection.

4.4 Visual and dimensional inspection. A random sample of door holders shall be selected from each lot in accordance with inspection level S-1, AQL 6.5 expressed in terms of defects per hundred units. The sample door holders shall be visually and dimensionally examined to verify compliance with this description. All dimensions are absolute as defined in ASTM E29.

4.5 Sampling performance and finish tests. Three door holders shall be randomly selected for performance testing. Samples for finish tests shall be selected in accordance with special inspection level S-1, AQL 4.0 expressed in terms of percent defective.

4.6 Testing. Door holders shall be tested in accordance with the performance and finish test procedures of ANSI/BHMA A156.16 and A156.18.

4.6.1 Performance test. The sample door holders shall be tested in accordance with section 4 of ANSI/BHMA A156.16 for the appropriate grade specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:13Z
Check the source to verify that this is the current version before use.

4.6.2 Finish test. The sample door holders shall be tested in accordance with section 5 of ANSI/BHMA A156.16.

4.7 Certification of performance test requirement. Unless otherwise specified in the contract or purchase order, a certificate of conformance may be furnished in lieu of actual testing on a lot by lot basis providing that:

(1) The product was manufactured domestically (United States).
(2) Objective evidence that the product offered has been tested to establish conformance with specified performance requirements.
(3) Tests specified in the industry standards referenced herein have been performed by a test facility acceptable to the Government.
(4) That the product being offered is the same type, material, and grade, and has been manufactured using the same manufacturing processes and techniques as the product tested.

In the event that conditions 2 thru 4 specified above are not met, testing shall be performed to establish conformance. If the contractor's source for product varies or if the product is of foreign manufacture, then testing must be performed on each inspection lot.

4.8 Examination for preparation for delivery. A random sample of shipping containers shall be selected from each lot for examination of the unit, intermediate and shipping containers (as applicable) for conformance with the preservation, packaging, packing, labeling, and marking required in the contract or order. Samples shall be selected in accordance with inspection S-2, AQL 6.5, expressed in terms of defects per hundred units. The sample unit shall be one shipping container.

5. PREPARATION FOR DELIVERY

5.1 Packaging, packing, and marking. The packaging, packing, and marking shall be as specified in the contract or order.

6. NOTES

6.1 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents (if applicable):

a. Title, number and date of this commercial item description.
b. Type and Size.
c. Material, grade and product code (see 3.3).
d. Finish and finish code (see 3.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:13Z
Check the source to verify that this is the current version before use.

e. Grade (see 3.5).
f. If certification is not permitted (see 4.7).
g. The packaging, packing, and marking desired.

6.2 National Stock Number: The following NSNs corresponds to the item described by this cid:

5340-00-568-9915 - Type I, Size 2
5340-00-930-8072 - Type II, Size 2

MILITARY INTERESTS:

LEAD STANDARDIZATION ACTIVITY:

DLA - IS

CIVIL AGENCY COORDINATING ACTIVITY:

VA - VOC
NASA - JFK

Preparing Activity:

GSA - FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:13Z
Check the source to verify that this is the current version before use.