INCH-POUND

A-A-50022A
December 13, 1989
SUPERSEDING
A-A-50022
February 2, 1982

# COMMERCIAL ITEM DESCRIPTION

## GLOVES, WELDER'S, LEATHER, GAUNTLET

The General Services Administration has authorized the use of this commercial item description in preference to type II of Federal specification KK-G-486.

## 1. CLASSIFICATION

1.1 Classification. This commercial item description covers gloves in the following sizes and widths as specified (see 5.2):

XX-Small
X-Small
Small
Medium
Large
Extra-Large

## 2. SALIENT CHARACTERISTICS

2.1 Description. The gloves shall be leather, Gunn cut pattern having a one-piece continuous back, and shall be inseam sewn. All seams except the hem shall include leather reinforcing welts. The seam at the base of the second and third fingers shall be inseam sewn with two rows of stitching and shall be covered with a leather welt in the hemming operation.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to: Commander, U.S. Army Natick Research, Development and Engineering Center, Natick, MA 01760-5014.

AMSC N/A FSC 8415

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:37Z
Check the source to verify that this is the current version before use.

2.2 Material.

2.2.1 Leather. The leather shall be flesh split cattlehide bends, and shall be suitable for use in gloves. Both sides of the leather shall be smooth and free of loose flesh. Middle splits, head splits, and shoulder splits shall not be used. The leather shall be chrome tanned, 2-1/2 to 3-1/2 ounce weight, and light gray in color. The components in each pair of gloves shall be of the same color.

2.2.2 Lining material. The inside of the leather gauntlet front and back shall be lined with an unbleached cotton duck weighing not less than 8.25 ounces per square yard and having a minimum tear strength of not less than 4 pounds in the warp and 3 pounds in the filling. There shall be a lining of knitted wool-cotton plaited cloth on the inside back extending from the bottom of the gauntlet facing to the tips of the fingers. The cotton back of the knitted cloth shall be next to the leather. The knitted cloth shall be a wool/cotton fabric of not less than 50's grade fleece or pulled new wool. The cotton backing yarn shall be not more than 30 percent of the weight of the cloth. The scoured and finished cloths shall range in weight from 9 to 11 ounces per square yard.

2.3 Thread, sewing. The thread for sewing shall be unbleached cotton.

2.4 Dimensions. The dimensions shall be not less than 12-1/4 inches in length and 3-1/2 inches in hand width for the smallest size, running upwards in a 1/2 inch grade. Each pair of gloves shall be matched, paired, and tacked together so that they can be easily pulled apart without damage.

3. QUALITY ASSURANCE

3.1 Certification. The contractor shall certify and maintain substantiating evidence that the product offered meets the salient characteristics and requirements of this Commercial Item Description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices. The Government reserves the right to require proof of such conformance prior to first delivery, and thereafter as may be otherwise provided for under the provision of the contract.

3.2 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:37Z
Check the source to verify that this is the current version before use.

3.3 End item visual examination. Each lot of gloves shall be inspected for consumer type defects, as follows:

Defects in design, construction, or workmanship; any component full, tight or twisted; open seam; any hole, cut or tear or any spot or stain clearly noticeable; any unhealed scratch, grub, tick marks, open veins, or clearly noticeable fat wrinkles in leather components.

The lot size shall be expressed in units of one glove. The sample unit shall be one glove, and the selection shall be by pairs. The inspection level shall II, and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 6.5.

3.4 End item dimensional examination. The finished gloves shall be measured for the minimum length (measured from the top of the second finger to the edge of the gauntlet) and the minimum width (measured from the base of the thumb across the palm to edges below the first and fourth fingers) as specified in 2.4. Also, any variation on the same pair of more than 1/4 inch for either dimension shall be scored as a defect. The lot size shall be expressed in units of one glove. The sample unit shall be one glove, and the selection shall be by pairs. The inspection level shall be S-3, and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

## 4. PACKAGING

4.1 Packaging. Each pair of gloves shall be placed end to end and packaged in a plastic bag.

4.2 Packing. Sixty pairs of gloves, of the same size, shall be packed in a fiberboard box conforming to style RSC-L, type CF (variety SW) or SF, class domestic, of PPP-B-636. The box shall be closed in accordance with the appendix of PPP-B-636.

4.3 Palletization. When specified (see 5.2), shipping containers shall be palletized in accordance with load type 1a of MIL-STD-147. Pallets shall be fabricated from wood groups I, II, III, or IV of MIL-STD-731. Each prepared load shall be bonded with primary and secondary straps in accordance with the bonding means C and D, or film bonding means F or G. Pallet pattern shall be in accordance with the appendix of MIL-STD-147.

4.4 Marking. In addition to any special marking required by the contract or purchase order, bundles, shipping containers, and palletized unit loads shall be marked in accordance with MIL-STD-129.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:37Z
Check the source to verify that this is the current version before use.

5. NOTES

5.1 Intended use. The gloves covered by this Commercial Item Description are intended for use as work gloves by welders.

5.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number and date of this document.
b. Size required (see 1.1).
c. When palletization is required (see 4.3).

5.3 Source for Government documents. Copies of military documents are available from:

Naval Publications and Forms Center
ATTN: NPODS
5801 Tabor Avenue
Philadelphia, PA 19120-5099

MILITARY INTERESTS:

Custodians:

Army - GL
Navy - NU
Air Force - 99

Review activities:

Army - MD
Air Force - 82
DLA - CT

User activities:

Navy - MC, MS, YD, SH
Air Force - 45

CIVIL AGENCY COORDINATION ACTIVITY:

GSA - FSS

PREPARING ACTIVITY:

Army - GL

(Project 8415-0729)



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:37Z
Check the source to verify that this is the current version before use.