INCH-POUND

A-A-50028A
October 29, 1993
SUPERSEDING
A-A-50028
July 27,1982

COMMERCIAL ITEM DESCRIPTION

BIN, INGREDIENT, MOBILE, 150 LB. AND 250 LB. CAPACITY

The General Services Administration has authorized the use of the Commercial Item Description in preference to size 2 of Military Specification MIL-B-43386B.

1. ABSTRACT

1.1 Abstract. This Commercial Item Description covers mobile ingredient bins of the following two sizes:

Size 1	150 lb. capacity
Size 2	250 lb. capacity

1.2 CID based part identification number (PIN). A document based PIN to identify sizes of items is included in section 5. This identification numbering procedure is for Government purposes and does not constitute a requirement for the contractor except as information on "Government unique" data nameplates (see 5.4).

2. SALIENT CHARACTERISTICS

2.1 Design and construction. The ingredient bins shall be fabricated with or without seams from stainless steel having a minimum thickness of 0.0375 inch. When applicable, seams shall be continuous, smooth, and blend in with bin body. The bins, when completely filled with water, shall not leak.

Beneficial comments, recommendations, additions, deletions, clarifications, etc., and any data which may improve this document should be sent to: Commander, U.S. Army Natick Research, Development, and Engineering Center, ATTN: SATNC-WEE, Natick, MA 01760-5018.

AMSC N/A FSC 7320

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil --·Downloaded: 2026-10-26T08:37Z
Check the source to verify that this is the current version before use.

The covers shall be fabricated from one piece of stainless steel having a minimum thickness of 0.0375 inch. The covers shall fit and slide properly without falling off the bins. When closed, the covers shall completely enclose the bin openings. The front top portion of the bins shall have a plate where a product identification card or label can be inserted. The bottom of the bins shall be reinforced for caster mounting. When bolts, nuts, or other fasteners are used they shall be drawn up tightly.

2.2 Sanitation. The complete bins, including covers and casters, shall comply with the requirements of NSF International Standard No. 2.

2.3 Dimensions. The bins, with covers, shall not exceed the following dimensions:

	Size 1	Size 2
Overall height	30 inches	30 inches
Overall length	29 inches	29 inches
Overall width	22 inches	25 inches

2.4 Capacities. The bins shall have minimum holding capacities equivalent to any of the following:

Size 1	Size 2
27 gallons	37 gallons
3 cubic feet	5 cubic feet
150 pounds of granulated sugar	250 pounds of granulated sugar

2.5 Casters. The bins shall have four casters attached to the body. Casters shall be 4 inches in diameter with a minimum load rating of 100 pounds each. The tread shall be polyurethane, natural rubber, synthetic rubber, or a combination thereof.

2.6 Bumper. A perimeter bumper shall be firmly attached and sealed to the bin bodies at a height not to exceed 12 inches. The bumper shall be fabricated from rubber or rubberlike material and protrude 1 inch $\pm$ 1/4 inch maximum beyond the bin bodies.

2.7 Data nameplate ("Government unique" requirement). The bins shall be furnished with a data nameplate in accordance with the applicable requirements of MIL-STD-130 except the requirements for: (a) Methods of applying, (b) Identification tags, (c) Information not required, and (d) Optional marking information shall not apply. The data nameplate shall be made of minimum 20 gauge corrosion-resisting metal and attached to the bin by rivets, screws, or welding in such a manner as to meet the applicable NSF International sanitary requirements for this equipment. The plate shall contain the following information which shall be stamped, engraved, or applied by photosensitive means:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:37Z
Check the source to verify that this is the current version before use.

Contract Number
National Stock Number
Procurement Instrument Identification Number
CID Based Part Identification Number (PIN)
Manufacturer's Name, Address, and Telephone Number
Supplier's Name, Address, and Telephone Number (List Only if Different from Manufacturer)
Manufacturer's Model and Serial Number
Government Approved Manual Number

Each plate shall be placed so that it is readily visible to the operator during normal operating use and so as to not adversely affect the life and utility of the bin.

2.8 Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within the tolerances specified using conversion tables contained in the latest revision of Federal Standard No. 376, and all other requirements of this commercial item description are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the contracting officer to determine if the product is acceptable. The contracting officer has the option of accepting or rejecting the product.

2.9 Regulatory requirements. In accordance with section 23.403 of the Federal Acquisition Regulations, the Government's policy is to acquire items composed of the highest percentage of recovered materials practicable, consistent with maintaining a satisfactory level of competition without adversely affecting performance requirements or exposing suppliers' employees to undue hazards from the recovered materials. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practicable. The term "recovered materials" means materials which have been collected or recovered from solid waste and reprocessed to become a source of raw materials as opposed to virgin raw materials. None of the above shall be interpreted to mean that the use of used or rebuilt products are allowed under this commercial item description unless otherwise specified.

2.10 Workmanship. The finished bins shall be complete, clean, and free of fabrication marks, scratches, dents, sharp edges, sharp corners, burrs, slivers, or visible evidence of rust. Rivets, when used, shall be tight and the rivet heads and peened ends shall be round and concentric and in full contact with the joined metal surfaces. There shall be no empty rivet holes. Welds shall be clean, continuous, sound, and free of flux, pits, buildups, undercuts, and shall be ground so as to blend with the adjacent surfaces. Spot welds shall be free from pits, burn throughs, and flashes.

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:37Z
Check the source to verify that this is the currentversion before use.

3. QUALITY ASSURANCE

3.1 Contractor certification. The contractor shall certify that the product offered meets the salient characteristics and requirements of this commercial item description and except for those Government unique requirements specified, conforms to the producer's own drawings, specifications, standards, and quality assurance practices, and is the same product offered for sale in the commercial marketplace or that had successfully been delivered to the Government on a previous contract or purchase order. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

3.2 Compliance. Prior to approval of the first shipment, the contractor shall submit satisfactory evidence to the contracting officer or his authorized representative that the bin conforms to the requirements of NSF International Standard No. 2 (see 2.2).

3.2.1 NSF International. Acceptable evidence of meeting the requirements of NSF International Standard No. 2 shall be a listing in the current edition of the NSF International "Listing of Food Service Equipment" and display of the NSF International mark on the finished product, or a certified test report from a recognized independent laboratory acceptable to the Government indicating compliance with the applicable NSF International requirement(s).

4. PACKAGING

4.1 Packaging. The mobile ingredient bin shall be preserved and packaged in accordance with ASTM D 3951.

4.2 Packing. Packing shall be in accordance with commercial packing complying with Uniform Freight Classification and National Motor Freight Classification, as applicable.

4.3 Marking. Commercial markings are acceptable, provided the following information is included:

National Stock Number
Item Description
Quantity
Date of Pack
Contract Number
Name, Address, and Zip Code of Manufacturer

5. NOTES

5.1 Intended use. The mobile ingredient bins covered by this commercial item description are intended for use in dining facilities for storage and transporting of dry bulk, meats, and liquids.

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:37Z
Check the source to verify that this is the currentversion before use.

5.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this commercial item description.
b. PIN designating size (see 1.1, 1.2, and 5.4).
c. Government approved manual number to be included on data nameplate (see 2.7).
d. Selection of applicable packaging and packing required (see 4.1).

5.3 Sources for documents.

5.3.1 Sources for non-Government association documents.

ASTM D 3951 - Standard Practice for Commercial Packaging

ASTM documents are available from:

American Society for Testing and Materials (ASTM)
1916 Race Street
Philadelphia, PA 19103-1187

National Motor Freight Classification 100-N

National Motor Freight Classification documents are available from:

National Motor Freight Traffic Association, Inc, Agent
American Trucking Associations, Inc., Traffic Department
1616 P Street, N.W.
Washington, DC 20036

NSF International Standard No. 2 - Food Service Equipment

NSF International documents are available from:

NSF International
3475 Plymouth Road
P.O. Box 130140
Ann Arbor, MI 48113-0140

Uniform Freight Classification 6000-E - Ratings, Rules and Regulations

Uniform Freight Classification documents are available from:


Uniform Classification Committee, Agent
222 South Riverside Plaza, Suite 1106
Chicago, IL 60606

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:37Z
Check the source to verify that this is the currentversion before use.

5.3.2 Source for Government documents. Copies of military and federal documents are available from:

Standardization Documents Order Desk
Building 4D
700 Robbins Avenue
Philadelphia, PA 19111-5094

5.4 Part identification number (PIN). The PIN's to be used for items required by this CID are created as follows:



5.5 "Government unique" requirements. Whenever a "Government unique" requirement is included in the title of a paragraph under "Salient Characteristics", it is meant that the requirement is something that is not normally offered to the commercial marketplace by the manufacturer.

MILITARY INTERESTS:

Custodians

Army - GL
Navy - YD
Air Force - 99

Review Activities

Army - MD, QM
Navy - MC
Air Force - 50, 84
DLA - GS

User Activity

Navy - SA

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

PREPARING ACTIVITY:

Army - GL

Project 7320-0900

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:37Z
Check the source to verify that this is the current version before use.