A-A-50030A
April 15, 1988
SUPERSEDING
A-A-50030
August 27, 1982

COMMERCIAL ITEM DESCRIPTION

SLICING MACHINE, BUN

The General Services Administration has authorized the use of this commercial item description in preference to Military specification MIL-S-43818.

1. SALIENT CHARACTERISTICS.

1.1 Design and construction. The bun slicing machine shall consist of a feeding chute tilted at a 25 to 35 degree vertical angle with the machine base and a circular cutting blade rotated by an electric motor. The motor shall be at least 1/4 horsepower and shall be controlled by an on-off switch provided with a safety guard cover located on the body of the bun slicing machine accessible to the operator. The feeding chute shall have adjustments for bun width and height, and thickness and depth of cut. The feeding chute interior width shall be infinitely adjustable from a lower limit of no more than 1-1/4 inches to an upper limit of no less than 5 inches. The feeding chute interior height shall be infinitely adjustable from a lower limit of no more than 1-3/4 inches to an upper limit of no less than 2-3/4 inches. The cutting blade height shall be infinitely adjustable from a lower limit of no more than 1/2 inch above the base of the chute to an upper limit of no less than 15/16 inch above the base of the chute. The bun slicing machine shall be a counter model with 4 non-skid feet, and shall have envelope dimensions no greater than 36 inches wide, 15 inches deep, and 25 inches high. No tools or excessive force shall be required to make adjustments on the bun slicing machine, and during adjustment there shall be no binding or jamming of moving parts. The bun slicing machine shall be capable of slicing both soft and hard buns and rolls without jamming or stalling, and without tearing or crushing the buns or rolls. When the machine is switched on, the cutting blade shall rotate such that, within the chute, the cutting edge travels away from the bun inlet. The cutting teeth or serrations, as applicable, shall have their cutting edge facing the same direction as the blade travels.

FSC 7320

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:37Z
Check the source to verify that this is the current version before use.

1.2 Electrical characteristics. The bun slicing machine shall be designed for operation on a nominal 120 volt, 60 hertz, 1 phase alternating current.

1.3 Standards compliance. The bun slicing machine shall comply with Underwriters Laboratories, Inc. (UL) Standard No. 763 and Baking Industry Sanitation Standards Committe (BISCC) Standard No. 13.

1.4 Data name plate (Government unique requirement (see 4.4)). The bun slicing machine shall be furnished with a data name plate in accordance with the applicable requirements of MIL-STD-130 except the requirements for: (a) Methods of applying, (b) Identification tags, (c) Information not required, and (d) Optional marking information shall not apply. The data name plate shall be made of minimum 20 gage corrosion-resisting metal, and attached to the bun slicing machine by rivets, screws, or by welding, in such a manner as to meet the applicable National Sanitation Foundation requirements for this equipment. The plate shall bear the following information which shall be stamped, engraved, or applied by photosensitive means:

National Stock Number
Procurement Contract Number
Specification Data
Manufacturer's Name, Address, and Telephone Number
Supplier's Name, Address, and Telephone Number (List only if different from Manufacturer)
Manufacturer's Model Number
Government Approved Manual Number (when specified, see 4.2)

Each plate shall be placed so that it is readily visible to the operator during normal operating use and so as to not adversely affect the life and utility of the bun slicing machine.

2. QUALITY ASSURANCE

2.1 Certification. The contractor shall certify that the product offered meets the salient characteristics and requirements of the description and except for those government unique requirements specified, conforms to the producer's own drawings, specifications, standards, and quality assurance practices, and is the same as the product offered for sale in the commercial marketplace. The contractor shall certify the product meets the "Government unique" requirements except when specific quality assurance provisions are specified for the Government unique requirements. In this case, the contractor shall provide data resulting from inspection conducted in accordance with the specified quality assurance. The Government reserves the right to require proof of such conformance prior to first delivery and

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:37Z
Check the source to verify that this is the current version before use.

3. PACKAGING

3.1 Packaging and packing. Packaging and packing shall be commercial or export, as specified (see 4.2).

3.2 Commercial packaging and packing. Each bun slicing machine shall be cleaned, preserved, packaged, packed, and unitized in accordance with ASTM D 3951.

3.3 Export packaging and packing.

3.3.1 Export packaging. Each bun slicing machine shall be cleaned, preserved, and cushioned to protect against corrosion, deterioration, and physical damage during shipping and storage.

3.3.2 Export packing. Each bun slicing machine shall be packed in a nailed and lock-corner wood box conforming to class 2, style optional, type 2 load of PPP-B-621 or a wood-cleated plywood box conforming to overseas type, style optional, type 2 load of PPP-B-601. Each box shall be waterproofed with a sealed case liner conforming to type I, II, or IV, grade optional of MIL-L-10547. Each box shall be closed and strapped in accordance with PPP-B-621 or PPP-B-601, as applicable.

3.4 Marking (commercial and export). Marking of unit packs and shipping containers shall be in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

4. NOTES

4.1 Intended use. The handfed, counter mounted electrically powered bun slicing machines are intended for use in garrison areas to slice rolls and buns.

4.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. Government approved manual number to be included on the data name plate when manuals are purchased under the contract (see 1.4).
c. Selection of applicable packaging and packing required (see 3.1).

4.3 Sources of documents.

4.3.1 Sources of nongovernment association documents.

UL Standard No. 763 - Motor Operated Commercial Food Preparing Machines, is available from:

Underwriters Laboratories, Inc. (UL)
333 Pfingsten Road
Northbrook, IL 60062

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:37Z
Check the source to verify that this is the currenversion before use.

BISCC Standard No. 13 - Bread and Roll Slicers and Wrappers, is available from:

Baking Industry Sanitation Standards Committee (BISCC)
111 East Wacker Drive
Suite 600
Chicago, IL 60601

ASTM D 3951 - Standard Practice for Commercial Packaging is available from:

The American Society for Testing and Materials (ASTM)
1916 Race Street
Philadelphia, PA 19103-1187

NSF Standards are available from:

National Sanitation Foundation (NSF)
3475 Plymouth Road
P.O. Box 1468
Ann Arbor, MI 48106

4.3.2 Sources of governmental documents.

Military documents are available from:

Naval Publications and Forms Center
5801 Tabor Avenue
Philadelphia, PA 19120

4.4 Government unique requirements. Whenever "(Government unique requirement)" is included in the title of a paragraph under "salient characteristics," it is meant that the requirement is something that is not normally offered to the commercial marketplace by the manufacturer.

MILITARY INTERESTS:

Custodians

Army - GL
Navy - SA
Air Force - 99

Review Activities

Army - MD
Navy - YD
Air Force - 84
DLA - GS

User Activity

Navy - MC

CIVIL AGENCY COORDINATING ACTIVITY:

GSA-FSS

PREPARING ACTIVITY:

Army - GL

Project No. 7320-0825

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:37Z
Check the source to verify that this is the current version before use.