A-A- 50035
September 27, 1982

COMMERCIAL ITEM DESCRIPTION

RANGES, ELECTRIC INDUSTRIAL

The General Services Administration has authorized the use of this commercial item description in preference to Military Specification MIL-R-11295.

Intended use. The ranges covered by this CID are intended for use in dining halls for oven roasting and top surface cooking.

Salient characteristics.

The ranges shall consist of an oven section surmounted by a griddle top or a cooking top as specified. The ranges shall be of the following types.

Type I - Griddle top
Grade A - Stainless steel exterior

Type II - Cooking top
Grade A - Stainless steel exterior
Grade B - Stainless steel front-remaining sides and back shall be carbon steel

Type I, griddle top. The griddle top shall be 36 inches wide by 24 inches deep with sides and rear back-splash guards. The range shall have front and rear grease troughs with drains that empty into a grease receptacle. The griddle temperature shall be controlled by a minimum of three thermostats. Each thermostat shall control the temperature of one third of the griddle surface from 175° to 450°F minimum. The griddle shall be capable of reaching a surface temperature of 400°F in 13 minutes.

Type II, cooking top. The cooking top shall consist of three hot plates each 12 inches wide by 24 inches deep. Each hot plate shall be equipped with a thermostat to control the hot plate surface temperature from 250° to 800°F. The hot plate shall be capable of reaching a surface temperature of 500°F in 20 minutes.

Oven. The oven shall have one slide rack and supports to divide the oven into at least two equal compartments. The oven door shall be hinged at the bottom, counter balanced, and when fully opened shall remain level and even with the oven deck. The oven and door shall be insulated. With the oven empty and the door closed the oven shall be capable of maintaining a temperature of 450°F with not more than 0.77 KW electrical energy. Two removable elements, one located at the top and one at the bottom shall be provided. Each element shall be controlled by a three-heat indicating switch and a thermostat calibrated from 200° to 500°F minimum. The oven shall preheat to 450°F in 20 minutes.

FSC 7310

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.

Dimensions. The range and oven dimensions are shown in Table I.

TABLE I. Range dimensions (inches, min)

	Width	Depth	Height
Range	36	36 1/	36 2/
Oven interior	22	26-1/2	12

1/ Includes front overhang.

2/ To cooking surface.

Legs. The range shall be equipped with 6 inch adjustable legs.

Finish. The grade A range front, sides and back shall be stainless steel. The grade B range front shall be stainless steel; the remaining sides and back shall be carbon steel.

Electrical characteristics. The ranges shall be wired for either 208 V, 60 Hz, 3 Ph or 220/380 V, 50 Hz, 3 Ph, 4 wire operation.

Standards compliance. The ranges shall comply with UL Standard No. 197 and the National Sanitation Foundation Standard No. 4.

Identification plate. In addition to the marking and identification required by UL 197, the identification plate shall include the contract number and national stock number.

Certification. The contractor shall certify that the product offered meets the salient characteristics of this description, and conforms to the producer's own drawings, specifications, standards and quality assurance practices, and is the same product sold in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be provided for under the provisions of the contract.

Packaging.

A. Commercial packaging. Each electric range shall be packaged in accordance with commercial practice.

B. Commercial packing. Each electric range shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall comply with the Uniform Freight Classification or National Motor Freight Classification, as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.

C. Export packaging. Each electric range shall be disassembled to the extent determined by the supplier to protect parts susceptible to damage during shipment and storage and for reduction of cubage. Parts removed shall be identified. Nuts, bolts and screws removed during disassembly shall be reinserted and secured in their respective locations or placed in a cloth drawstring bag. The range and parts shall be cleaned, preserved and cushioned to afford protection against corrosion, deterioration and physical damage during shipment and storage. Disassembled parts may be packaged in a class weather-resistant fiberboard box conforming to PPP-B-636 Boxes, Shipping, Fiberboard, or placed within the range or directly into the shipping container with the range. The owner's manual shall be placed in a plastic bag and then securely attached to the unit. The range door shall be secured in a closed position with strapping or filament reinforced pressure-sensitive tape. Cushioning or other appropriate material shall be placed between the range surfaces and securement to protect the finish.

D. Export packing. Each electric range shall be packed in a snug-fitting wood-cleated plywood box conforming to domestic type, style A or J, grade B, type 2 load of PPP-B-601 Boxes, Wood, Cleated-Plywood, or nailed wood box conforming to class 1, style 2 or 4, grade B of PPP-B-621 Boxes, Wood, Nailed and Lock-Corner. The contents of the box shall be cushioned, blocked and braced to prevent movement while the box is in transmit. Each shipping container shall be closed and strapped in accordance with the appendix of PPP-B-601 or PPP-B-621, as applicable.

E. Marking of interior boxes and shipping containers (commercial and export). Commercial marking for interior boxes and shipping containers is acceptable provided the following information is included:

National Stock Number	Date of Packaging (month/year)
Item Description	Contract Number
Quantity, Unit of Issue	Name, Address and Zip Code of Contractor 1/

1/ Interior boxes do not require this information.

Source of Information for Non-Government Associated Documents.

Underwriters Laboratories, Inc.
333 Pfingsten Road, Northbrook, IL 60062

National Sanitation Foundation (NSF)
P.O. Box 1468, Ann Arbor, MI 48106

National Motor Freight Traffic Association, Inc., Agent
National Motor Freight Classification
American Trucking Associations Inc., Traffic Department
1616 P Street, N.W., Washington, DC 20036

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.

A-A-50035

Unirorm Classification Committee Agent
Uniform Freight Classification
Uniform Classification Committee, Suite 1106
222 South Riverside Plaza, Chicago, IL 60606

MILITARY INTERESTS:

Custodians

Army - GL
Navy - YD
Air Force - 99

Review Activities

Army - MD
Navy - MC
Air Force - 84

User Activity

Army - CE

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

PREPARING ACTIVITY:

Army - GL

Project No. 7310-0668

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.