A-A-50036
September 30, 1982

COMMERCIAL ITEM DESCRIPTION

DOUGH TROUGHS

The General Services Administration has authorized the use of this Commercial Item Description in preference to Size 4 and Size 6 of Military Specification MIL-D-13053.

Intended Use. The dough troughs covered by this CID are intended for use in bakeries and pastry kitchens for transporting dough.

Sizes:

Size 4 - 4 ft. long
Size 6 - 6 ft. long

Salient Characteristics:

Description. The dough trough shall be fabricated of stainless steel (min. 12 gage) conforming to ASTM-A167 and shall have a rectangular shape. The top of the dough trough shall have a rolled rim tightly closed and seal welded against the wall of the trough. The sides and bottom of the trough shall be formed of one sheet stainless steel. The ends shall be welded to the sides and bottom. Caster shoes shall be completely inclosed and be seal welded to the trough body.

Casters. The dough trough shall be equipped with four heavy duty sanitary type swivel casters bolted to caster shoes. The swivel assembly shall have ball or roller bearings equipped with a pressure type lubricating fitting. The wheel bearings shall be ball or roller with pressure type lubricating fitting or lubricated and permanently sealed. Caster wheels shall be 4 inch diameter minimum fabricated from nonmarking material.

Dimensions. The minimum inside dough trough dimensions shall be 26 inches wide at the top, 21 inches deep, 4 feet long for size 4 and 6 feet long for size 6.

Standard compliance. The dough troughs shall comply with Baking Industry Sanitation Standard No. 2.

Identification plate. The dough trough shall be plainly and permanently marked with the contract number, national stock number, manufacturer's name, trade name, or trademark or such known character that the source of manufacture can be determined.

Certification. The contractor shall certify that the product offered meets the salient characteristics of the description and conforms to the producers' own drawings, specifications, standards, and quality assurance practices, and is the same as the product sold in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be [illegible] provided for under the provisions of the contract.

FSC 7320

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:37Z
Check the source to verify that this is the current version before use.

Packaging:

Commercial packaging. Dough troughs shall be packaged in accordance with commercial practice.

Commercial packing. Dough troughs shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall comply with the Uniform Freight Classification or National Motor Freight Classification, as applicable.

Export packaging. The swivel casters shall be removed from the trough and be packaged in a class weather-resistant fiberboard box constructed and closed in accordance with PPP-B-636, Boxes, Shipping, Fiberboard. The trough shall be cleaned, preserved and cushioned to afford adequate protection against corrosion, deterioration and physical damage during shipment and storage.

Export packing. Each dough trough shall be packed in a snug-fitting wood-cleated plywood box conforming to domestic type, style A or J, grade B, type 2 load of PPP-B-601, Boxes, Wood, Cleated Plywood or nailed wood box conforming to class 1, style 2 or 4, grade B, type 2 load of PPP-B-621, Boxes, Wood, Nailed and Lock Corner. the contents of the box shall be cushioned, blocked and braced to prevent movement while the box is in transit. Each shipping container shall be closed and strapped in accordance with the appendix of PPP-B-601 or PPP-B-621, as applicable.

Marking of interior boxes and shipping containers (commercial and export). Commercial marking for interior boxes and shipping containers is acceptable provided the following information is included:

National Stock Number	Date of Packaging (month/year)
Item Description	Contract Number
Quantity, Unit of Issue	Name, Address and Zip Code of Contractor 1/

1/ Interior boxes do not require this information.

Source of Information for Non-Government Association Documents

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

A167 - Stainless and Heat-Resisting Chromium-Nickel Steel Plate, Sheet and Strip

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:37Z
Check the source to verify that this is the currentversion before use.

A-A- 50036

BAKING INDUSTRY SANITATION STANDARD (BISSC)

No. 2 Dough Troughs

(Copies of Baking Industry Standards Publication may be obtained from the Baking Industry Sanitation Standards Committee, 521 Fifth Avenue, New York, NY 10017.)

National Motor Freight Traffic Association, Inc., Agent
National Motor Freight Classification
American Trucking Associations, Inc., Traffic Department,
1616 P Street, N.W., Washington, DC 20036

Uniform Classification Committee, Agent
Uniform Freight Classification
Uniform Classification Committee, Suite 1106
222 South Riverside Plaza, Chicago, IL 60606

MILITARY INTERESTS:

Custodians

Army - GL
Navy - YD
Air Force - 99

Review activities

Army - MD
Navy - MC, MS, SA

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

PREPARING ACTIVTY:

Army - GL

Project No. 7320-0715

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:37Z
Check the source to verify that this is the current version before use.