A-A-50040
November 1, 1982

COMMERCIAL ITEM DESCRIPTION

FILTER UNIT, COOKING GREASE, PRESSURE

The General Services Administration has authorized the use of this commercial item description in preference to type II, size 1 and type III, size 1 of Military Specification MIL-F-2296.

Salient characteristics.

Design and construction. The filters shall be designed to filter liquified, solidifying, or nonsolidifying frying medium used in deep fat fryers and doughnut machines at a rate of 3 gallons per minute minimum. The filter shall consist of an electric motor(s), as specified, pump(s), reservoir, hoses, filters, controls and fittings and have a means for fast draining of the system. The filters shall be of the following types and sizes:

Type II - Gravity or pumped drain and pumped refill
Size 1 - 50-pound minimum reservoir capacity
Style A - 120 V, 60 Hz, single phase
Style B - 220 V, 50 Hz, single phase

Type III - Pumped suction drain and pumped refill
Size 1 - 80 pound minimum reservoir capacity
Style A - 120 V, 60 Hz, single phase
Style B - 220 V, 50 Hz, single phase

Type II, size 1 filters may be equipped with a reversing capability to permit pumped suction, from fryer to filter, or they shall be capable of being rolled under the fryer drains where they can be filled. Filters without the reversing capability shall not exceed a height of 13-3/4 inches, exclusive of the handle. Type III, size 1 filters shall have a reversing capability to permit pumped suction as well as pumped refill each at a minimum rate of 3 gallons per minute. Each type of filter assembly shall be supplied with sufficient filters necessary for 100 filtering operations and each filter be capable of being easily removed and replaced. When a filtering compound is necessary to perform the complete filtering process, a sufficient quantity shall be supplied for at least 100 filtering operations and the compound shall restore color and remove odor and taste from the frying medium. The filters, when used with or without the filtering compound, as recommended by the manufacturer, shall retain particles 10 microns and larger. The filter assemblies shall be mounted on swivel casters: the total load rating of which shall be equal to or greater than the weight of the filter assembly and the rated load of the reservoir. All materials in contact with the frying medium shall be acceptable for food handling service and be capable of withstanding the temperatures normally encountered in filtering operations. The filters sanitation standard shall comply with the requirements set forth in the National Sanitation Foundation Standard No. 4, as applicable.

FSC 7330

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.

Reservoir. The reservoir shall be fabricated of stainless steel or aluminum of sufficient thickness to prevent dents or damage which would impair function in normal operation. The reservoirs shall have a minimum fat capacity of 50 pounds for the type II, size 1 and 80 pounds for the type III, size 1.

Electrical requirements. Filters shall be supplied with motors of not less than 1/4 Hp and be equipped with an overload protection device. The motors for the type III filters shall be of the reversing type. Motors for style A units shall be rated for 120 V, 60 Hz, single phase, motors for style B units shall be rated for 220 V, 50 Hz, single phase. Filters shall be supplied with a 6 foot (minimum) power supply cord and have provisions for storing cord when not in use. Filters designed for 120 V, 60 Hz, 1 Ph power shall have a NEMA 5-15P plug assembled to the end of the cord. Controls for motor(s) and pump(s) operation shall be rigidly mounted in a location easily accessible to the operation. Filters having the reversing capability shall be supplied with a switch clearly indicating wether the filter is in the pumped suction or the pumped refill mode.

Instruction plate. The filters shall have an instruction plate permanently attached to it in a readily visible area. The plate shall contain the manufacturers' standard operating instructions etched, embossed, or die-stamped.

Standard compliance. The cooking grease filters shall comply with the National Sanitation Foundation Standard No. 4 and Underwriters Laboratories Standard No. 197.

Identification plate. In addition to the marking and identification requirements of UL Standard No. 197, the identification plate shall include the contract number and national stock number.

Certification. The contractor shall certify that the product offered meets the salient characteristics of this description, and that the product conforms to the producers' own drawings, specifications, standards and quality assurance practices and is the same product sold in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94/580 to the maximum extent practicable.

Packaging.

A. Packaging. The cooking grease filters shall be preserved and packaged in accordance with commercial practice.

B. Packing. Packing shall be in accordance with commercial packing complying with Uniform Freight Classification or National Motor Freight Classification, as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.

C. Marking. Commercial markings are acceptable, provided the following information is included:

National Stock Number	Date of Pack
Item Description	Contract Number
Quantity	Name, Address and Zip Code of Manufacturer

Source of Information for Non-Government Association Documents

National Electrical Manufacturers Association
2101 L. Street, N.W.
Washington, DC 20037

National Sanitation Foundation (NSF) - National Sanitation Foundation
P.O. Box 1468
Ann Arbor, MI 48105

Underwriters Laboratories, Inc. (UL) - Underwriters Laboratories Inc.
33 Pfingsten Road, Northbrook, IL 60062

National Motor Freight Traffic Association, Inc., Agent
National Motor Freight Classification
American Trucking Associations, Inc., Traffic Department
1616 P. Street, N.W., Washington, DC 20036

Uniform Classification Committee, Agent
Uniform Freight Classification
Uniform Classification Committee, Suite 1106
222 South Riverside Plaza, Chicago, IL 60606

MILITARY INTERESTS:

Custodians

Army - GL
Navy - SA
Air Force - 99

Review Activities

Army - MD
Navy - MC, MS
DLA - GS

User Activity

Army - CE

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - OPP

PREPARING ACTIVITY:

Army - GL

Project No. 7310-0666

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.