A-A-50042
December 30, 1982

COMMERCIAL ITEM DESCRIPTION

OVENS, BAKING AND ROASTING, FORCED CONVECTION, GAS

The General Services Administration has authorized the use of this commercial item description in preference to Military Specification MIL-O-43679.

Intended use. This description covers two types of ovens used in military dining facilities as follows:

Type I, one oven compartment
Type II, two oven compartments

Salient characteristics.

Description. The type II oven shall consist of two type I ovens stacked and secured. Each oven compartment shall operate independently. Oven exterior surfaces except the bottom and back shall be stainless steel. The oven compartment and door lining shall be stainless steel. Each oven compartment shall be equipped with removable stainless steel top, right-hand, left-hand, and bottom oven liner panels, five equally spaced shelves supported by removable shelf supports, two speed blower, oven light, oven indicator light, and a 5 hour oven timer with alarm. The oven without liner panels shall preheat from an ambient temperature of 70°to 400°F within 20 minutes. Oven doors shall be vertically split, side opening type, with heat-resisting viewing windows. A handle shall be provided on each door or one handle to open and close the doors simultaneously. The type I oven shall be mounted on legs or mounted on an open or inclosed stainless steel stand. All ovens shall be equipped with stainless steel legs with leveling devices.

Dimensions. The ovens shall be within the dimensional limits shown in table I.

TABLE I. Dimensions (inches)

Measurements	Minimum	Maximum
Width overall	33	52
Depth overall	30	48
Height 1/ overall (excluding vent)		
Type I	26	63
Type II	52	78
Height 1/ to bottom deck		
Type I	26	38
Type II	11	19-3/4
Height 1/ to top deck (type II)	30	51-3/4

FSC 7310

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.

TABLE I. Dimensions (inches) (cont'd)

Measurements	Minimum	Maximum
Compartment (inside usable)		
Width	21-1/2	29-1/4
Depth	20	30
Height	19-3/8	28

1/ Height from floor, including supporting legs and base.

Fuel system. The oven shall be designed to burn natural gas. Each oven rating shall not exceed 120,000 BTU/hr. The ovens shall be equipped with an automatic pilot of the 100 percent shut-off type, a pressure regulator and automatic gas ignition system. An ANSI approved quick disconnect (socket and plug) and a 5 foot minimum flexible metal connector consisting of a male pipe thread fitting on one end and union with female thread on the opposite end shall be supplied with each oven(s).

Thermostats. Each oven compartment shall have a manually operated thermostat to provide automatic heat control of the oven compartment.

Electrical characteristics. The electrical controls, lights, switches, and blower shall operate on a nominal 120 volt, 60 hertz, single phase power source or 220 volt, 50 Hertz, single phase power source when specified. The oven blower motor shall be of the capacitor or split-phase type rated at 1/2 or 3/4 horsepower (HP).

Standard compliance. The ovens shall comply with American National Standard Institute No. Z83.12 and the National Sanitation Foundation Standard No. 4.

Identification plate. In addition to the marking and identification requirements of ANSI No. Z83.12, the identification plate shall include the contract number, national stock number and date of manufacture.

Certification. The contractor shall certify that the product offered meets the salient characteristics of description and conforms to the producers own drawings, specifications, standards, and quality assurance practices, and is the same as the product sold in the commercial marketplace, except for those additional requirements/characteristics specified herein. The Government reserves the right to require proof of such conformance prior to first delivery and therefore as may be otherwise provided for under the provisions of the contract.

Packaging.

A. Commercial packaging. Each oven shall be packaged in accordance with commercial practice.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:38Z
Check the source to verify that this is the currentversion before use.

B. Commercial packing. Each oven shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall comply with the Uniform Freight Classification or National Motor Freight Classification, as applicable.

C. Export packaging. The oven shall be disassembled to the extent determined by the supplier to protect parts susceptible to damage during shipment and storage and for reduction of cubage. Parts removed shall be identified. The oven and parts shall be cleaned, preserved and cushioned to afford protection against corrosion, deterioration, and physical damage during shipment and storage. Disassembled parts may be packaged in a class weather-resistant fiberboard box conforming to PPP-B-636 or placed within the oven or directly into the shipping container with the oven.

D. Export packing. One oven shall be packed in a snug-fitting wood-cleated plywood box conforming to domestic type, style A or J, grade B, type 2 load of PPP-B-601 or nailed wood box conforming to class 1, style 2 or 4, grade B of PPP-B-621. The contents of the box shall be cushioned, blocked, and braced to prevent movement while the box is in transit. Each shipping container shall be closed and strapped in accordance with the appendix of PPP-B-601 or PPP-B-621, as applicable.

E. Marking of interior boxes and shipping containers (commercial and export). Commercial marking for interior boxes and shipping containers is acceptable provided the following information is included:

National Stock Number	Date of Packaging (month/year)
Item Description	Contract Number
Quantity, Unit of Issue	Name, Address, and Zip Code of Contractor 1/

1/ Interior boxes do not require this information.

Source of Information for all Non-Government Association Documents.

National Sanitation Foundation (NSF) - National Sanitation Foundation, NSF Building, Ann Arbor, MI 48105

American National Standards Institute (ANSI) - American National Standards Institute, 1430 Broadway, New York, NY 10018

National Motor Freight Traffic Association, Inc., Agent
National Motor Freight Classification
American Trucking Associations, Inc., Traffic Department,
1616 P Street, N.W., Washington, DC 20036

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:38Z
Check the source to verify that this is the currentversion before use.

Uniform Classification Committee, Agent
Uniform Freight Classification
Uniform Classification Committee, Suite 1106
222 South Riverside Plaza, Chicago, IL 60606

MILITARY INTERESTS:

Custodians

Army - GL
Navy - YD
Air Force - 99

Review Activities

Army - MD
Navy - MC
DLA - GS

User Activity

Army - ME

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - OPP

PREPARING ACTIVITY:

Army - GL

Project No. 7310-0667

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.