A-A-50048
April 11, 1983

COMMERCIAL ITEM DESCRIPTION

WAFFLE IRON, ELECTRIC

The General Services Administration has authorized the use of this commercial item description in preference to Military Specification MIL-W-40110.

Intended use. The waffle irons covered by this document are intended for use in military kitchens and galleys.

Salient characteristics.

The waffle iron shall consist of two, 7 inch diameter or square units and shall be an electrically heated, counter-type design. Each unit shall operate independently of the other and shall consist of an upper and lower grid, an independent "ON-OFF" switch control, spillage receptacle, and indicating light. Each unit shall be capable of producing 15 waffles per hour. Each baking unit shall have a mechanical timer with audible alarm. The body shall be fabricated of stainless steel and the grids shall be cast aluminum treated with a non-stitch compound. The upper grid shall have a floating hinge so that, when closed, it will remain parallel to the batter filled lower grid. A handle shall be securely fastened to each upper grid for raising and lowering the grid. Removable, stainless steel receptacles shall be provided for each lower grid section. The receptacles shall be formed so as to retain overflow from the baking units. The waffle iron assembly shall be electrically grounded by a three wire grounding type cord, 6 feet long, and an attachment plug for 120 volts to conform to NEMA Standard 5-15P and, for 240 volts, to conform to NEMA Standard 6-15P.

Electrical characteristics. The waffle iron assembly shall be rated for one of the following nominal system voltages, as specified:

(a) - 120 volt, 1 phase, 60 Hz, 1600 W (min)
(b) - 240 volt, 1 phase, 60 Hz, 1600 W (min)
(c) - 220 volt, 1 phase, 50 Hz, 1600 W (min)

Standards compliance. The waffle iron shall conform to National Sanitation Foundation (NSF) Standard No. 4 and Underwriters Laboratories (UL) No. 197.

FSC 7310

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.

Identification plate. In addition to the marking and identification required by UL No. 197, the identification plate shall include the contract number and national stock number.

Certification. The contractor shall certify that the product offered meets the salient characteristics of this description, conforms to the producer's own drawings, specifications, standards, and quality assurance practices, and is the same as the product sold in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under provisions of the contract.

Packaging.

A. Commercial packaging. Each waffle iron shall be packaged in accordance with commercial practice.

B. Commercial packing. Each waffle iron shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall comply with the Uniform Freight Classification or National Motor Freight Classification, as applicable.

C. Export packaging. Each waffle iron shall be disassembled to the extent determined by the supplier to protect parts susceptible to damage during shipment and storage and for reduction of cubage. The owners manual shall be placed in a paper envelope or plastic bag. The waffle iron and parts shall be cleaned, preserved and cushioned to afford protection against corrosion, deterioration and physical damage during shipment and storage. Each waffle iron and parts shall be packaged in a snug-fitting fiberboard box constructed and closed in accordance with style optional, class domestic, grade, 200 of PPP-B-636. Fiberboard inner packing shall be used to physically protect and immobilize the waffle iron and parts within the box.

D. Export packing. Six waffle irons shall be packed in a snug-fitting wood-cleated plywood box conforming to domestic type, style A or J, grade B, type 2 load of PPP-B-601 or nailed wood box conforming to class 1, style 2 or 4, grade B, type 2 load of PPP-B-621. Each shipping container shall be closed and strapped in accordance with the appendix of PPP-B-601 or PPP-B-621, as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.

E. Marking of interior boxes and shipping containers (commercial and export). Commercial marking for interior boxes and shipping containers is acceptable provided the following information is included:

National stock number	Date of packaging (month/year)
Item description	Contract number
Quantity, unit of issue	Name, address and zip code of contractor 1/

1/ Interior boxes do not require this information.

Sources of information for nongovernment association documents:

National Electrical Manufacturers Association
155 East 44th Street
New York, NY 10017

National Sanitation Foundation
P.O. Box 1468
Ann Arbor, MI 48106

Underwriters Laboratories, Inc.
333 Pfingsten Road
Northbrook, IL 60062

National Motor Freight Traffic Association, Inc., Agent
National Motor Freight Classification
American Trucking Associations, Inc., Traffic Department
1616 P Street, N.W., Washington, DC 20036

Uniform Classification Committee, Agent
Uniform Freight Classification
Uniform Classification Committee, Suite 1106
222 South Riverside Plaza, Chicago, IL 60606

MILITARY INTERESTS:

Custodians

Army - GL
Navy - SA
Air Force - 99

Review Activities

Army - MD
Air Force - 84
DSA - GS

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

PREPARING ACTIVITY:

Army - GL

Project No. 7310-0670

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.