COMMERCIAL ITEM DESCRIPTION

ROPE, FIBROUS, TENT-LAY

The General Services Administration has authorized the use of this commercial item description in preference to Military Specification MIL-R-1670.

Salient characteristics.

The rope shall be either a three or four strand construction and fabricated from manila hemp, sisal, jute or cotton fiber. The rope shall be furnished with either a natural finish or with a mildew resistant treatment conforming to the requirements specified in T-T-616. The rope shall conform to the physical and construction properties specified in table I.

TABLE I. Breaking strength and length per pound

Circumference, inch		Diameter	Breaking strength	Length per pound
Min	Max	inches (approx)	lbs (min)	ft (min) 1/
9/16	11/16	3/16	410	66.7
5/8	7/8	1/4	570	50.0
7/8	1-1/8	5/16	920	34.5
1	1-1/4	3/8	1260	24.4
1-3/8	1-5/8	1/2	2650	13.3
1-13/16	2-3/16	5/8	4000	7.4
2-1/16	2-7/16	3/4	5100	6.1
2-3/4	3-1/4	1	8350	3.7
3-1/2	4	1-1/4	13200	2.4

1/ Tolerance of ± 10 percent.

FSC 4020

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:38Z
Check the source to verify that this is the current version before use.

No material shall be added for the purpose of weighting the rope. The percent extractable matter by weight shall not exceed 25 percent. The maximum allowable water absorption by weight for jute and cotton rope shall be 25 and 35 percent respectively.

Certification. The contractor shall certify that the product offered meets the salient characteristics of the description and conforms to the producer's own drawings, specifications, standards, and quality assurance practices, and is the same as the product sold in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to the first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practicable.

Packaging.

A. Commercial packaging. The rope shall be packaged in accordance with commercial practice.

B. Commercial packing. Rope packaged as specified shall be packed in accordance with commercial packing complying with pertinent Uniform Freight Classification or National Motor Freight Classification, as applicable.

C. Export packaging or put-up. Unless otherwise specified, the ropes shall be furnished in coils in the minimum lengths specified in the table below. A plus tolerance of 10 percent is allowed on the minimum length specified. The coils shall contain not more than two pieces of rope and no piece shall be less than 100 feet in length. The rope shall be continuous throughout; shall not contain splices, strand knots, loose or broken ends; and shall be wound so that each turn and layer is free from entanglement. The ends of all rope shall be cut off equally and shall be securely whipped or taped to prevent the ends from unlaying or untwisting.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.

TABLE II. Put-up

Size, circumference (in)	Minimum length of coil (feet)				Approximate gross weight of coil (lbs)			
	Manila	Sisal	Jute	Cotton	Manila	Sisal	Jute	Cotton
5/8	-	-	-	3570	-	-	-	50
3/4	2775	2775	2500	2175	56	56	50	42
1	1925	1925	1725	1385	56	56	50	39
1-1/8	1350	1350	1220	1200	51	51	50	46
1-1/2	1200	1200	1200	1200	90	90	90	76
2	1200	1200	1200	1200	160	160	160	101
2-1/4	1200	1200	1200	1200	200	200	200	134
3	1200	-	-	-	324	-	-	-
3-3/4	1200	-	-	-	502	-	-	-

D. Export packing for coils weighing under 100 pounds. Each coil of rope shall be inclosed by a snug-fitting fiberboard container conforming to type CF, class weather-resistant, variety DW, grade V13c, style RSC of PPP-B-636. Each shipping container shall be provided with a case liner conforming to type I, II, or IV, grade C or F of MIL-L-10547. Case liner closure and sealing shall be in accordance with the appendix to MIL-L-10547. Shipping containers shall be closed by method V of PPP-B-636.

E. Export packing for coils weighing over 100 pounds. Each coil of rope shall be packed in a nailed wood box conforming to class 2, style 4 of PPP-B-621. Each shipping container shall be provided with a case liner conforming to type I, II, or IV, grade C or F of MIL-L-10547. Case liner closure and sealing shall be in accordance with the appendix to MIL-L-10547. The shipping container shall be closed in accordance with the appendix of PPP-B-621.

F. Marking (commercial and export). Commercial markings are acceptable, provided the following information is included:

National stock number
Item description
Quantity (units)
Date of pack
Contract number
Name, address and zip code of manufacturer

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:38Z
Check the source to verify that this is the currenversion before use.

Source of information for nongovernmental association documents.

National Motor Freight Traffic Association, Inc., Agent
National Motor Freight Classification
American Trucking Associations, Inc., Traffic Department
1616 P Street, N.W.
Washington, DC 20036

Uniform Classification Committee, Agent
Uniform Freight Classification
Uniform Classification Committee, Suite 1106
222 South Riverside Plaza
Chicago, IL 60606

MILITARY INTERESTS:

Custodians

Army - GL
Air Force - 82

Review Activities

Army - MD, ME
DSA - IS

User Activity

Navy - YD

CIVIL AGENCY COORDINATING ACTIVITIES:

GSA - FSS

PREPARING ACTIVITY:

Army - GL

Project No. 4020-0276

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.