INCH-POUND

A-A-50057A

August 29, 1989
SUPERSEDING
A-A-50057
September 23, 1983

COMMERCIAL ITEM DESCRIPTION

ROPE, FIBROUS, TENT-LAY

The General Services Administration has authorized the use of this commercial item description in preference to MIL-R-1670.

1. CLASSIFICATION.

1.1 Classification.

Circumference, inch		Diameter	Breaking strength	Length per pound
Min	Max	Inches (approx)	Pounds (min)	Feet (min) 1/
9/16	11/16	3/16	200	70.0
5/8	7/8	1/4	540	50.0
7/8	1-1/8	5/16	900	34.5
1	1-1/4	3/8	1215	24.4
1-3/8	1-5/8	1/2	2385	13.3
1-13/16	2-3/16	5/8	3960	7.4
2-1/16	2-7/16	3/4	4860	6.1
2-3/4	3-1/4	1	8100	3.7
3-1/2	4	1-1/4	12150	2.4

1/ Tolerance of ± 10 percent.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to: Commander, U.S. Army Natick Research, Development, and Engineering Center, ATTN: STRNC-ES, Natick, MA 01760-5014.

AMSC N/A FSC 4020

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:38Z
Check the source to verify that this is the current version before use.

2. SALIENT CHARACTERISTICS

2.1 Description. The rope shall be either a three or a four strand construction and shall be fabricated from manila hemp, sisal, jute or cotton fiber. The rope shall be furnished with either a natural finish or with a mildew resistance treatment conforming to the requirements specified in T-T-616. No material shall be added for the purpose of weighting the rope. The percentage extractable matter by weight shall not exceed 25 percent. The maximum allowable water absorption by weight for jute and cotton rope shall be 25 and 35 percent respectively.

3. QUALITY ASSURANCE

3.1 Certification. The contractor shall certify, and maintain substantiating evidence, that the product offered meets the salient characteristics and requirements of this Commericial Item Description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

3.2 Recycled, reclaimed materials. The contractor is encouraged to use recovered material in accordance with Public Law 94-580 to the maximum extent practicable.

4. PACKAGING

4.1 Put-up. The rope shall be furnished in coils. No piece of rope shall be less than 100 feet. Minimum coil length shall be 3500 feet for 5/8 inch rope, 2200 feet for 3/4 inch rope, 1400 feet for 1 inch rope, and 1200 feet for all other sizes. The ends of the rope shall be whipped or taped to prevent uncoiling. Each coil shall be secured with four ties.

4.2 Packing.

4.2.1 Packing for coils weighing under 100 pounds. Each coil of rope shall be packed in a fiberboard container conforming to RSC-L, grade V13c of PPP-B-636. The container shall be closed by method V as specified in the appendix of PPP-B-636.

4.2.2 Packing for coils weighing over 100 pounds. Each coil of rope shall be packed in a cleated plywood container conforming to oversea type, style A or I, type II load of PPP-B-601. The container shall be closed in accordance with PPP-B-601.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.

4.3 Palletization. When specified, rope packed as specified in 4.2.1, shall be palletized on a 4-way entry pallet in accordance with load type 1a of MIL-STD-147. Pallet types shall be type I (4-way entry), type IV, or type V fabricated from wood groups I, II, III, or IV of MIL-STD-731. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means C and D or film bonding means F or G.

4.4 Marking. In addition to any special marking required by the contract or purchase order, shipping containers and unitized pallet loads shall be marked in accordance with MIL-STD-129.

5. NOTES

5.1 Intended use. The rope is intended for use in the fabrication of tent lines.

5.2 Sources of documents.

5.2.1 Source of government documents. Copies of military and Federal documents are available from:

Naval Publications and Forms Center
ATTN: NPODS
5801 Tabor Avenue
Philadelphia, PA 19120

MILITARY INTERESTS:

Custodians

Army - GL
Air Force - 99

Review Activities

Army - MD, ME
Air Force - 82
DLA - IS

PREPARING ACTIVITY:

Army - GL

(Project 4020-0295)

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:38Z
Check the source to verify that this is the current version before use.