A-A-50058
September 22, 1983

COMMERCIAL ITEM DESCRIPTION

PUNCHING MACHINE, PAPER, ELECTRIC MOTOR DRIVEN

The General Services Administration has authorized the use of this commercial item description in preference to Military Specification MIL-P-43244.

Salient characteristics.

The punching machine shall cleanly and accurately punch a predetermined number of holes of one size at a preset distance from the edge of the stack. Stacks up to 3/8 inches thick shall be punched at one time. Machines shall accomodate up to six sets of punches and dies at one time. Hole sizes, quantities and adjustments shall be changed over the full range of the following by changing punches and dies:

Floor area required (maximum)	41 by 33 inches
Hole punches, diameter (minimum range)	13/32 to 1/2 inches
Hole spacing (minimum range)	0 to 20 inches
Margin adjustment	0 to 1-7/8 inches
Work table, depth	14 $\pm$ 2 inches
Work table, length	34 $\pm$ 2 inches
Work table, height (from floor)	38 $\pm$ 2 inches
Sheet size capacity	26 $\pm$ 2 inches
Weight, net (maximum)	800 pounds

Punching operation shall consist of either direct punching operation by one step operation (by operation of a single switch or release lever) or, when it is the manufacturers practice, by switching the machine on and by subsequent activation of an additional switch, level or release; releasing the head for the punching operation. In either case, the punching head shall return to its topmost position and stop upon completion of the punching stroke. Punching machines shall be suitable for use on either 208 or 220 volts single phase power supply or for the power requirements specified in the contract.

Standard. The punching machine units shall meet the applicable requirements for use as defined in the Standard of the National Fire Protection Association NFPA No. 70 - Natioanl Electric Code.

FSC 3610

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:38Z
Check the source to verify that this is the current version before use.

Certification.

The contractor shall certify that the product offered meets the salient characteristics of this description and conforms to the producers' own drawings, specifications, standards and quality assurance practices and it is the same as the product sold in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under provisions of the contract.

Packaging.

A. Preservation. Each punching machine shall be preserved in accordance with commercial practice to afford adequate protection against corrosion and deterioration.

B. Packaging (commercial and export). Each punching machine shall be packaged in accordance with commercial practice.

C. Commercial packing. Each punching machine shall be packed in a manner to insure carrier acceptance and safe delivery to destination at the lowest transportation rate for such supplies. Containers shall comply with the Uniform Freight Classification or National Motor Freight Classification, as applicable.

D. Export packaging. Each punching machine and parts shall be cleaned, preserved, cushioned and immobilized to afford protection against corrosion, deterioration and physical damage during shipment and storage. Interior fiberboard boxes used for packaging disassembled parts, punches, dies and tools shall conform to class weather-resistant conforming to PPP-B-636.

E. Export packing. Each punching machine shall be packed in a wood cleated plywood box conforming to domestic type style A or J, grade B, type 3 load of PPP-B-601 or a nailed wood box conforming to class 1, style 2 or 4, grade B, type 3 load of PPP-B-621. The contents of the box shall be cushioned, blocked and braced to prevent movement while the box is in transit. Each punching machine shall be covered with a full-height shroud made of waterproof barrier material conforming to class E-2, H-1, H-5, or M-1 of PPP-B-1055. All seams of the shroud shall be sealed with water resistant adhesive. Each shipping container shall be closed and strapped in accordance with the appendix of PPP-B-601 or PPP-B-621, as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.

F. Marking of interior boxes and shipping containers (commercial and export). Commercial marking for interior boxes and shipping containers is acceptable providing the following information is included:

National stock number	Date of packaging (month/year)
Item description	Contract number
Quantity, unit of issue	Name, address and zip code of contractor 1/

1/ Interior boxes do not require this information.

Sources of information for nongovernment association documents.

National Fire Protection Association (NFPA)
Batterymarch Park
Quincy, MA 02169

National Motor Freight Traffic Association, Inc., Agent
National Motor Freight Classification
American Trucking Associations, Inc., Traffic Department
1616 P Street, N.W., Washington, DC 20036

Uniform Classification Committee, Agent
Uniform Freight Classification
Uniform Classification Committee, Suite 1106
222 South Riverside Plaza, Chicago, IL 60606

MILITARY INTERESTS:

Custodians

Army - GL
Air Force 99

Review Activity

Air Force - 84

CIVIL AGENCY COORDINATING ACTIVITY:

GSA-FSS

PREPARING ACTIVITY:

Army - GL

Project No. 3610-0329

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.