A-A-1511
March 4, 1981

COMMERCIAL ITEM DESCRIPTION

CLOCK, WALL
(ELECTRIC, DIGITAL)

The General Services Administration has authorized the use of this commercial item description.

Salient characteristics:

Class and type. The class and type of clock shall be specified in the procurement documents.

Class A clocks shall have 12 hour time displays.
Class B clocks shall have 24 hour time displays.

Type I clocks shall be battery powered. Batteries shall be commercially available, and have a lifetime of at least one full year.
Type II clocks shall draw power from 120 VAC, 60 Hz outlets. The power connection shall be appropriate for use on a standard three-prong single gang outlet.

Safety. The complete wall clock unit being offered shall conform to the applicable requirements of Underwriters Laboratories' (UL) Standard No. 863.
Acceptable evidence of such conformance shall be the UL label, UL listing mark, or certified report from a recognized independent testing laboratory acceptable to the Government, indicating that the clocks being offered have been tested and conform to UL 863.
If any UL requirement or section of a requirement is not applicable to the clocks, the independent testing laboratory shall so state in their report, giving a brief, adequate explanation in each case.
Evidence of conformance shall accompany the bid.

The issue of UL standard in effect on the date of solicitation shall be used to determine compliance with these requirements.

Case. Cases shall be surface type with a concealed mounting that will not interfere with plugging in the clock over a single gang outlet.
Cord openings shall be smoothly rounded.
The overall dimensions of the clock shall be no more than 12-inches wide, 6-inches high, and 4-inches deep.

Time display. Time displays shall be either light emitting diode (LED) or liquid crystal display (LCD) type, at the manufacturer's option.
Numerals shall be at least 2-inches high.
The display shall read constantly in hours and minutes.

Resetting. The clock shall have a simple means of resetting which does not require special tools, removing the clock from the wall or holding the clock with more than one hand.

Accuracy. The clocks shall be accurate to $\pm$ 1.0 seconds per month, at 20° C; and shall not vary more than $\pm$ 4.0 seconds per month at the temperature extremes of -10° C and $+ 50^{\circ}$ C.

Workmanship. The complete wall clock unit shall be of sufficient quality to ensure trouble-free operation for at least the first five years. All component parts shall be compatible, properly fitted and securely attached The clocks shall be free from rough or sharp edges, or other defects which may injure the user, or impair serviceability.

Certification The contractor shall certify that the product offered meets the salient characteristics of this description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices, and is the same product sold in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Regulatory requirements. The manufacturer shall utilize recovered materials to the maximum extent practicable.

FSC 6645

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:14Z
Check the source to verify that this is the current version before use.

Packaging, packing, and marking. The items shall be packaged in accordance with normal commercial practice and packed to assure acceptance by common carrier and provide product protection against loss and damage during multiple shipments, handling, and storage. The shipping container shall be in compliance with National Motor Freight Classification and Uniform Freight Classification. Shipping containers shall be marked as specified in the contract or order.

UL standards are available from Underwriters Laboratories, Inc., Publication Stock, 333 Pfingsten Road, Northbrook, IL 60062.

Preparing activity:

GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:14Z
Check the source to verify that this is the current version before use.