A-A-182
September 23, 1979

COMMERCIAL ITEM DESCRIPTION

BASKET, WASTEPAPER, METAL, OFFICE AND LOBBY

The General Services Administration has authorized the use of this commercial item description in lieu of Federal Specification RR-B-181.

The metal wastepaper baskets covered by this document are intended for use as temporary receptacles for paper waste and small articles of trash. They shall be used in offices or lobbies as applicable.

Salient characteristics:

1. The baskets shall be made of good commercial quality steel not less than 0.0159 inch thick.

2. Top diameters shall be reinforced by a side bead formed tightly around a steel wire which encircles the outside of the vertical wall and is not less than 0.207 inch in diameter.

3. The basket shall rest squarely on a flat surface.

4. The bottom of the waste compartment shall be recessed 0.925 ± .050 inch from the bottom edge of the basket.

5. The basket shall be marked with the name or trademark of the manufacturer.

6. Basket color shall be as specified in the procurement documents.

7. When specified in the procurement documents, lobby baskets shall have hand grips located near the top, 180 degrees apart.

Enamel coating.

1. All basket surfaces shall be cleaned and coated with finishing enamel in accordance with good commercial practice.

2. The film thickness shall be not less than 0.7 mil.

3. When tested as specified in Method A of ASTM D 3359, the coating shall not peel or be removed from the substrate.

Fire hazard. The basket shall minimize any fire hazard resulting from combustion of its contents. If a fire starts in a basket containing not less than 12 ounces per cubic foot of writing paper, carbon paper, newspaper and empty wax or plastic coated milk containers, the basket shall contain the fire without spilling the burning contents onto the floor. When the fire has burned itself out, the only damage to the basket shall be charred or cracked coating.

Workmanship. Baskets shall be free of burrs, sharp edges, runs, wrinkles, blisters, flakes, gritty finish, areas of not film or thin film, faulty construction, and any other defects which affect appearance or serviceability.

TABLE I. Basket dimensions + 1/2 inch

Type	Top diameter	Bottom diameter	Overall height
Office	13	10-1/2	14-1/2
Lobby	16	14	29

FSC 7520

GSA DC-01000195

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:05Z
Check the source to verify that this is the current version before use.

Certification. The contractor shall certify that the product offered meets the characteristics of this description and that the product conforms to the producers own drawnings, specifications, standards and quality assurance practices and is the same product as the product offered for sale in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Recovered Materials. The manufacturer shall utilize recovered materials to the maximum extent practicable.

Packaging, packing, and marking. The wastepaper basket shall be packaged in accordance with normal commercial practice and packed in fiberboard boxes that will assure acceptance by common carrier and provide product protection against loss and damage during multiple shipments, handling and storage. The shipping container shall be in compliance with the National Motor Freight Classification and Uniform Freight Classification. Unit and intermediate packages, as applicable, shall be marked in accordance with normal commercial practice. The shipping containers shall be marked as specified in the contract or order.

ASTM Standards are available from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:05Z
Check the source to verify that this is the current version before use.