INCH-POUND

A-A-2314A
October 8, 2002
SUPERSEDING
A-A-2313
September 27, 1985

COMMERCIAL ITEM DESCRIPTION
FILE, HAND (AMERICAN PATTERN), KNIFE

The General Services Administration has authorized the use of this commercial item description by all federal agencies.


1. SCOPE. This commercial item description covers hand files used for filing acute angles such as in keyways and slots.

2. CLASSIFICATION.

Type I – Bastard-cut
Type II – Second-cut
Type III – Smooth-cut

3. SALIENT CHARACTERISTICS.

3.1 Design. The file shall have a knife cross-section with an included angle between sides of 9-15°, inclusive. Each wide flat double-cut (two sets of parallel cuts on the surface, one set crossing the other.) the thin flat side shall be single-cut (one set of parallel cuts on the surface). The back shall be single-cut or smooth (safe). The file shall be furnished in three types and assorted sizes as shown in section 3.2.



Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any other data which may improve this document should be sent to: General Services Administration, Federal Supply Service, Hardware SuperStore (6FEE), 1500 E. Bannister Rd Bldg. #6, Kansas City, Missouri 64131.

FSC 5110

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:21Z
Check the source to verify that this is the current version before use.

3.2 Dimensions.

Length	Dimensions at Largest Section			Number of Teeth		Allowable Distortion	Allowable Warpage
	A	B	C	Min	Max	Max	Max
In	In	In	In	Per In	Per In	In	Degree
Type I -- Bastard-cut							
6	5/32	1/16	11/16	41	45	0.008	5
8	13/16	1/16	7/8	33	37	0.010	6
10	1/4	1/16	1-1/16	28	32	0.025	7
Type II --Second-cut							
4	7/64	1/32	15/32	60	68	0.006	3
6	5/32	1/16	11/16	52	59	0.008	5
8	3/16	1/16	7/8	42	48	0.010	6
12	1/4	1/16	1-1/16	34	39	0.025	7
Type III -- Smooth-cut							
6	5/32	1/16	11/16	66	73	0.008	5
8	3/16	1/16	7/8	54	60	0.010	6
10	1/4	1/16	1-1/16	43	49	0.025	7

Length Dimensions: Measured from the point (free or front end) to the heel and have a tolerance of +/- 1/8".

Tolerance: Width (A) plus or minus 1/16"; Thickness (B) files 6" in length +/- 1/32"

Files over 6" in length +/- 1/16.

3.3 Material. The file shall be of a carbon alloy steel.

3.4 Tang. Shall be of a conventional shape and size suitable for attachment to a wood handle. Tempered to a maximum hardness of 45 on the Rockwell C scale when tested per ASTM E18. It shall be measured at a point approximately midway of its length and width.

3.5 Teeth. Shall be designed for fast cutting and minimize clogging. Uniformly cut or etched and of uniform height throughout the fully cut portion. Cutting surfaces shall be hardened to a uniform hardness. The distance between the heel and point of the file, excluding the tang, shall be hardened to not greater than 68 nor less than 64 on the Rockwell C scale when tested per ASTM E18. The file shall be free from decarburization and brittleness.

3.6 Marking. The file shall be marked with the name of the manufacturer or with a trademark of such known character that the source of manufacture may be readily determined.

3.7 Workmanship. The teeth of the file shall be well-defined, sharp, and uniform in height and form. There shall be no evidence of rust or other defect which may impair serviceability, durability or appearance.

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:21Z
Check the source to verify that this is the currentversion before use.

4. REGULATORY REQUIREMENTS.

4.1 Recovered Materials. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal acquisition Regulation (FAR).

4.2 Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within the tolerances specified (using conversion tables contained in the latest revision of Federal Standard 376) and all other requirements of this document are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch- pound units, a request should be made to the contracting officer to determine if the product is acceptable.

5. PRODUCT CONFORMANCE.

5.1 Product Conformance. The product provided shall meet the salient characteristics of this Commercial Item Description, conform to the producer's own drawing, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial market. The government reserves the right to require proof of such conformance.

5.2 Responsibility for Inspection. Unless otherwise specified, the contractor is responsible for the performance of all inspection requirements and may use any commercial facilities (including the contractor's own facilities) suitable for performance of the inspection requirements, unless disapproved by the Government. The Government reserves the right to perform any of the inspections deemed necessary to assure the item conforms to the specified requirements.

6. PACKAGING. Preservation, packaging and marking shall be as specified in the contract or order.

7. NOTES. This section contains information of a general or explanatory nature that is not mandatory.

7.1 Source of Documents.

American Society for Testing and Materials (ASTM), PO Box C700, West Conshohocken, PA 19428-2959.

Federal Acquisition Regulation (FAR): Government Printing Office, Superintendent of Documents, Washington DC. 20401-9371.

GSA Specification Section (3FP-E), Suite 8100, 470 L'Enfant Plaza, SW, Washington, DC 20407.

7.2 Ordering data. Purchasers should select the preferred options permitted herein and should include the following information in procurement documents.

a. Title, number, and date of Commercial Item Description.
b. Type
c. Dimensions
d. Packaging requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:21Z
Check the source to verify that this is the current version before use.

7.3 National Stock Numbers (NSN's). A list of NSN's assigned that correspond to this CID. The list may not be indicative of all possible NSN's associated with the CID.

NSN	Length	Dimensions of Cross-Section		
		A	B	C
	In	In	In	In
Type I -- Bastard-cut				
5110-00-234-6563	6	5/32	1/16	11/16
5110-00-234-6566	8	13/16	1/16	7/8
5110-00-234-6569	10	1/4	1/16	1-1/16
Type II -- Second-cut				
5110-00-238-7866	4	7/64	1/32	15/32
5110-00-203-4948	6	5/32	1/16	11/16
5110-00-234-6567	8	3/16	1/16	7/8
5110-00-234-6570	12	1/4	1/16	1-1/16
Type III -- Smooth-cut				
5110-00-203-4552	6	5/32	1/16	11/16
5110-00-203-4553	8	3/16	1/16	7/8
5110-00-203-4554	10	1/4	1/16	1-1/16

7.4 Key words. File, Hand (American Pattern), Knife

MILITARY INTERESTS:
NONE: DoD has no registered interest in revisions and amendments to this Commercial Item Description until further notice.

Preparing Activity:
GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:21Z
Check the source to verify that this is the current version before use.