A-A-235
September 30, 1979

COMMERCIAL ITEM DESCRIPTION

WASTE RECEPTACLE, PLASTIC, WITH LID

The General Services Administration has authorized the use of this commercial item description in lieu of Federal Specification L-W-25.

This commercial item description covers high-density polyethylene waste receptacles with lids in the following capacities: 10, 20, 24, 32, and 44 gallons, as specified.

Salient characteristics:

Receptacles shall be molded in one piece and shall be watertight.

Interior and exterior surfaces shall allow for easy and thorough cleaning.

Volume capacity and color of receptacles shall be as specified in the contract or order.

Receptacles shall have two diametrially positioned handles located near the top edge. Metal handles, when used, shall be corrosion resistant.

Lids shall be molded in one piece and shall have a handle for easy removal. A means shall be provided for locking the lid securely to the receptacle.

Workmanship. Receptacles shall be free from seams, flash, blisters, cracks, chips, sharp fins, sharp edges, lumps, imbedded foreign material, and any sign of corrosion on metal handles.

Receptacles shall show no evidence of cracking, splitting, failure, separation, or deformation when tested as below:

(1) Pour sand or cracked ice into one receptacle in amounts as indicated below. Condition the loaded receptacle at 0 ± 5 degrees F for a period of 12 hours. Drop the loaded receptacle onto a concrete surface from a height of 3 feet, allowing it to strike the bottom edge.

(2) Condition two empty receptacles as described above. One of these receptacles shall be dropped 3 times from a height of 6 feet, striking the bottom edge once and the top edge twice at opposite points. The remaining receptacle shall be placed on its side and weight shall be added to the rim until the sides touch.

Note: The above tests shall commence within 10 seconds after removal from the conditioning chamber.

(3) Fill the receptacle with weights as indicated below and lift 200 times from a flat surface to a height of at least 1 inch, using only the handles for lifting.

Weights to be added for above tests:

Receptacle capacity	Weight to be added
10 gallons	40 pounds
20 gallons	80 pounds
24 gallons	80 pounds
32 gallons	100 pounds
44 gallons	120 pounds

FSC 7240

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:06Z
Check the source to verify that this is the current version before use.

(4) Place a receptacle in an upright position on a six inch horizontally mounted 50 grit sanding belt. Tilt the receptacle to a 45 ± 5 degree angle opposite to the travel of the belt. Secure the receptacle to assure that the same point of contact with the belt is maintained. Add a volume of water equal to 20 percent of the receptacle's capacity. Operate the belt at 60 surface feet per minute or less until 600 feet of abrasion occurs. Seepage or leakage prior to 600 feet of abrasion shall constitute failure of this test. The 10 gallon receptacle is not required to be tested for abrasion.

Certification. The contractor shall certify that the product offered meets the salient characteristics of this description, and that the product conforms to the producer's own drawings, specifications, standards and quality assurance practices and is the same product offered for sale in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Recovered materials. The manufacturer shall utilize recovered materials to the maximum extent practicable.

Packaging, packing, and marking. Each receptacle shall be packaged in accordance with commercial practice and packed in fiberboard boxes that will assure acceptance by common carrier and provide product protection against loss and damage during multiple shipments, handling, and storage. The shipping containers shall be in compliance with National Motor Freight Classification and Uniform Freight Classification. Shipping containers shall be marked as specified in the contract or order.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:06Z
Check the source to verify that this is the current version before use.