[METRIC]
A-A-2717
August 16, 1991

COMMERCIAL ITEM DESCRIPTION

CLOCKS, WALL (QUARTZ CRYSTAL-BATTERY OPERATED)

The General Services Administration has authorized the use of this commercial item description as a replacement for Interim Federal Specification GG-C-001072 which has been canceled.

This description covers quartz crystal, battery powered wall clocks, furnished in two dial face diameters and three dial face types; as specified.

Size I - 20 cm
Size II - 30 cm

Type A - 12 Hour
Type B - 24 Hour (Single ring)
Type C - 24 Hour (Double ring)

Salient characteristics.

General. Clocks shall be completely assembled and ready for operation, requiring only the insertion of the proper dry cell battery(preferably alkaline). It shall not be necessary to perform periodic adjustments to obtain the timing accuracy specified herein.

Tolerances. Tolerances on dial face diameters shall be ± 2 cm.

Mounting. The clock unit shall be equipped with a concealed hanging device, suitable for hanging the clock flush with the wall.

Cases. Cases shall be of the surface type, fabricated of plastic and molded in either brown, bronze or white.

Dials.

Type A & C - Dial shall register 12 hours in one revolution of the hour hand taking 12 hours and one hour in one revolution of the minute hand. All numerals for each hour shall appear on the dial, with the numeral 12 appearing at the top of the dial.

Type B - Dial shall register 24 hours in one revolution of the hour hand taking 24 hours and one hour in one revolution of the minute hand. The numerals indicating the hours 00, 4, 8, 12, 16 and 20 shall be dimensionally higher than the remaining numerals in accordance with the manufacturer's standard practice. The numeral 00 shall appear at the top of the dial.

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

FSC 6645

Source: https://assist.dla.mil -- Downloaded: 20260-26T08:25Z
Check the source to verify that this is the current version before use.

Type C - The dial face shall have an outer ring marked 1-12 and an inner ring marked 13-24, indicating the hours, in accordance with the manufacturer's standard practice. The numerals 12 and 24 shall appear at the top of the dial.

General. Dials will be white with black arabic numerals and minute marks.

Dial covers. Dial covers shall be of either glass or non-yellowing plastic and be securely positioned to prevent accidental separation.

Hands. Minute and hour hands shall be black. The second hand shall be a distinguishing color and shall be at least 7 cm long. The minute hand shall be at least 8.5 cm long, measured from the center of the dial. The hour hand shall be 45 to 85 percent as long as the minute hand.

Resetting. The clocks shall have a simple means of resetting.

Accuracy. The clocks shall be accurate to ± 1 second per 72 hours.

Workmanship. The units shall be of sufficient quality to ensure trouble-free operation for one year. The clocks shall operate without objectionable noise or hum, and shall not develop such from normal usage. All components shall be compatible, properly fitted and securely attached. The clocks shall be free from rough edges or other defects which may injure the user, impair the smooth operation of the clock, or impair serviceability.

QUALITY ASSURANCE PROVISIONS.

Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein.

Sampling for inspection and tests. Shall be in accordance with MIL-STD-105. Inspection level II, AQL 4.0 percent defective for visual inspection. Inspection level S-2, AQL shall not exceed 4.0 percent defective for testing. For purposes of sampling a lot shall consist of all clocks manufactured under the same conditions at essentially the same time.

Regulatory requirements. In accordance with Section 23.403 of the Federal Acquisition Regulations, the Government's policy is to acquire items composed of the highest percentage of recovered materials practicable, consistent with maintaining a satisfactory level of competition without adversely affecting performance requirements or exposing the supplier's employees to undue hazards from the recovered materials.

Preservation, packaging, packing, labeling and marking. The preservation, packaging, packing, labeling and marking shall be as specified in the contract or purchase order.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:25Z
Check the source to verify that this is the current version before use.

Copies of MIL-STD-105 may be obtained from the Naval Publications and Forms Center, 5801 Tabor Avenue, Philadelphia, PA 19120.

Note: Purchaser shall specify by Type and NSN.

Size I,	Type A	NSN 6645-01-046-8848
Size I,	Type B	NSN 6645-01-342-5313
Size II,	Type A	NSN 6645-01-046-8849
Size II,	Type B	NSN 6645-01-342-5314
Size II,	Type C	NSN 6645-01-342-8199

PREPARING ACTIVITY:

GSA - FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:25Z
Check the source to verify that this is the current version before use.