COMMERCIAL ITEM DESCRIPTION

# DIE AND COLLET
# (TWO-PIECE DIES WITH COLLETS)

The General Services Administration has authorized the use of this commercial item description in lieu of Federal Specification GGG-D-296.

This commercial item description covers adjustable, rectangular, two-piece dies with collets.

Salient characteristics:

Collet. The collet shall consist of a cap and guide made of steel.

Cap. The cap shall be a cylindrical-shaped item with a rectangular opening on one end, beveled to seat the dies, and an internal thread on the other end to accommodate the guide.

Guide. The guide shall be externally threaded to fit the cap and have an internal opening for guiding the die onto the pipe.

Dies. The die halves shall fit into the beveled recesses in the cap and be adjustable by setscrews protruding through the cap sides at the ends of the rectangular opening. The material of the dies shall be either carbon or high-speed steel, hardened to Rockwell C 57-63 or C 61-65, respectively. The cutting lands of the threads shall show no evidence of partial or total decarbonization.

Sizes. The die and collets shall be furnished in right-hand threads in the following thread sizes and collet diameters as shown below for the National Stock Number (NSN) specified.

| National Stock Number (NSN) | Thread size, pitch, and series | Nominal outside diameter of collet (inches) |
|---|---|---|
| 5136-00-187-7173 | 10-24 NC | 1-1/4 |
| 5136-00-187-7176 | 12-24 NC | 1-1/4 |
| 5136-00-223-6638 | 9/16-12 NC | 2-3/4 |
| 5136-00-223-6640 | 9/16-18 NF | 2-3/4 |
| 5136-00-223-6641 | 5/8-18 NF | 2-3/4 |
| 5136-00-223-6642 | 3/8-24 NF | 2-3/4 |
| 5136-00-223-6647 | 1-14 NS | 2-3/4 |
| 5136-00-223-6649 | 5/16-24 NF | 2 |
| 5136-00-226-8129 | 1-1/4-7 NC | 4 |
| 5136-00-226-8130 | 1-1/8-7 NC | 4 |
| 5136-00-226-8134 | 1/2-20 NF | 2-3/4 |
| 5136-00-226-8136 | 6-32 NC | 1-1/4 |
| 5136-00-226-8138 | 5-40 NC | 1-1/4 |
| 5136-00-226-8139 | 4-48 NF | 1-1/4 |
| 5136-00-226-8140 | 4-40 NC | 1-1/4 |
| 5136-00-226-8141 | 3-48 NC | 1-1/4 |
| 5136-00-226-8142 | 2-56 NC | 1-1/4 |
| 5136-00-240-1513 | 1/4-20 NC | 1-1/4 |
| 5136-00-243-1535 | 1-8 NC | 2-3/4 |
| 5136-00-243-1536 | 1-1/8-7 NC | 4-1/2 |
| 5136-00-243-1538 | 7/8-9 NC | 2-3/4 |
| 5136-00-243-1539 | 1/2-13 NC | 2-3/4 |
| 5136-00-243-1540 | 5/8-11 NC | 2-3/4 |
| 5136-00-243-1542 | 7/16-14 NC | 2-3/4 |
| 5136-00-243-1543 | 1/4-20 NC | 2-3/4 |
| 5136-00-243-1544 | 5/16-18 NC | 2-3/4 |
| 5136-00-243-1545 | 1/4-28 NF | 1-1/4 |
| 5136-00-264-3776 | 7/8-14 NF | 2-3/4 |
| 5136-00-273-0148 | 3/4-16 NF | 2-3/4 |
| 5136-00-273-0158 | 1-8 NC | 4 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:07Z
Check the source to verify that this is the current version before use.

| National Stock Number (NSN) | Thread size, pitch, and series | Nominal outside diameter of collet (inches) |
|---|---|---|
| 5136-00-542-4220 | 10-32 NF | 1-1/4 |
| 5136-00-542-4221 | 14-20 NS | 1-1/4 |
| 5136-00-542-4222 | 12-28 NF | 1-1/4 |
| 5136-00-542-4223 | 5-44 NF | 1-1/4 |
| 5136-00-542-4225 | 3-56 NF | 1-1/4 |
| 5136-00-542-4227 | 2-64 NF | 1-1/4 |
| 5136-00-580-7686 | 3/8-26 NC | 2-3/4 |
| 5136-00-580-7687 | 3/4-10 NC | 2-3/4 |
| 5136-00-585-2381 | 7/16-14 NC | 2 |
| 5136-00-585-2382 | 7/16-20 NF | 2 |
| 5136-00-585-2412 | 1/2-13 NC | 2 |
| 5136-00-585-2413 | 1/2-20 NF | 2 |
| 5136-00-585-2419 | 5/16-18 NC | 2 |
| 5136-00-585-2421 | 3/8-16 NC | 2 |
| 5136-00-595-8895 | 3/32-48 NS | 1-1/4 |
| 5136-00-595-8898 | 8-32 NC | 1-1/4 |
| 5136-00-595-8899 | 4-36 NS | 1-1/4 |
| 5136-00-618-0516 | 3/8-24 NF | 2 |
| 5136-00-689-9124 | 1-1/4-12 NF | 4 |
| 5136-00-689-9125 | 1-1/8-12 NF | 4 |
| 5136-00-689-9126 | 8-36 NF | 1-1/4 |
| 5136-00-689-9127 | 6-40 NF | 1-1/4 |
| 5136-00-889-2090 | 1/4-20 NC | 2 |
| 5136-00-889-2091 | 1/4-28 NF | 2 |

Marking. The dies shall be marked in a legible and permanent manner with the manufacturer's name or trade mark, the thread size, and "HS," "HSS," or "High Speed" to indicate high speed steel, if applicable.

Workmanship. All dies shall be free from imperfections which may affect their appearance, serviceability, or durability.

Certification. The contractor shall certify that the product offered meets the salient characteristics of this description and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices and is the same product offered for sale in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Recovered materials. The manufacturer shall utilize recovered materials to the maximum extent practicable.

Preservation, packaging, packing, and marking. The dies and collets shall be preserved and packaged in accordance with normal commercial practice and packed to assure acceptance by common carrier and provide product protection against loss and damage during multiple shipments, handling, and storage. The shipping containers shall be in compliance with the National Motor Freight Classification and Uniform Freight Classification. Marking shall be as specified in the contract or order.

Note: Diestocks for these dies and collets are covered by CID A-A-415.



GSA DC-01001759

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:07Z
Check the source to verify that this is the current version before use.