NOT MEASUREMENT SENSITIVE


MIL-P-14631/14A
5 February 1992
SUPERSEDING
MIL-P-14631/14
30 September 1971

MILITARY SPECIFICATION SHEET

PLATE, AUTOMOBILE, INDIVIDUAL; LIEUTENANT GENERAL, U.S. ARMY

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-P-14631.



MATERIAL:
- BASE: Aluminum
- STAR: Brass

DIMENSIONS:
- BASE:
  - HEIGHT: (Overall): 6 inches ± 1/16 inch (15.24 cm ± 0.16 cm)
  - WIDTH: 9 inches ± 1/16 inch (22.86 cm ± 0.16 cm)
  - THICKNESS: .064 inch ± .003 inch (0.162 cm ± 0.007 cm)
- STAR:
  - DIAMETER (Circumscribed): 1-7/8 inches (4.76 cm) (REF)
  - THICKNESS Thickest Point: .155 inch ± .020 inch (0.393 cm ± 0.050 cm)

FSC 8345

AMSC N/A

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:37Z
Check the source to verify that this is the current version before use.

FINISH:
PLATE BASE: Enameled (See note 1.)
EMBOSSED STAR: Nickel plated, Rhodium plated, Mirror-like polished.

NOTES:
1. Enamel color for Dash No. 1 and 2 shall match the chip number of FED-STD-595 as follows or the standard sample.

DASH NO.	COLOR/CHIP NO.
1	Scarlet (11350)
2	Maroon (10049)

2. Star position and details for stud, wing nut and registration prongs shall be as shown on figure 1 (DWG 4-4-81).

Custodian:
Army - IH

Preparing Activity:
Army - IH

Review Activity:
DLA - CT

(Project No. 8345-0191

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:37Z
Check the source to verify that this is the current version before use.