MIL-R-36967 (DSA-DM)
3 May 1973

MILITARY SPECIFICATION

RUBBER STAMP, FIXED AND REMOVABLE TYPE,
Department of Defense,
Surveillance Inspection, Medical Service

This limited coordinated Military Specification has been prepared by the Defense Personnel Support Center based upon currently available technical information, but it has not been approved for promulgation as a coordinated Military specification. It is subject to modification. However, pending its promulgation as a coordinated Military specification, it may be used in procurement.

1. SCOPE

1.1 This specification covers one type of rubber stamp principally to be used on storage of nonperishable subsistence.

2. APPLICABLE DOCUMENTS

2.1 Specifications, standards and drawing. The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

SPECIFICATIONS

Federal

PPP-T-76	Tape, Pressure-Sensitive Adhesive Paper (for Carton Sealing).
MMM-A-250	Adhesive, Water-Resistant (for Sealing Waterproof Paper).
PPP-B-566	Boxes, Folding, Paperboard.
PPP-B-585	Boxes, Wood, Wirebound.
PPP-B-601	Boxes, Wood, Cleated-Plywood.
PPP-B-621	Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636	Box, Fiberboard.
PPP-B-676	Box, Setup.

FSC 7520

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:40Z
Check the source to verify that this is the current version before use.

STANDARDS

Federal

FED-STD-66	Steel: Chemical Composition and Hardenability.
FED-STD-601	Rubber, Sampling and Testing.

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	Marking for Shipment and Storage.

DRAWING

Defense Personnel Support Center (DPSC)

20528	Rubber Stamp, Fixed and Removable Type, Department of Defense, Surveillance Inspection, Medical Service.

(Copies of specifications, standards and drawing required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publication. The following publication forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposals shall apply.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D2016-65	Standard Methods of Test for Moisture Content of Wood.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pa. 19103.)

3. REQUIREMENTS

3.1 Material. Material shall be of the highest quality throughout. Materials not definitely specified shall be of the quality normally used by the manufacturer for rubber stamps, provided the completed item complies with all provisions of this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:40Z
Check the source to verify that this is the current version before use.

3.1.1 Wood. The wood for the handle shall be a close-grained and straight-grained hard wood.

3.1.2 Rubber. The rubber for the stamp shall be Buna-N-Rubber in accordance with the manufacturer's commercial practice, except the rubber shall have a durometer hardness of 50 ± 5 when tested as specified in 4.4.1.

3.1.3 Corrosion-resisting steel. Corrosion-resisting steel shall conform to type 302 of FED-STD-66.

3.2 Design. The stamps shall conform to the design and dimensions shown on DPSC Drawing 20528.

3.3 Construction. The handle and base of the stamp shall be formed of one piece of wood as specified in 3.1.1. The wood shall be cut so that the grain runs in a vertical direction from the base to the top of the handle. The moisture content of the formed handle shall not exceed 14 percent prior to finishing, when tested as specified in 4.4.2. The rubber die mats shall be fabricated of Buna-N-Rubber as specified in 3.1.2. The face of the stamp shall be lettered as follows: 'INSPECTED' / MIL. The letters shall be routed to a depth of 0.125 inch, and shall be American Type Founders, Inc., Regular News Gothic, 24 point. Six 24-point metal troughs, constructed of AISI 302 stainless steel conforming to FED-STD-66, or chrome-plated brass, shall be vulcanized solidly into the face of the rubber stamp at such height that the rubber type numerals and letters (NSN 7520-00-809-9200 and NSN 7520-00-823-7923) shall be level with the printing face of the stamp. The rubber numerical and alphabetical characters shall fit into the trough in such a manner that they will remain in position during use. Two metal troughs shall be located side by side at the bottom of the stamp with a separation between them. Each of these troughs shall be constructed to accommodate seven rubber numerals or letters. Two troughs, one on each side of 'MIL', shall accommodate five rubber numerals or letters, and one trough, located above 'INSPECTED', shall accommodate five rubber numerals or letters. The trough at the top of the stamp shall accommodate 14 rubber numerals or letters. The rubber face shall be securely joined to the wooden base with alcohol-resistant glue, and eight steel nails, 3/4 inch long. When tested as specified in 4.4.3 for alcohol resistance, the separation between the handle and the stamp mat shall not exceed 1/4 inch.

3.4 Finish. Handle of the stamp shall be stained in accordance with the manufacturer's commercial practice and shall be coated

Source: https://assist.dla.mil -- Downloaded: 202610-21T09:40Z
Check the source to verify that this is the current version before use.

with an alcohol-resistant varnish. When tested as specified in 4.4.3, no evidence of softening of the varnished surfaces shall be allowed.

3.5 Marking for identification. The manufacturer shall permanently and legibly indent his name or readily identifiable trademark on the handle of each stamp. In addition, each stamp shall have a four-digit serial number indented on the right of the handle base and the word "Front" indented on the front of the stamp in white or silver block letters. Serial numbers shall be as specified (see 6.1). The serial numbers shall be not less than 1/4 inch in height.

3.6 Workmanship. Workmanship shall be first class throughout. Wood and metal components shall be free of rough or sharp edges. Wood components shall have no loose grain, cracks or splinters. Pointed ends of nails shall not protrude through the block. Rubber components shall be free of splits, chipped edges or tears.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Records. Records of examinations and tests performed by or for the contractor shall be maintained by the contractor and made available to the Government, upon the Government's request, at any time, or from time to time, during the performance of the contract and for a period of 3 years after delivery of the supplies to which such records relate.

4.1.2 Inspection. Inspection, as used in this specification, is defined as both examination (such as visual or auditory investigation without the use of special laboratory appliances or procedures) and testing (determination by technical means of physical and chemical properties) of the item.

4.1.3 Certificate of quality. Certificate of quality, supplied by the manufacturer of the steel, may be furnished in lieu of actual performance of such testing by the contractor, provided lot

Source: https://assist.dla.mil -- Downloaded: 202610-21T09:40Z
Check the source to verify that this is the current version before use.

ii ... for Guidelines for Levels of Rehabilitation ... 25

identity has been maintained and can be demonstrated to the Government. The certificate shall include the name of the contractor, the contract number, the name of the manufacturer or supplier, the NSN, the item identification, the name of the material, the lot number, the lot size, the sample size, the date of testing, the test method, individual test results, and the specification requirements.

4.2 Sampling.

4.2.1 For examination. Sampling for examination shall be conducted in accordance with MIL-STD-105 and Table I. The unit of product for inspection purposes shall be the rubber stamp.

Table I Sampling for examination

	Inspection level	AQL (percent defective)
For visual examination		
Major defects	II	1.0
Minor defects	II	2.5
For dimensional examination	S-1	2.5

4.2.2 For tests. Tests shall be conducted in accordance with MIL-STD-105 and Table II. The unit of product for testing purposes shall be the rubber stamp or handle as indicated.

Table II Sampling for tests

Characteristic	Unit of product	Requirement	Test procedure	Inspection level	AQL
Rubber hardness	Stamp	3.1.2	4.4.1	S-1	*
Wood moisture content	Handle	3.3	4.4.2	S-1	2.5
Mat retention	Stamp	3.3	4.4.3	S-1	*
Varnish softening	Stamp	3.4	4.4.3	S-1	*

* Acceptance number shall be zero regardless of lot size.

4.3 Examination. The rubber stamp shall be examined to determine compliance with all requirements contained in this specification.

4.3.1 Classification of defects. Examination shall be conducted in accordance with the classification of defects shown in Table III. Examination shall not be restricted to the classified possible defects listed in the table.

Source: https://assist.dla.mil -- Downloaded: 202610-21T09:40Z
Check the source to verify that this is the current version before use.

Table III Classification of defects

Categories	Defects
Major	
101	Not free of sharp edges or burrs.
102	Handle not free of protruding sharp ends of nails.
103	Rubber face not free of tears, splits or chipped edges.
104	Wood not free of cracks, loose grain, splinters or chipped corners.
105	Metal troughs not properly secured in rubber face.
106	Metal troughs not sized to fit rubber numerals or letters.
107	Serial number missing or illegible.
Minor	
201	Finish not free of rough surfaces, chipping or blisters.
202	Handle not one piece, not close grain; grain not vertical or not free of knots.
203	Nail missing.
204	Identification missing, not legible or not located as specified.
205	Word "Front" missing, or not located as specified.

4.3.2 Dimensional examination. The rubber stamp shall be examined for defects in dimensions. Any dimension not within the specified limits shall be classified as a defect.

4.4 Tests. Tests shall be conducted to determine compliance with specification requirements.

4.4.1 Rubber hardness. The durometer hardness of rubber shall be determined by method 3021 of Federal Test Method Standard No. 601.

4.4.2 Moisture content of wood. The moisture content of wood shall be determined in accordance with ASTM D2016 prior to finishing. The lot shall be all handles prepared under the same conditions, stored as a group, and offered for inspection at one time. The unit of product shall be one handle prior to finishing. When testing is performed by the electric moisture meter method, three determinations shall be made on each sample unit. The average of the three determinations shall be the moisture content of the sample unit.

4.4.3 Mat retention test. After the handle of the stamp has been finished, and the die mat has been glued to the handle, but prior to application of nails, the stamp shall be immersed in a solution of absolute ethyl alcohol 40 $\pm$ 2 percent and water 60 $\pm$ 2

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:40Z
Check the source to verify that this is the current version before use.

percent. The stamps shall be immersed so that not less than 1/4 inch of handle is covered. The stamp shall be removed after one minute. The stamp handle shall be clamped with the mat parallel to the floor and a one-pound weight suspended from the edge of the rubber die mat for 30 seconds by means of a clamp.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be Level A or C as specified (see 6.1).

5.1.1 Unit of issue. One rubber stamp, as specified, constitutes one unit of issue.

5.1.2 Packaging quantities. The number of units of issue indicated in Table IV shall be packaged in each unit, intermediate and exterior container, as applicable, for the required level of protection specified in the procurement document.

Table IV Packaging quantities

Unit package	Intermediate package	Exterior container
1 unit	12 units	144 units

5.1.2.1 Packing variation permitted. If the required number of units in the entire shipment is less than the number of units specified to be overpacked in an exterior container, such units may be packed in an exterior container of suitable size and design, acceptable to a common carrier, which shall insure safe delivery to destination.

5.1.3 Level A.

5.1.3.1 Unit package. Unit package shall be a box of appropriate size and design constructed in accordance with PPP-B-566 or PPP-B-676, except commercial colors will be acceptable. Closure shall be adequate to prevent accidental opening under normal handling.

5.1.3.2 Intermediate package. Intermediate package shall be a box of appropriate size and design constructed in accordance with PPP-B-636, type CF, class weather-resistant. Boxes shall be closed by taping the top and bottom flaps with 2-inch wide tape conforming to PPP-T-76. Closing of bottom flap with adhesive conforming to MMM-A-250 or metal stitches is permitted.

Source: https://assist.dla.mil -- Downloaded: 202610-21T09:40Z
Check the source to verify that this is the currentversion before use.

5.1.4 Level C. Units shall be packaged in standard commercial containers of the size and kind commonly used, which will afford the degree of protection required for shipment and use of the product for its intended purpose.

5.2 Packing. Packing shall be Level A, B or C as specified (see 6.1).

5.2.1 Level A.

5.2.1.1 Exterior container. Exterior container shall be designed for a type 2 load and constructed in accordance with PPP-B-585, class 3, style 3; PPP-B-601, overseas type; PPP-B-621, class 2; or PPP-B-636, class weather-resistant, grade V3c. Closure and strapping shall be as specified in the appendix of the applicable box specification. Special requirements of applicable table shall apply for PPP-B-636 box.

5.2.2 Level B.

5.2.2.1 Exterior container. Exterior container shall be designed for a type 2 load and constructed in accordance with PPP-B-585, class 1, style 3; PPP-B-601, domestic type; PPP-B-621, class 1; or PPP-B-636, class domestic. Closure shall be as specified in the appendix of the applicable box specification. Fiberboard box shall be closed by method II of PPP-B-636. Special requirements of applicable table shall apply for PPP-B-636 box.

5.2.3 Level C. The subject commodity shall be packed in substantial commercial containers of the type, size and kind commonly used for the purpose, so constructed as to insure acceptance and safe delivery by common or other carriers, at the lowest rate, to point of delivery called for in the contract or purchase order.

5.3 Marking.

5.3.1 Interior packages. Each unit package and each intermediate package shall be marked in accordance with MIL-STD-129. When labels are utilized, waterproofing shall be required only when applicable carton is fabricated of water-resistant material. Contract or purchase order number and name of contractor shall be shown.

5.3.2 Exterior container. Exterior container shall be marked in accordance with MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 202610-21T09:40Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

a. Title, number and date of this specification.
b. National Stock Number (NSN).
c. Serial number required for stamp.
d. Selection of applicable levels of packaging and packing (see 5.1 and 5.2).

6.2 This specification does not cover all types, classes, grades or sizes of the commodity indicated by the title of this specification, or those which are commercially available, but is intended to cover the type which is normally procured to meet Military requirements.

6.3 This specification covers the following item shown in the Federal Supply Catalog:

National Stock No.	Item Identification
7520-00-817-2649	RUBBER STAMP, FIXED AND REMOVABLE TYPE, Department of Defense, Surveillance Inspection, Medical Service

Custodians:
Army - MD
Navy - MS
Air Force - 03

Review activities:
Army - MD
Navy - MS
Air Force - 03

Preparing activity:
Defense Supply Agency - DM

Project No. 7520-A150

Review information is current as of the date of this document. For future coordination of changes to this document, draft circulation should be based on the information in the current DODISS.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:40Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No 22-R255

INSTRUCTIONS. The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers, vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE
MIL-R-36967 (DSA-DM)

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A
☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?
☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 68 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 202610-21T09:40Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEFENSE SUPPLY AGENCY
DoD - 304



OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
Defense Personnel Support Center
ATTN: DPSC-ATT
2800 South 20th Street
Philadelphia, Pa. 19101

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:40Z
Check the source to verify that this is the current version before use.