NOT MEASUREMENT SENSITIVE

MIL-D-3943/123B
24 June 1994
SUPERSEDING
MIL-D-3943/123A
24 October 1988

MILITARY SPECIFICATION SHEET

DECORATION, SUPERIOR CIVILIAN SERVICE AWARD, ARMY

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-D-3943.



OBVERSE



REVERSE

DASH NO.
-1: Regular Size
-2: Miniature Size

MATERIAL: Red Brass

FINISH: Oxidized, Relieved, Polished Highlights and shall match TIOH Metal Finish Chip Number 5.

DIMENSIONS:
HEIGHT (Including Lug):
-1: 1-1/2 inch (3.81 cm) (REF)
-2: 3/4 inch (1.91 cm) (REF)

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil - Downloaded: 2026-10-17T00:55Z
Check the source to verify that this is the current version before use.

DIAMETER:
-1: 1-3/8 inch (3.49 cm) (REF)
-2: 5/8 inch (1.59 cm) (REF)

THICKNESS (At Thickest Point):
-1: 0.150 inch ± 0.010 inch (0.381 cm ± 0.025 cm)
-2: 0.075 inch ± 0.010 inch (0.191 cm ± 0.025 cm)

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Decoration set shall consist of a regular size medal, a service ribbon and a lapel button all packaged in a presentation case conforming to MIL-C-14633, Type VIII, Style 6 with a Class 1 or 1A pad.

3. The ribbon for the pendant drape and service ribbon shall conform to MIL-R-11589/332.

4. The lapel button shall conform to MIL-L-11484/159.

Custodians:
Army - IH

Review activities:
DLA - CT

Preparing activity:
Army - IH

(Project No. 8455-0764)

Source: https://assist.dla.mil --Downloaded: 2026-10-17T00:55Z
Check the source to verify that this is the current version before use.