This document has been approved for public release and sale; its distribution is unlimited.


MIL-C-24404/3(SHIPS)
1 September 1971
SUPERSEDING
NAVSHIPS DWG. 9000-88106-73144

MILITARY SPECIFICATION SHEET

CONNECTION BOX, 15 FEET SUBMERSIBLE, FOR DEGAUSSING CABLES


(SYMBOL NUMBERS 479.1 AND 479.2)

The complete requirements for procuring the connection boxes described herein shall consist of this document and the latest issue of Specification MIL-C-24404(SHIPS).



FSC 1075

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T21:50Z
Check the source to verify that this is the current version before use.



Source: https://assist.dla.mil -- Downloaded: 2026-10-19T21:50Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

1. Connection boxes shall be 60 terminal as specified in table I.
2. Terminals shall conform to table II and shall accommodate the wire sizes specified in table I.
3. The symbol numbers of Drawing 9000-88106-73144 have been replaced by this specification sheet as follows:

Specification sheet	Drawing 9000-88106-73144
479.1	479
479.2	479

Table I - Assembly data.

Symbol number	Number of 2 conductor terminals	Terminal wire size C.M.	Terminal (see figure 15)	Terminal strip	Terminal strip and terminals assembly Military part no.	Enclosure Military part no. M24404/3
479.1	60	6,500 to 13,090	See table II	Figure 9	M24404/1-002	-001
479.2	60	14,000 to 60,090		Figure 10	M24404/1-003	-001

Table II - Stud terminals dimensions.

Symbol number	Wire size	C (inches)	D thread	E (inches)	F	G	H
479.1	12-8 AWG	1	1/4-20UNC-2	1-13/16	Use of pin is optional		
479.2	8-2 AWG	1-1/8	3/8-16UNC-2	2-1/2			

Preparing activity:
Navy - SH
(Project 1075-N021)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T21:50Z
Check the source to verify that this is the current version before use.