INCH-POUND
MIL-F-24402/5
3 April 1990

MILITARY SPECIFICATION SHEET

FILTER INDICATORS, DIFFERENTIAL PRESSURE, HYDRAULIC

This specification is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-F-24402.

CLASSIFICATION. Filter differential pressure indicators covered by this specification sheet shall be designated using part or identifying numbers (PIN) as follows:

M	24402	/5	-G150
Prefix to indicate an item identified by inch-pound units	Specification number	Applicable specification sheet	Dash number

Examples: M24402/5-G150 is for a gauge-type indicator with a minimum range of 150 lb/in^2 differential.

M24402/5-M45 is for a mechanical pop-up indicator with an actuation pressure of 45 lb/in^2 differential.

DIFFERENTIAL PRESSURE INDICATOR FORM. The dash number for indicators consists of a letter designating the indicator form followed by a number representing the range or actuating pressure of the indicator.

GAUGE FORM INDICATORS. Gauge form indicators shall be designated by the following dash numbers:

-G150 Gauge shall have a minimum range of 30 to 150 lb/in^2 differential.

AMSC N/A FSC 4330
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-19T21:49Z
Check the source to verify that this is the current version before use.

MECHANICAL FORM INDICATORS. Mechanical indicators shall be designated by the following dash numbers:

-M45 Actuation pressure shall be 45 ± 5 lb/in^2 differential
-M90 Actuation pressure shall be 90 ± 10 lb/in^2 differential

ELECTRICAL FORM INDICATORS. Electrical form indicators with mechanical pop-up indicator shall be designated by the following dash numbers:

-E45 Actuation pressure shall be 45 ± 5 lb/in^2 differential
-E90 Actuation pressure shall be 90 ± 10 lb/in^2 differential

PART NUMBER CROSS REFERENCE. Table I provides a cross-reference between old (MIL-F-24402D and earlier) and new part numbers.

TABLE I. Cross reference of part numbers.

New part number	Old part numbers	
(Fatigue rated)	(Fatigue rated)	(Non-fatigue rated)
M24402/5-E90	M24402 form E-3	M24402 form E-0
M24402/5-E45	-	-
M24402/5-G150	M24402 form G-3	M24402 form G-0
M24402/5-M90	M24402 form M-3	M24402 form M-0
M24402/5-M45	-	-

SUBSTITUTION OF ASSEMBLIES. Indicators with new part numbers may be substituted for corresponding indicators with old part numbers as shown in table I. Only indicators with old part numbers that are fatigue rated may be substituted for indicators with new part numbers.

REQUIREMENTS

(a) Configuration. The indicators shall comply with the envelope dimensions shown on figure 1.

(1) Male gland dimensions. The male gland shall comply with the dimensions shown on figure 2.
(2) Seals. The O-rings and backup ring specified on figure 2 shall be supplied already assembled onto the indicator.
(3) Mounting screws. When acquired separately from a filter housing, differential pressure indicators shall be provided with four mounting screws. The mounting screws shall be NAS 1351-4LE*P where * is the length of the cap screw in sixteenths of an inch. Length of cap screw shall be selected to provide between 3/8 and 1/2 inch thread engagement.

Source: https://assist.dla.mil -- Downloaded: 202610-19T21:49Z
Check the source to verify that this is the currenversion before use.

(b) Maximum rated operating pressure. The indicators shall have a rated operating pressure of 3000 lb/in^2.

Preparing activity:
Navy - SH
(Project 4330-N057-05)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T21:49Z
Check the source to verify that this is the current version before use.





FIGURE 1. Pressure indicator envelope dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T21:49Z
Check the source to verify that this is the current version before use.





DETAIL A

FIGURE 2. Male gland dimensions.

Source: https://assist.dla.mil -- Downloaded: 202640-19T21:49Z
Check the source to verify that this is the current version before use.