INCH-POUND

MIL-F-24402/5A(SH)
AMENDMENT 1
10 April 1995

MILITARY SPECIFICATION SHEET

FILTER INDICATORS, DIFFERENTIAL PRESSURE, HYDRAULIC

This amendment forms a part of Military Specification MIL-F-24402/5A(SH), dated 10 February 1992, and is approved for use by the Naval Sea Systems Command, Department of the Navy and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

5.1(c): Delete and substitute:

"(c) Mounting screws. The mounting cap screws may be NAS 1351N4H* where * is the length of the cap screw in sixteenth of an inch. Length of the cap screw shall be selected to provide a thread engagement of between 3/4 to 1-1/4 times the diameter of the cap screw."

Add as new paragraph 5.4:

"5.4 Indicators for logistic support. When the differential pressure indicators are procured as separate items, an instruction sheet shall be packed with each indicator and shall contain as a minimum the following statement.

" Installation information. For mounting screw material and torque requirements see applicable filter assembly drawing or NAVSEA S9086 S4-STM-000, Naval Ships' Technical Manual Chapter 556 (Hydraulic Equipment), Section 7. The length of the cap screw for mounting this indicator is (indicate length which will provide an engagement between 3/4 to 1-1/4 time the diameter of the cap screw.)"

Preparing activity:
Navy - SH
(Project 4330-N001)

AMSC N/A FSC 4330

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T21:48Z
Check the source to verify that this is the current version before use.