MILITARY SPECIFICATION

TURBINE, STEAM AND REDUCTION GEAR,

AUXILIARY, GENERATOR-DRIVE (NAVAL

SHIPBOARD USE)

This amendment forms a part of Military Specification MIL-T-24398(SHIPS), dated 29 January 1971.

PAGE 2

2.1, under "SPECIFICATIONS, MILITARY" delete: "MIL-P-15137 - Provisioning Technical Documentation For Repair Parts For Electrical and Mechanical Equipment (Naval Shipboard Use)."

PAGE 3

2.1, under "STANDARDS, MILITARY" add: "MIL-STD-1552 - Provisioning Technical Documentation, Uniform DOD Requirements for." and "MIL-STD-1561 - Provisioning Procedures, Uniform DOD.".

PAGE 4

2.2, under "AMERICAN NATIONAL STANDARDS INSTITUTE (ANSI)" add: "B16.5 - Steel Pipe Flanges and Flanged Fittings.".

PAGE 14

3.2.7: Add as item (i):

"(i) Lead or lead containing lubricants shall not be used on assembly or parts in steam path."

PAGE 24

3.4.32.4: Delete and substitute:

"3.4.32.4 Other component piping and connections. Other component piping and connections may be welded, if take-down joint is not required for maintenance and overhaul. Where take-down joint is required, it shall be flanged using male-female flanges or it shall have a straight thread adapter with O-rings and O-ring face seal type unions (CPV Mark VIII or equal). The wall thickness of tubing used shall be not less than 0.065 inch in sizes above 1/2 inch. Where flanges are used in oil piping, male-female flanges conforming to ANSI B16.5 shall be used. Tapered pipe threads shall not be used. Steel socket welding fittings in accordance with ANSI B16.11, schedule 40, may be used for 50 p.s.i. self-contained lube oil systems. Face-feed silver-braze fittings in sizes 1/2 inch and above shall not be used. Only preinserted ring fittings shall be used in sizes 1/2 inch and above. Face-feed fittings may be used in sizes below 1/2 inch. Brazing shall be accomplished in accordance with NAVSHIPS 0900-001-7000. Mechanical flareless (bite-type) fittings shall not be used."

3.4.34, add: "Only unclassified information is to be contained on identification plates."

PAGE 59

3.12: Delete and substitute:

"3.12 Equipment variations. Equipment which does not conform to contractual requirements shall be handled in accordance with the provisions of the contract. Other variations, which result in conforming equipment but constitute deviations from the approved configuration, materials, or processes, shall be handled in accordance with the procedures set forth hereinafter. Specific examples of these are as follows:

(a) Manufacturing errors which necessitate special repair procedures or the use of non-standard repair parts.
(b) An improperly-applied process procedure or a substitute process which does not adversely affect the end use of the part or assembly involved.

FSC 2825

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T21:46Z
Check the source to verify that this is the current version before use.

"3.12.1 Disposition. Variations which affect installation, operation, performance, maintainability, repair parts (onboard and shore based), or interchangeability of parts that would be repaired or replaced during maintenance of the equipment require Government approval.

"3.12.2 Conditions for acceptance of parts having variations. Variations will be considered for approval under the following conditions:

(a) The effect of the variation, either as-is or with the part modified, is technically acceptable to the Government.
(b) The nature of the part involved is such that replacement is not economically justified.
(c) Where parts involved are normally onboard repair parts, three of each such non-standard parts or sets of parts shall be furnished at contractor's expense, consisting of one of each as onboard repair parts and two of each as stock repair parts.
(d) Where parts involved are normally stock repair parts but not onboard repair parts, two of each such special parts or sets of parts shall be furnished at contractor's expense as stock repair parts.
(e) The repair parts furnished in accordance with (c) and (d) shall consist of the lowest echelon of the parts required to compensate for the variation. For example, the major parts in which the basic error is made, need not necessarily be furnished; if a rotor bearing journal is machined undersize necessitating the installation of a non-standard bearing, spare non-standard bearings shall be furnished, but a spare non-standard rotor need not be furnished.
(f) Separate provisioning documentation for non-standard repair parts shall be submitted in accordance with MIL-STD-1552 and MIL-STD-1561. The component involved shall be identified by ship, unit, component serial number, and shown at "NO CHARGE" in the documentation.
(g) An equipment variation summary drawing, together with certification that resultant special parts have been furnished, shall be submitted for all variations permitted herein under each contract.
(h) Where the variation results in additional cost to the Government to accommodate a non-standard Government furnished material (GFM) item, such as additional shipyard costs for installation, the contractor shall reimburse the Government for the total amount of such costs involved.
(i) The requirements of (c) and (d) apply only where the variation affects interchangeability.

"3.12.3 Procedure for approval of variations. The following shall be used for approval of variations:

(a) Variations shall be referred to NAVSEA for approval via the local Government inspector within thirty days after occurrence. Submittals shall be in the same manner as established for obtaining drawing approval which on shipbuilder furnished equipment, will require submittal via the shipbuilder and cognizant supervisor. While on Government furnished equipment (GFE), submittals shall be made via local inspector directly to NAVSEA. Any work done on equipment with variations prior to obtaining Government approval shall be at the contractor's risk.
(b) Each variation referred to NAVSEA shall be accompanied by a letter report containing:
    (1) The contract number and item involved.
    (2) The date on which the variation was discovered.
    (3) The circumstances or conditions under which the variation occurred.
    (4) A complete description (including sketch or drawing to scale) of the nature and extent of the variation.
    (5) The corrective measures proposed.
        a. For the part or parts containing variations.
        b. To prevent the recurrence of similar variations.
    (6) The effect of the variation (as corrected) on performance, endurance, stress levels, and parameters cited in 3.12.1, including:
        a. Detailed engineering basis for acceptance.
        b. Certification of the part or parts as corrected.
    (7) Identification of the benefit to the Government, if variation is accepted as modified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T21:46Z
Check the source to verify that this is the current version before use.

(c) Copies of all correspondence involving repair parts shall be forwarded to Ships Parts Control Center, Code 521, Mechanicsburg, PA 17055."

3.13 and 3.14: Delete.

PAGE 60

Add as paragraph 3.16:

"3.16 Workmanship and quality control records. Machinery errors and equipment variations which do not require Government approval (see 3.12.1) (such as non-significant and non-critical deviations from drawing dimensions or tolerances for castings, forgings, weldments, connections, or machine-processed parts) shall be documented, and a copy shall be furnished to the local Government inspector. If the inspector considers that an unclassified deviation does involve contractural requirements, then such deviation shall be classified and treated in accordance with 3.12 through 3.12.3. When a repair restores a part to original drawing dimensions, but involves no change of materials and uses a previously-approved repair process, the local Government inspector shall approve such repair. There shall be periodic reviews between the manufacturer and the inspection activity on the accumulated incidents of machining errors for determination of corrective measures to improve workmanship. The frequency and timing of such reviews shall be as determined by the inspector."

Preparing activity:
Navy - SH
(Project 2825-N015)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T21:46Z
Check the source to verify that this is the current version before use.